

Kit Revision Date: 09 March 2020

# 8329TFF THERMALLY CONDUCTIVE EPOXY ADHESIVE KIT

# **MG Chemicals Multipart Product Kit**

This product is a kit made up of multiple parts. Each part is an independently packaged chemical component and has independent hazard assessments.

#### **Kit Content**

Part	Product Name	Product Use
Α	8329TFF-A	Thermally conductive adhesive resin
В	8329TFF-B	Thermally conductive adhesive hardener

Safety Data Sheets for each part listed above follow this cover sheet.

# **Transportation Instruction**

Before offering this product kit for transport, read Section 14 for <u>all</u> parts listed above.



8329TFF-A

(PART A)

# Safety Data Sheet

#### Section 1: Identification

#### **Product Identifier and Other Means of Identification**

**Product Identifier: 8329TFF-A** 

Other Means of Identification: Thermally Conductive Epoxy Adhesive

Related Part # 8329TFF-25ML, 8329TFF-50ML

#### Recommended Use and Restriction on Use

**Use:** Thermally conductive adhesive resin

**Uses Advised Against:** Not for use as a spray coating

#### **Details of Manufacturer or Importer**

#### Manufacturer

MG Chemicals 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA

+1-800-340-0772 +1-800-340-0773 FAX support@mgchemicals.com E-MAIL **WEB** www.mgchemicals.com

MG Chemicals (Head Office)

9347-193 Street

Surrey, British Columbia V4N 4E7

**CANADA** 

+1-905-331-1396 FAX +1-905-331-2682 info@mgchemicals.com E-MAIL

**E-MAIL** (Competent Person): <a href="mailto:sds@mqchemicals.com">sds@mqchemicals.com</a>

#### **Emergency Phone Number**

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) USA or CANADA—Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service CANADA—Call CANUTEC collect at +1-613-996-6666 or \*666 on cellular phones



(PART A) 8329TFF-A

# Section 2: Hazard(s) Identification

#### **Classification of Hazardous Chemical**

# **GHS Categories**

Criteria		Category	Signal Word	Pictograms
Sensitization	Skin	1	Warning	Exclamation
Eye Irritation		2	Warning	Exclamation
Skin Irritation		2	Warning	Exclamation
Reproductive Toxicity		2	Warning	Health
Hazardous to the Aquatic Environment	Acute	1	Warning	Environment
Hazardous to the Aquatic Environment	Chronic	2	none	Environment

Note: The degree of severity is ranked within each hazard class from

1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

#### **Label Elements**

Signal Word	WARNING
Pictograms	Hazard Statements
^	H317: May cause an allergic skin reaction
	H319: Causes serious eye irritation
	H315: Causes skin irritation
	H361: Suspected of damaging fertility or the unborn child
	H400: Very toxic to aquatic life
***	H411: Toxic to aquatic life with long lasting effects

Section continued on the next page

Page **2** of **15** 



SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-A (PART A)

#### Continued..

Precautionary Statements
Keep out of reach of children.
Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
Avoid breathing fumes/vapors.
Wear protective gloves/protective clothing/eye protection.
Wash hands and exposed skin thoroughly after handling.
Contaminated work clothing should not be allowed out of the workplace.
Avoid release to the environment.
Precautionary Statements
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN: Wash with plenty water.
If skin irritation or rash occurs: Get medical advice/attention.
IF exposed or concerned: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
Collect spillage.
Precautionary Statements
Store locked up.
Processia nome Statements
Precautionary Statements

# **Hazards Not Otherwise Classified**

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None



Burlington, Ontario, Canada

8329TFF-A (PART A)

# **Section 3: Composition/Information on Ingredients**

CAS #	Chemical Name	%(weight)
21645-51-2	aluminum trihydrate	54%
28064-14-4	phenol, polymer with formaldehyde, glycidyl ether	36%
138265-88-0	zinc borate	7%
17557-23-2	neopentyl glycol diglycidyl ether	3%

# Section 4: First-Aid Measures

Exposure Condition	GHS Code/Symptoms/Precautionary Statements
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	redness, serious irritation, pain
Response	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	If eye irritation persists: Get medical advice/attention.
IF ON SKIN	P302 + P352, P333 + P313, P362 + P364
Immediate	redness, irritation, allergic contact dermatitis
Response	Wash with plenty water.
	If skin irritation or rash occurs: Get medical advice/attention.
	Take off contaminated clothing and wash it before reuse.
IF INHALED	P304 + P340
Immediate Symptoms	cough, sore throat
Response	Remove person to fresh air and keep comfortable for breathing.
IF SWALLOWED	P301 + P330 + P331, P308 + P313
Immediate Symptoms	irritation, abdominal pain, diarrhea, nausea, vomiting
Response	Rinse mouth. Do NOT induce vomiting.
	IF exposed or concerned: Get medical advice/attention.

SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-A (Part A)

# **Section 5: Fire-Fighting Measures**

**Extinguishing Media** In case of fire: Use extinguishing media suitable for surrounding

materials.

**Specific Hazards** Not flammable or combustible, but burns if involved in a fire.

Produces irritating smoke of unknown toxicity in fires.

Prevent fire-fighting wash from entering waterway or sewer

system.

**Combustion Products** Produces carbon oxides (CO, CO<sub>2</sub>), nitrogen oxides, boron

oxides, and toxic metal fumes.

**Fire-Fighter** Wear self-contained breathing apparatus and full fire-fighting

turn-out gear.

#### **Section 6: Accidental Release Measures**

**Personal Protection** See personal protection recommendations in Section 8.

**Precautions for Response** 

Avoid breathing the fumes/vapors. Remove or keep away all

sources of extreme heat or open flames.

Environmental Precautions

Avoid releasing to the environment. Prevent spill from entering

drains and waterways.

**Containment Methods** Contain with inert and non-flammable absorbent (such as soil,

sand, vermiculite).

**Cleaning Methods** Collect liquid in a sealable, chemical-resistant container. Sprinkle

inert absorbent compound onto spill, then sweep into the container. Wash the spill area with soap and water to remove

remaining residues.

**Disposal Methods** Dispose of spill waste according to Section 13.

SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-A (Part A)

# Section 7: Handling and Storage

**Prevention** Keep out of reach of children.

Obtain special instructions before use. Do not handle until all

safety precautions have been read and understood.

Avoid breathing fumes/vapors. Contaminated work clothing

should not be allowed out of the workplace.

Avoid release to the environment.

**Handling** Wear protective gloves/eye protection. Wash hands and exposed

skin thoroughly after handling. Take off contaminated clothing

and wash it before reuse.

Collect spillage.

**Storage** RECOMMENDATION: Keep in a dry and clean area, away from

incompatible substances.

#### **Section 8: Exposure Controls/Personal Protection**

# **Substances with Occupational Exposure Limit Values**

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
aluminum metal and insoluble compounds <sup>a)</sup>	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	1 mg/m <sup>3</sup> 15 mg/m <sup>3</sup> 10 mg/m <sup>3</sup> 1 mg/m <sup>3</sup> 1 mg/m <sup>3</sup>	Not established Not established Not established Not established Not established Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS<sup>2</sup> database and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Respirable airborne particles.

Section continued on the next page



SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-A (Part A)

#### **Engineering Controls**

**Ventilation** Keep airborne concentrations below the occupational exposure

limits (OEL).

#### **Personal Protective Equipment**

**Eye protection** Wear appropriate protective eyeglasses or chemical safety

goggles.

**RECOMMENDATION:** Ensure that glasses have side shields for

lateral protection.

**Skin Protection** For likely contacts, use of protective butyl rubber, latex,

neoprene, or other chemically resistant gloves.

For incidental contacts, use nitrile, latex, neoprenee or other

chemically resistant gloves.

**Respiratory Protection** For over-exposures up to 10 x OEL of vapors, wear respirator

such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator

or a self-contained breathing apparatus.

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with

an independent air supply.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3.

The respirator should be fitted to the employee by a

professional. Ensure vapor cartridges are stored in sealed plastic

bags when not being used.

# **General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.

SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-A (PART A)

#### **Section 9: Physical and Chemical Properties**

Physical State	Liquid	Lower Flammability Limit	Not available
Appearance	Beige	Upper Flammability Limit	Not available
Odor	Slight	Vapor Pressure @20°C	Not available
Odor Threshold	Not available	Vapor Density	Not available
pH	Not available	Relative Density @25 °C	1.71
Freezing/Melting Point	Not available	Solubility in Water	Insoluble
Initial Boiling Point <sup>a)</sup>	>150 °C [302 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point a)	150 °C [302 °F]	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability	Non Flammable	Viscosity @40 °C	>20.5 mm <sup>2</sup> /s

a) Values for the component with the lowest reported boiling point.

# **Section 10: Stability and Reactivity**

Reacts exothermically with amines. Reactivity

**Chemical Stability** Chemically stable at normal temperatures and pressures.

**Conditions to** Avoid ignition sources, open flames, and incompatible substances. Do Avoid not use in away that forms mist or aerosolizes the product.

Incompatibilities Avoid strong oxidizing agents, strong acids, strong bases, amines,

and strong reducing agents.

**Polymerization** Will not occur

Will not decompose under normal conditions. For thermal **Decomposition** 

decomposition, see combustion products in Section 5.

SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-A (PART A)

#### **Section 11: Toxicological Information**

#### **Summary of Effects and Symptoms by Routes of Exposure**

**Eyes** May cause redness, serious irritation, or pain.

**Skin** Causes skin redness, irritation, dry skin, or allergic contact dermatitis.

**Inhalation** May cause cough and respiratory irritation, and cough.

Ingestion May cause irritation, abdominal pain, diarrhea, nausea, or vomiting.Chronic Prolonged and repeated exposure may lead to skin sensitization.

# **Acute Toxicity (Lethal Exposure Concentrations)**

Chemical Name	LD50	LD50	LC50
	oral	dermal	inhalation
aluminum trihydrate	>2 000 mg/kg	Not	Not
	Rat	available	available
phenol, polymer with formaldehyde, glycidyl ether	>2 000 mg/kg <sup>a)</sup>	>2 000 mg/kg <sup>a)</sup>	Not available
zinc borate	>10 000 mg/kg	>10 000 mg/kg	Not
	Rat	Rabbit	available
neopentyl glycol diglycidyl	2 000 mg/kg	2 150 mg/kg	Not
ether	Rat <sup>a)</sup>	Rabbit <sup>a)</sup>	available

*Note:* Toxicity data from the RTECS<sup>2</sup> and ECHA databases were consulted. The data from supplier (M)SDS were also consulted.

a) Supplier SDS

#### **Other Toxicological Effects**

Skin corrosion/irritation	Phenol, polymer with formaldehyde, glycidyl ether and neopentyl glycol diglycidyl ether are known skin irritants.
Serious eye damage/irritation	Phenol, polymer with formaldehyde, glycidyl ether causes serious eye irritation.
Sensitization (allergic reactions)	May cause skin sensitization based on animal studies due to the epoxy components.
Carcinogenicity (risk of cancer)	Not classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.

Section continued on the next page

Page **9** of **15** 



SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-A (PART A)

Mutagenicity Based on available data, the classification criteria are not

(risk of heritable genetic effects) met

**Reproductive Toxicity**Animal ingestion studies show that high doses of zinc (risk to sex functions)
borate cause reproductive and developmental effects.

**Teratogenicity** Based on available data, the classification criteria are not

(risk of fetus malformation) me

**STOT-single exposure** Based on available data, the classification criteria are not

met

**STOT-repeated exposure** Based on available data, the classification criteria are not

met

**Aspiration hazard** There are no category 1 components, and the kinematic

viscosity is >20.5 mm<sup>2</sup>/s at 40 °C.

#### Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<a href="http://echa.europa.eu">http://echa.europa.eu</a>), and other reliable sources.

In Europe, similar epoxy resin mixtures with CAS# 28064-14-4 are generally classified as chronic category 2 marine pollutant due to LC50 96 h of >1 mg/L but  $\leq 10$  mg/L.

Zinc borate is classified as a chronic category 1 environmental toxicant with a M-Factor of 1 (with minimal LC50 96 h of 2.4 mg/L for Oncorhhynchus mykiss (rainbow trout); LC50 48 h of 76 mg/L Daphnia magna (water flea); and transformation/dissolution endpoint for zinc borate powder that release of 0.452 mg/L of zinc ion, which is higher than zinc's NOEC limit).

Based on available data, aluminum trihydrate, and neopentyl glycol diglycidyl ether are not classified as environmental hazard according to GHS criteria.

#### **Acute Ecotoxicity**

Category 1

Very toxic to aquatic life

#### **Chronic Ecotoxicity**

Category 2

Toxic to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

Section continued on the next page

Page **10** of **15** 



SAI Global File #004008

Burlington, Ontario, Canada

8329TFF-A (PART A)

#### **Biodegradability**

Not readily biodegradable

#### **Bioaccumulation**

Not available

#### Other Effects

Not available

#### **Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, national, and international regulations.

# **Section 14: Transport Information**

#### Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); USA DOT 49 CFR (Parts 100 to 185) Regulations.

TDG: Sizes under 450 L

Cat No. 8329TFF-25ML, 8329TFF-50ML

**NOT REGULATED** in TDG per Special Provisions 99

49 CFR: Sizes 5 L and

under

**NOT REGULATED** in 49 CFR per exception 171.4 (c)(2)

49 CFR: Sizes greater than 5 kg

FOR REFERENCE ONLY

UN number: UN3082

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (zinc borate; phenol, polymer with

formaldehyde, glycidyl ether)

Class: 9

Packing Group: III Marine Pollutant: Yes

Special Provision 99 (2): These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

Section continued on the next page

Page **11** of **15** 



SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-A (Part A)

#### Air

#### Refer to ICAO-IATA regulations.

Sizes 5 L and under:

Cat. No. 8329TFF-25ML, 8329TFF-50ML

**NOT REGULATED** 

On air waybill, write:

"Not Restricted, as per Special

Provisions A197"

**Special Provision A197**: These substances when transported in single or combination packagings containing net quantity per single or inner packaging of less than 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

#### Sea

#### Refer to IMDG regulations.

Sizes 5 L and under:

Cat. No. 8329TFF-25ML, 8329TFF-50ML

NOT REGULATED

per 2.10.2.7

**2.10.2.7**: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provision of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this Code relevant to any additional hazards continue to apply.

*Note:* Shipper must be appropriately <u>trained and certified</u> before involvement with the transport of dangerous goods.



8329TFF-A (PART A)

#### **Section 15: Regulatory Information**

#### Canada

#### **Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL.

#### Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

#### USA

#### **Other Classifications**

#### **HMIS® RATING**

HEALTH:	*	2
FLAMMABILITY:		1
PHYSICAL HAZARD:		1
PERSONAL PROTECTION:		

#### NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

#### **CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

**EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain substances, which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

**TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any of the listed substances.

Section continued on the next page

Page **13** of **15** 



SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-A (PART A)

#### **Europe**

**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

#### **Section 16: Other Information**

**SDS Prepared by** MG Chemical's Regulatory Department

Date of Review 09 March 2020 Supersedes 22 May 2018

**Reason for Changes:** Update to the emergency phone number information.

#### Reference

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Section continued on the next page

SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-A (PART A)

#### **Abbreviations**

ACGIH American Conference of Governmental Industrial Hygienists (USA)

EC50 Half maximal effective concentration

EL50 Half maximal effective loading

IARC International Agency for Research on Cancer

NOELR No observable effect loading ratio NTP National Toxicology Program

GHS Globally Harmonized System of Classification of Labeling of Chemicals

LC50 Lethal Concentration 50%

LCLo Lowest published lethal concentration

LD50 Lethal Dose 50%

OEL Occupational Exposure Limit
PEL Permissible Exposure Limit

SDS Safety Data Sheet

STEL Short-Term Exposure Limit

TCLo Lowest published toxic concentration

TWA Time Weighted Average VOC Volatile Organic Content

**Technical Queries** Contact us regarding any questions, improvement suggestions, or

problems with this product. Application notes, instructions, and FAQs

are located at www.mgchemicals.com.

Email: support@mqchemicals.com

Mailing Addresses Manufacturing & Support Head Office

1210 Corporate Drive 9347–193rd Street


Burlington, Ontario, Canada Surrey, British Columbia, Canada

L7L 5R6 V4N 4E7+

**Disclaimer** This safety data sheet is provided as an information resource only.

*M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional,

national, and international regulations.





8329TFF-B

(PART B)

# Safety Data Sheet

#### Section 1: Identification

#### **Product Identifier and Other Means of Identification**

**Product Identifier: 8329TFF-B** 

Other Means of Identification: Thermally Conductive Epoxy Adhesive

Related Part # 8329TFF-25ML, 8329TFF-50ML

#### Recommended Use and Restriction on Use

**Use:** Thermally conductive adhesive hardener

**Uses Advised Against:** Not for use as a spray coating

#### **Details of Manufacturer or Importer**

#### Manufacturer

MG Chemicals 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA

+1-800-340-0772 +1-800-340-0773 FAX support@mgchemicals.com E-MAIL **W**EB www.mgchemicals.com

MG Chemicals (Head Office)

9347-193 Street

Surrey, British Columbia V4N 4E7

CANADA

+1-905-331-1396 +1-905-331-2682 FAX E-MAIL

info@mqchemicals.com

**E-MAIL** (Competent Person): sds@mqchemicals.com

#### **Emergency Phone Number**

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) USA or CANADA—Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service CANADA—Call CANUTEC collect at +1-613-996-6666 or \*666 on cellular phones

8329TFF-B

(PART B)

# **Section 2: Hazard(s) Identification**

#### **Classification of Hazardous Chemical**

#### **GHS Categories**

Criteria		Category	Signal Word	Pictograms
Skin Corrosion		1	Danger	Corrosion
Eye Damage		1	Danger	Corrosion
Sensitization	Skin	1	Warning	Exclamation
Hazardous to the Aquatic Environment	Chronic	3	none	none

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

#### **Label Elements**

Signal Word	DANGER		
Pictograms	Hazard Statements		
	H314: Causes severe skin burns and eye damage		
	H317: May cause an allergic skin reaction		
No symbol mandatory	H412: Harmful to aquatic life with long lasting effects		

Section continued on the next page

Page 2 of 14



SAI Global File #004008 Burlington, Ontario, Canada


8329TFF-B (PART B)

Continued ...

Prevention	Precautionary Statements
P102	Keep out of reach of children.
P260	Do not breathe fumes or vapors.
P280	Wear protective gloves, protective clothing, and eye protection.
P264	Wash hands and exposed skin thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
Response	Precautionary Statements
P310	For all routes of exposure: Immediately call a POISON CENTER or doctor.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303 + P361 + P364 + P352	IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash it before reuse. Wash skin with plenty of water [or shower]
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Storage	Precautionary Statements
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of container in accordance to local, regional, and international regulations.

# **Hazards Not Otherwise Classified**

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None





8329TFF-B

(PART B)

Section 3: Composition/Information on Ingredients			
CAS #	Chemical Name	%(weight)	
21645-51-2	aluminum trihvdrate	50%	

pentaerythritol-PO-mercaptoglycerol~ 42% 72244-98-5 2,4,6-tris(dimethylaminomethyl)phenol 90-72-2 8%

# **Section 4: First-Aid Measures**

Exposure Condition	GHS Code: Precautionary Statement
IF IN EYES	P305 + P351 + P338, P310
Immediate Symptoms	redness, burns, pain
Response	Rinse cautiously with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	Immediately call a POISON CENTER or doctor.
IF ON SKIN (or hair)	P303 + P361 + P352, P310, P333 + P313, P363
Immediate Symptoms	redness, allergic contact dermatitis, burns
Response	Take off immediately all contaminated clothing. Wash skin with plenty of water [or shower].
	Immediately call a POISON CENTER or doctor.
	If skin irritation or rash occurs: Get medical advice or attention.
	Wash contaminated clothing before reuse.
IF INHALED	P304 + P340, P310
Immediate Symptoms	cough, irritation of the respiratory track
Response	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	Immediately call a POISON CENTER or doctor.
IF SWALLOWED	P301 + P330 + P331, P310
Immediate Symptoms	burns to mouth and throat, abdominal pain
Response	Rinse mouth. Do NOT induce vomiting.
	Immediately call a POISON CENTER or doctor.



SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-B (Part B)

# **Section 5: Fire-Fighting Measures**

**Extinguishing Media** In case of fire: Use extinguishing media suitable for surrounding

materials.

**Specific Hazards** Not flammable or combustible, but burns if involved in a fire.

Produces irritating smoke of unknown toxicity in fires.

Prevent fire-fighting wash from entering waterway or sewer

system.

**Combustion Products** Produces carbon oxides (CO, CO<sub>2</sub>), nitrogen oxides (NO<sub>x</sub>),

sulphur oxides, and toxic metal fumes.

**Fire-Fighter** Wear self-contained breathing apparatus and full fire-fighting

turn-out gear.

# Section 6: Accidental Release Measures

**Personal Protection** Use personal protection recommended in Section 8.

**Precautions for** 

Response

Do not breathe the fumes or vapors.

**Environmental** 

**Precautions** 

Avoid releasing to the environment. Prevent spill from entering

drains and waterways. Do not flush to sewer.

**Containment Methods** 

Contain with inert absorbent (such as soil, sand, vermiculite).

**Cleaning Methods** 

Collect liquid in a sealable container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.

**Disposal Methods** Dispose spill waste according to Section 13.

# Section 7: Handling and Storage

**Prevention** Keep out of reach of children.

Do not breathe fumes or vapors.

Contaminated work clothing should not be allowed out of the

workplace.

Avoid release to the environment.

**Handling** Wear protective gloves, protective clothing, and eye protection.

Take off contaminated clothing and wash it before reuse.

Wash hands and exposed skin thoroughly after handling.

**Storage** Store locked up.

Page **5** of **14** 

SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-B (Part B)

#### **Section 8: Exposure Controls/Personal Protection**

#### **Substances with Occupational Exposure Limit Values**

Chemical Name	Country or Vendor	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
aluminum metal and insoluble compounds <sup>a)</sup>	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	1 mg/m <sup>3</sup> 15 mg/m <sup>3</sup> 10 mg/m <sup>3</sup> 1 mg/m <sup>3</sup> 1 mg/m <sup>3</sup> 10 mg/m <sup>3</sup>	Not established Not established Not established Not established Not established Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA, and Canadian provinces exposure limits were consulted. Limits from the RTECS database² and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are usually for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) As respirable airborne particles.

#### **Engineering Controls**

**Ventilation** Keep airborne concentrations below the occupational exposure

limits (OEL).

#### **Personal Protective Equipment**

**Eye protection** Wear appropriate protective eyeglasses or chemical safety

goggles.

**RECOMMENDATION:** Use safety glasses with lateral protection

(side shields).

**Skin Protection** For likely contacts, use of protective butyl rubber, neoprene, or

other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant

gloves.

Section continued on the next page

SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-B (Part B)

#### **Respiratory Protection**

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

# **General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.

# **Section 9: Physical and Chemical Properties**

Physical State	Liquid	Lower Flammability Limit	Not available
Appearance	Beige to	Upper Flammability	Not
	light yellow	Limit	available
Odor	Mercaptan-like	Vapor Pressure @20°C	Not available
Odor Threshold	Not available	Vapor Density	Not available
рН	Not available	Relative Density @25°C	1.5
Freezing/Melting	Not	Solubility in	Insoluble
Point	available	Water	
Initial Boiling	118 °C	Partition Coefficient n-octanol/water	Not
Point <sup>a)</sup>	[244 °F]		available
Flash Point a)	124 °C	Auto-ignition	365 °C
	[255 °F]	Temperature	[689 °F]
Evaporation	Not	Decomposition	Not
Rate	available	Temperature	available
Flammability	Non Flammable	Viscosity @25 °C	>20.5 mm <sup>2</sup> /s

a) Component with the lowest reported value.



SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-B (PART B)

#### **Section 10: Stability and Reactivity**

**Reactivity** Not available

**Chemical Stability** Chemically stable at normal temperatures and pressures

**Conditions to** A

Avoid excessive heat and incompatible substances.

Avoid

Do not use in a way that forms a mist or aerosolize the product.

**Incompatibilities** Strong oxidizing agents, reducing agents, strong acids and alkalis

metals

**Polymerization** Will not occur

**Decomposition** For thermal decomposition, see combustion products in Section 5.

# **Section 11: Toxicological Information**

#### Summary of Effects and Symptoms by Routes of Exposure

**Eyes** May cause chemical burns, redness and pain.

**Skin** May cause redness, allergic contact dermatitis, and chemical burns.

**Inhalation** Inhalation of vapors or mist may cause cough and irritation of the nose,

throat, and lungs (upper respiratory tract).

**Ingestion** May cause severe irritation and abdominal pain. It is corrosive to the

mouth, throat, esophagus, and stomach. (See inhalation symptoms.)

**Chronic** Prolonged and repeated exposure to uncured epoxy hardener may lead to

skin sensitization.

# **Acute Toxicity (Lethal Exposure Concentrations)**

Chemical Name	LD50	LD50	LC50
	oral	dermal	inhalation
aluminum trihydrate	>2 000 mg/kg	Not	Not
	Rat <sup>a)</sup>	available	available
pentaerythritol-PO-	Not	Not	Not
mercaptoglycerol~	available	available	available
2,4,6-tris	2 169 mg/kg	969 mg/kg	Not
(dimethylaminomethyl)phenol	Rat	Rabbit	available

*Note:* Representative toxicity data from RTECS database<sup>2</sup> and data from supplier SDS were also consulted.

a) Supplier SDS

Section continued on the next page

Page **8** of **14** 

SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-B (PART B)

#### **Other Toxicological Effects**

**Skin corrosion/irritation** Causes severe skin burns. **Serious eye damage/irritation** Causes severe eye damage.

Respiratory and skin

sensitization (allergic reactions) tri

Pentaerythritol-PO-mercaptoglycerol~ and 2,4,6-tris(dimethylaminomethyl)phenol may cause skin

sensitization according to animal studies.

**Carcinogenicity** Not classified or listed as a carcinogen by IARC, ACGIH,

(risk of cancer) CA Prop 65, or NTP.

**Mutagenicity** Based on available data, the classification criteria are

(risk of heritable genetic effects) no

**Reproductive Toxicity**Based on available data, the classification criteria are

(risk to sex functions) not.

**Teratogenicity** Based on available data, the classification criteria are

(risk of fetus malformation) no

**STOT-single exposure** Based on available data, the classification criteria are

not met.

**STOT-repeated exposure** Based on available data, the classification criteria are

not.

**Aspiration hazard** There are no category 1 components, and the kinematic

viscosity is >20.5 mm<sup>2</sup>/s at 40 °C.

#### **Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (http://echa.europa.eu), and other reliable sources.

Based on available data, pentaerythritol-PO-mercaptoglycerol~ and 2,4,6-tris(dimethylaminomethyl)phenol as chronic aquatic hazard category 3.

#### **Acute Ecotoxicity**

Available toxicity data does not meet classification thresholds.

Section continued on the next page

SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-B (Part B)

# **Chronic Ecotoxicity**

Harmful to aquatic life with long lasting effects Avoid release to the environment.

#### **Biodegradability**

Not readily biodegradable

#### **Bioaccumulation**

Not available

#### **Other Effects**

Not available

# **Section 13: Disposal Considerations**

Dispose of contents in accordance with all local, provincial, state, and federal regulations.

#### **Section 14: Transport Information**

#### **Ground**

**Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.** 

Sizes 30 mL and under

Part B of 8329TFF-25ML, 8329TFF-50ML kits

**Excepted Quantity** 

Code **E2** 



\*\* Shipper Name

Section continued on the next page

SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-B

(PART B)

#### Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes 30 mL and under

Part B of 8329TFF-25ML, 8329TFF-50ML kits

**Excepted Quantity** 

Code **E2** 

Class 8

FOR REFERENCE ONLY UN number: UN2735

Shipping Name: AMINES, LIQUID

CORROSIVE, N.O.S. (2,4,6-

tris(dimethylaminomethyl)phenol)

Class: 8

Packing Group: II Marine Pollutant: No

On air waybill, write: "Dangerous Goods in Excepted Quantities".

\*\* Shipper name

#### Sea

#### Refer to IMDG regulations.

Sizes 30 mL and under

Part B of 8329TFF-25ML, 8329TFF-50ML kits

**Excepted Quantity** 

Code **E2** 

Class 8

FOR REFERENCE ONLY UN number: UN2735

**Shipping Name:** AMINES, LIQUID CORROSIVE, N.O.S. (tris-2,4,6-(dimethylaminomethyl) phenol)

Class: 8

**Packing Group**: II Marine Pollutant: No

In transport document, write: "Dangerous Goods in Excepted Quantities".

*Note:* Shipper must be appropriately <u>trained and certified</u> before involvement with the transport of dangerous goods.

<sup>\*\*</sup> Shipper name

SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-B (PART B)

# **Section 15: Regulatory Information**

#### Canada

#### **Domestic Substance List (DSL)/Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL/NDSL.

#### Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

#### USA

#### **Other Classifications**

#### **HMIS® RATING**

# HEALTH: \* 3 FLAMMABILITY: 1 PHYSICAL HAZARD: 0 PERSONAL PROTECTION:

#### NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

#### **CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product does not contain substances, which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

**TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity)

This product does not contain any of the listed substances.

Section continued on the next page

Page **12** of **14** 



SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-B

(PART B)

#### **Europe**

**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

#### **Section 16: Other Information**

**SDS Prepared by** MG Chemical's Regulatory Department

Date of Revision 09 March 2020 Supersedes 02 April 2019

**Reason for Changes:** Update to the emergency phone number information.

#### Reference

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Section continued on the next page

SAI Global File #004008 Burlington, Ontario, Canada

8329TFF-B (PART B)

#### **Abbreviations**

ACGIH American Conference of Governmental Industrial Hygienists (USA)

EC50 Half maximal effective concentration

EL50 Half maximal effective loading

IARC International Agency for Research on Cancer

NOELR No observable effect loading ratio NTP National Toxicology Program

GHS Globally Harmonized System of Classification of Labeling of Chemicals

LC50 Lethal Concentration 50%

LCLo Lowest published lethal concentration

LD50 Lethal Dose 50%

OEL Occupational Exposure Limit
PEL Permissible Exposure Limit

SDS Safety Data Sheet

STEL Short-Term Exposure Limit

TCLo Lowest published toxic concentration

TWA Time Weighted Average VOC Volatile Organic Content

**Technical Queries** Contact us regarding any questions, improvement suggestions, or

problems with this product. Application notes, instructions, and FAQs

are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses Manufacturing & Support Head Office

1210 Corporate Drive 9347–193rd Street

Burlington, Ontario, Canada Surrey, British Columbia, Canada

L7L 5R6 V4N 4E7

**Disclaimer** This safety data sheet is provided as an information resource only.

M.G. Chemicals, Ltd. believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional,

national, and international regulations.