

Page 1/9

### according to WHS Regulations

Printing date 10.04.2024

· Label elements

Version number 4

Revision: 10.04.2024

# 1 Identification · Product identifier Trade name: 8351-Flux · Other Means of Identification: No Clean Flux, Halogen Free · Related Part Number: 8351-Liquid, 8351-125ML, 8351-125MLCA, 8351-1L, 8351-4L, 8351-20L, 8351-55G · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Details of the supplier of the safety data sheet M.G. Chemicals Ltd. · Manufacturer/Supplier: MG Chemicals Ltd. (Head Office) 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA +(1) 800-340-0772 Mektronics Australia Pty Ltd 5 Prince William Drive Seven Hills NSW 2147 Australia www.mektronics.com.au sales@mektronics.com.au · Further information obtainable from: sds@mgchemicals.com · Emergency telephone number: CHEMTREC Australia: + (61) 2-9037-2994 Other emergency telephone number: +(1) 703-527-3887 2 Hazard(s) Identification · Classification of the substance or mixture flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. Serious eye damage/irritation – Category 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

• GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

(Contd. on page 2)

Version number 4 Printing date 10.04.2024 Trade name: 8351-Flux (Contd. of page 1) · Hazard pictograms GHS02 GHS07 · Signal word Danger - Hazard-determining components of labelling: propan-2-ol (15-20 %) · Hazard statements Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness. · Precautionary statements Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use explosion-proof electrical/ventilating/lighting equipment. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · Other hazards

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

# 3 Composition and Information on Ingredients

· Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

#### · Dangerous components:

64-17-5 ethanol 75-80% 🚸 Flam. Lig. 2, H225; 🕔 Serious eye damage/irritation – Category 2A, **H**319 67-63-0 propan-2-ol 15-20%

Flam. Liq. 2, H225; (1) Serious eye damage/irritation – Category 2A, H319; STOT SE 3, H336

• Additional information: For the wording of the listed hazard phrases refer to section 16.

### 4 First Aid Measures

- General information: Immediately remove any clothing soiled by the product.

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

AU

Printing date 10.04.2024

#### Version number 4

Revision: 10.04.2024

(Contd. of page 2)

#### Trade name: 8351-Flux

- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

# 5 Fire Fighting Measures

- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. **Special hazards arising from the substance or mixture**
- Vapors are heavier than air. Vapors may travel to sources of ignition near the ground. They can cause flash fire or ignite explosively.
- · Protective equipment: No special measures required.

# 6 Accidental Release Measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Dilute with plenty of water.
- Do not allow to enter sewers/ surface or ground water. • Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.

# 7 Handling and Storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- *Further information about storage conditions:* Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls and personal protection

• Additional information about design of technical facilities: No further data; see section 7.

(Contd. on page 4)

Printing date 10.04.2024

Version number 4

Revision: 10.04.2024

### Trade name: 8351-Flux

Incredients with limit value	(Contd. of page 3) s that require monitoring at the workplace:
64-17-5 ethanol	s that require monitoring at the workplace.
WES Long-term value: 1880 r	mg/m³, 1000 ppm
67-63-0 propan-2-ol	
Personal protective equipm General protective and hyge Keep away from foodstuffs, be Immediately remove all soiled Wash hands before breaks ar Avoid contact with the eyes. Avoid contact with the eyes an <b>Respiratory protection:</b> In case of brief exposure or let	ng/m <sup>3</sup> , 400 ppm e lists valid during the making were used as basis. <b>nent:</b> <b>ienic measures:</b> everages and feed. I and contaminated clothing and at the end of work.
Protective gloves	
The glove material has to be preparation.	e impermeable and resistant to the product/ the substance/ the
•	mmendation to the glove material can be given for the product/
Selection of the glove materi and the degradation	ial on consideration of the penetration times, rates of diffusion
marks of quality and varies preparation of several substa in advance and has therefore	gloves does not only depend on the material, but also on further s from manufacturer to manufacturer. As the product is a inces, the resistance of the glove material can not be calculated to be checked prior to the application.
<b>Penetration time of glove m</b> The exact break through tim gloves and has to be observe <b>Eye protection:</b>	ne has to be found out by the manufacturer of the protective
Tightly sealed gogg	les
Physical and Chemical	Properties
General Information	
Appearance:	
Form:	Fluid
Colour:	According to product specification

· Odour:

· Odour threshold:

· pH-value:

Fluid According to product specification Characteristic Not determined. Not determined.

(Contd. on page 5)

<sup>—</sup> AU

Printing date 10.04.2024

Version number 4

Revision: 10.04.2024

Trade name: 8351-Flux

ol : ""	(Contd. of page 4)
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	
· Flash point:	12 °C
Flammability (solid, gas):	Highly flammable.
Auto-ignition temperature:	363 ℃
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
<ul> <li>Explosive properties:</li> </ul>	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Explosion limits:	
· Lower:	2 Vol %
· Upper:	15 Vol %
<ul> <li>Vapour pressure at 20 °C:</li> </ul>	59 hPa
<ul> <li>Vapour pressure at 50 ℃:</li> </ul>	280 hPa
· Density at 20 °C:	0.81 g/cm³
· Bulk density:	710–877 kg/m³
· Relative density	Not determined.
· Vapour density	Not determined.
<ul> <li>Evaporation rate</li> </ul>	Not determined.
<ul> <li>Solubility in / Miscibility with</li> </ul>	
· water:	Fully miscible.
<ul> <li>Partition coefficient: n-octanol/water:</li> </ul>	Not determined.
· Viscosity:	
· Dynamic:	Not determined.
<ul> <li>Kinematic at 20 °C:</li> </ul>	3 mm²/s
<ul> <li>Solvent content:</li> </ul>	
<ul> <li>Organic solvents:</li> </ul>	90–100 %
· VOC (EC)	90–100 %
<ul> <li>Solids content:</li> </ul>	0.0 %
· Other information	No further relevant information available.

# 10 Stability and Reactivity

• *Reactivity* No further relevant information available.

- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

### 64-17-5 ethanol

Oral LD50 7,060 mg/kg (rat) Inhalative LC50/4 h 20,000 mg/l (rat)

(Contd. on page 6)

AU

Printing date 10.04.2024

Version number 4

Revision: 10.04.2024

(Contd. of page 5)

Trade name: 8351-Flux

### 67-63-0 propan-2-ol

Oral LD50 5,045 mg/kg (rat)

Dermal LD50 12,800 mg/kg (rabbit)

Inhalative LC50/4 h 30 mg/l (rat)

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation Causes serious eye irritation.

· Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

## 12 Ecological Information

### · Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

# 14 Transport information

- · UN-Number
- · ADG, IMDG, IATA

UN1987

(Contd. on page 7)

AIJ

Printing date 10.04.2024	Version number 4	Revision: 10.04.2024
Trade name: 8351-Flux		
IN proper chipping perce		(Contd. of page 6)
<ul> <li>UN proper shipping name</li> <li>ADG</li> </ul>		S, N.O.S. (ETHANOL (ETHYL OPROPANOL (ISOPROPYL
· IMDG	ALCOHOŰS, N	I.O.S. (ETHANOL (ETHYL OPROPANOL (ISOPROPYL
·IATA		(ETHANOL, ISOPROPANOL .COHOL))
<ul> <li>Transport hazard class(es)</li> </ul>	·	·/
· ADG, IMDG, IATA		
· Class · Label	3 Flammable liqu 3	iids.
· Packing group	0	
· ADG, IMDG, IATA	И	
Environmental hazards:     Special process for use	Not applicable. Pr Warning: Flamma	abla liquida
<ul> <li>Special precautions for use</li> <li>Hazard identification numb</li> </ul>		able liquids.
code):	33	
EMS Number:	F-E,S-D	
Stowage Category     Transport in bulk according	B a to Appen II of	
<ul> <li>Transport in bulk according Marpol and the IBC Code</li> </ul>	Not applicable.	
· Transport/Additional inform		
ADG		
<ul> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	1L Code: E2	
· Excepted quantities (EQ)		antity per inner packaging: 30
	ml	
	Maximum net qu ml	antity per outer packaging: 500
· Transport category	2	
Tunnel restriction code	D/E	
·IMDG		
Limited quantities (LQ)	1L	
<ul> <li>Excepted quantities (EQ)</li> </ul>	Code: E2 Maximum pet qu	antity per inper packaging: 20
	maximum net qu ml	antity per inner packaging: 30
	Maximum net qu	antity per outer packaging: 500
· UN "Model Regulation":		DHOLS, N.O.S. (ETHANOL OHOL), ISOPROPANOL

(Contd. on page 8)

Printing date 10.04.2024

Version number 4

Revision: 10.04.2024

Trade name: 8351-Flux

(Contd. of page 7)

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Australian Inventory of Industrial Chemicals All ingredients are listed.
- · Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

Australia: Priority Existing Chemicals

None of the ingredients is listed.

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS). • **Hazard pictograms** 



· Signal word Danger

- *Hazard-determining components of labelling:* propan-2-ol (15–20 %)
- Hazard statements Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

#### • **Precautionary statements** Keep out of reach of children.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

*IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.* 

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

(Contd. on page 9)

Printing date 10.04.2024

Version number 4

Revision: 10.04.2024

### Trade name: 8351-Flux

(Contd. of page 8) H336 May cause drowsiness or dizziness. · Department issuing SDS: Product safety department. · Contact: sds@mgchemicals.com · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Serious eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 \* Data compared to the previous version altered. AU