SAI Global File #004008 Burlington, Ontario, Canada

8309-P

CONFORMAL COATING STRIPPER PEN

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: 8309-P

Other Means of Identification: Conformal Coating Remover - Pen

Related Part # 8309-P

Recommended Use and Restriction on Use

Use: Coating stripper

Uses Advised Against: Not applicable

Details of Manufacturer or Importer

Manufacturer

MG Chemicals 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA

E-MAIL <u>support@mgchemicals.com</u> **WEB** <u>www.mgchemicals.com</u>

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) USA or CANADA—Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service CANADA—Call CANUTEC collect at +1-613-996-6666 or *666 on cellular phones

SAI Global File #004008 Burlington, Ontario, Canada

8309-P

CONFORMAL COATING STRIPPER PEN

Section 2: Hazard(s) Identification

Classification of Hazardous Chemical

GHS Categories

Criteria		Category	Signal Word	Pictograms
Flammable Liquid		2	Danger	Flame
Eye Irritation		2	Warning	Exclamation
Specific Target Organ Toxicity	Single Exposure	3	Warning	Exclamation

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity). Severity categories rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H225: Highly flammable liquid and vapor
	H319: Causes serious eye irritation
	H336: May cause drowsiness or dizziness
Prevention	Precautionary Statements
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking.
P261	Avoid breathing vapors.
P271	Use only outdoors or a in well-ventilated area.
P280	Wear protective gloves.
P264	Wash hands thoroughly after handling.

Section continued on the next page

Page 2 of 14



SAI Global File #004008 Burlington, Ontario, Canada

8309-P

CONFORMAL COATING STRIPPER PEN

Continued...

Response	Precautionary Statements
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P304 + P340, P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell.
Storage	Precautionary Statements
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
67-64-1	acetone	50%
646-06-0	1,3-dioxolane	34%
109-87-5	dimethoxymethane	16%



SAI Global File #004008 Burlington, Ontario, Canada

8309-P

CONFORMAL COATING STRIPPER PEN

Section 4: First-Aid Measures				
Exposure Condition	GHS Code: Precautionary Statement			
IF ON SKIN (or hair)	P303 + P361 + P353			
Immediate Symptoms	dry skin, redness, pain, (see also inhalation symptoms)			
Response	Take off immediately all contaminated clothing. Rinse skin with water or shower.			
IF IN EYES	P305 + P351 + P338, P337 + P313			
Immediate Symptoms	severe irritation, redness, pain, blurred vision			
Response	Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.			
	If eye irritation persists: Get medical advice or attention			
IF INHALED	P304 + P340, P312			
IF INHALED Immediate Symptoms	P304 + P340, P312 cough, sore throat, headache, drowsiness, dizziness, confusion, unconsciousness			
	cough, sore throat, headache, drowsiness, dizziness, confusion,			
Immediate Symptoms	cough, sore throat, headache, drowsiness, dizziness, confusion, unconsciousness Remove person to fresh air (out of the contaminated zone) and			
Immediate Symptoms	cough, sore throat, headache, drowsiness, dizziness, confusion, unconsciousness Remove person to fresh air (out of the contaminated zone) and keep comfortable for breathing.			
Immediate Symptoms Response	cough, sore throat, headache, drowsiness, dizziness, confusion, unconsciousness Remove person to fresh air (out of the contaminated zone) and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell.			
Immediate Symptoms Response IF SWALLOWED	cough, sore throat, headache, drowsiness, dizziness, confusion, unconsciousness Remove person to fresh air (out of the contaminated zone) and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell. P301 + P330, P331, P308 + P313 nausea, weakness, abdominal pain, vomiting, (see also			

Section	5: Fire-F	iahtina	Measures
Occilon	J. I II C-I	igittiig	Mcasai cs

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
Specific Hazards	The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.
Combustion Products	Produces carbon oxides (CO, CO ₂).
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting

Page **4** of **14**

turn-out gear.



SAI Global File #004008 Burlington, Ontario, Canada

8309-P

CONFORMAL COATING STRIPPER PEN

Section 6: Accidental Release Measures

Personal Protection See personal protection equipment in Section 8.

Precautions for Response

Avoid breathing the vapors. Remove or keep away all sources of

ignition or extreme heat.

Environmental Precautions

Prevent spill from entering drains and waterways.

Containment Not applicable

Cleaning Place inert absorbent pads directly on the spill. Let absorb and

wipe clean. Collect the contaminated pad in a sealable, solvent-resistant container. Wash the spill area with soap and water to

remove remaining residues.

RECOMMENDATION: Use a grounded stainless steel or carbon steel

container.

Disposal Methods Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention Keep out of reach of children.

Keep away from heat, hot surfaces, sparks, flames, and other

ignition sources. No Smoking.

Avoid breathing vapors. Use only outdoors or in a well-ventilated

area.

Keep cap tightly closed.

Handling Wear protective gloves.

Wash hands thoroughly after handling.

Storage Store in a well-ventilated area. Keep cool.

Store locked up.

SAI Global File #004008 Burlington, Ontario, Canada

8309-P

CONFORMAL COATING STRIPPER PEN

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
acetone	ACGIH	500 ppm	750 ppm
	U.S.A. OSHA PEL	1 000 ppm	Not established
	Canada AB	500 ppm	750 ppm
	Canada BC	250 ppm	500 ppm
	Canada ON	500 ppm	750 ppm
	Canada QC	750 ppm	1 000 ppm
1,3-dioxolane	ACGIH a)	20 ppm	Not established
	U.S.A. OSHA PEL	Not established	Not established
	Canada AB	20 ppm	Not established
	Canada BC b)	20 ppm	Not established
	Canada ON	20 ppm	Not established
	Canada QC	Not established	Not established
dimethoxymethane	ACGIH c)	1 000 ppm	Not established
	U.S.A. OSHA PEL	1 000 ppm	3 100 ppm
	Canada AB	1 000 ppm	3 100 ppm
	Canada BC	1 000 ppm	1 250 ppm
	Canada ON	1 000 ppm	Not established
	Canada QC	1 000 ppm	3 110 ppm

Note: The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

- a) Hematologic effect
- b) Adverse reproductive effect
- c) Eye irritation; CNS impairment

Engineering Controls

Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

Section continued on the next page

SAI Global File #004008 Burlington, Ontario, Canada

8309-P

CONFORMAL COATING STRIPPER PEN

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety

goggles.

RECOMMENDATION: Use safety glasses with lateral protection

(side shields).

Skin Protection For incidental contacts, use neoprene, natural latex rubber, or

other chemically resistant gloves.

Respiratory Protection

For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor

cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator

or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when

not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.



SAI Global File #004008 Burlington, Ontario, Canada

8309-P

CONFORMAL COATING STRIPPER PEN

Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit ^{c)}	2.7%
Appearance	Colorless	Upper Flammability Limit ^{c)}	16.5%
Odor	Ketone-like	Vapor Pressure @20 °C ^{b)}	221 hPa [166 mmHg]
Odor Threshold	Not available	Vapor Density	>2.01 (Air = 1)
рН	Not available	Relative Density @25 °C	0.89
Freezing/Melting Point	Not available	Solubility in Water	Miscible
Initial Boiling Point	42 °C [107 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point a)	-30 °C [-22 °F]	Auto-ignition Temperature	250 °C [482 °F]
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability	Flammable	Viscosity @40 °C	<20.5 mm ² /s

a) Closed cup value

b) Calculated using Raoult's Law

c) Calculated using LeChatelier Principal

Section 10: Stability and Reactivity

Reactivity Not available

Chemical Chemically stable at normal temperatures and pressures

Stability

Conditions to Avoid flames, sparks, other ignition sources and incompatible

Avoid substances.

Incompatibilities Phosphorous oxychloride, strong oxidizing agents, strong bases,

strong acids

Polymerization Will not occur

Decomposition Will not decompose under normal conditions. For thermal

decomposition, see combustion products in Section 5.

Page **8** of **14**

SAI Global File #004008 Burlington, Ontario, Canada

8309-P

CONFORMAL COATING STRIPPER PEN

Section 11: Toxicological Information

Summary of Effects and Symptoms by Routes of Exposure

Eyes Causes redness, serious eye irritation, pain and/or blurred vision.

Skin May cause dry skin, redness, and/or pain. (see also inhalation

symptoms).

Inhalation May cause cough, sore throat, headache, drowsiness, dizziness,

and/or confusion. Severe overexposure may lead to

unconsciousness.

Ingestion May cause nausea, weakness, abdominal pain, and/or vomiting.

(see also inhalation symptoms)

Chronic Prolonged or repeated exposure may cause skin dryness,

cracking, as well as defatting the skin.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50	LD50	LC50
	oral	dermal	inhalation
acetone	5 800 mg/kg	20 mL/kg	16 000 ppm
	Rat	Rabbit ^{a)}	4 h Rat ^{a)}
1,3-dioxolane	5 200 mg/kg	15 000 mg/kg	20 650 mg/m³
	Rat	Rat	4 h Rat
dimethoxymethane	6 423 mg/kg	Not	57 mg/L
	Rat	available	7 h Rat

Note: Toxicity data from the ECHA were consulted. The data from supplier SDS were also consulted.

a) Supplier safety data sheet



SAI Global File #004008 Burlington, Ontario, Canada

8309-P

CONFORMAL COATING STRIPPER PEN

Other Toxicological Effects

Skin corrosion/irritationBased on available data, the classification criteria are

not met.

Serious eye Acetone and 1,3-dioxolane are known serious eye

damage/irritation irritants.

Sensitization Based on available data, the classification criteria are

(allergic reactions) not met.

CarcinogenicityNone of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.

Mutagenicity Based on available data, the classification criteria are

(risk of heritable genetic effects) not met.

Reproductive ToxicityBased on available data, the classification criteria are

(risk to sex functions) not met.

Teratogenicity Based on available data, the classification criteria are

(risk of fetus malformation) not met.

STOT-single exposure Acetone can affect the central nervous system by

inhalation causing drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are

not met.

Aspiration hazardBased on available data, the classification criteria are

not met. There are no category 1 components.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (http://echa.europa.eu), and other reliable sources.

Acetone does not meet classification criteria for aquatic environmental toxicants with LC50 and EC50 of >100 mg/L.

 Acetone has a minimal LC50 96 h of 5 540 mg/L for Oncorhynchus mykiss (rainbow trout) and an EC50 48 h of 13 500 mg/L for Daphnia magna (water flea).

1,3-dioxolane and dimethoxymethane is not classifiable as an environmental toxicant.

Acute Ecotoxicity

Available toxicity data does not meet classification thresholds.

Section continue on the next page

Page **10** of **14**



SAI Global File #004008 Burlington, Ontario, Canada

8309-P

CONFORMAL COATING STRIPPER PEN

Chronic Ecotoxicity

Available toxicity data does not meet classification thresholds.

Biodegradability

Not available

Other Effects

Volatile Organic Compound (VOC) content = 50% [446 g/L] by VOC-Exemption

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations**.

Sizes 30 mL and under

Excepted Quantity

Document as class **E2**



FOR REFERENCE ONLY

UN number: UN1993

Shipping Name: Flammable liquid, n.o.s. (acetone, 1,3-dioxolane, dimethoxymethane)

Class: 3

Packing Group: II Marine Pollutant: No

Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes 30 mL and under

Excepted Quantity

Document as class **E2**

On air waybill, write: "Dangerous Goods in Excepted Quantities".



FOR REFERENCE ONLY

UN number: UN1993

Shipping Name: Flammable liquid, n.o.s. (acetone, 1,3-dioxolane, dimethoxymethane)

Class: 3

Packing Group: II Marine Pollutant: No

Section continued on the next page

Page **11** of **14**



SAI Global File #004008 Burlington, Ontario, Canada

8309-P

CONFORMAL COATING STRIPPER PEN

Sea

Refer to IMDG regulations.

Sizes 30 mL and under

Excepted Quantity

Document as class **E2**

Class 3 Shipper name

FOR REFERENCE ONLY

UN number: UN1993

Shipping Name: Flammable liquid, n.o.s. (acetone, 1,3-dioxolane, dimethoxymethane)

Class: 3

Packing Group: II Marine Pollutant: No

Note: Shipper must be appropriately <u>trained and certified</u> before involvement with the transport of dangerous goods.

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

USA

Other Classifications

HMIS® RATING

HEALTH:	*	2
FLAMMABILITY:		3
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

Section continued on the next page

Page **12** of **14**

SAI Global File #004008 Burlington, Ontario, Canada

8309-P

CONFORMAL COATING STRIPPER PEN

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product contains acetone (CAS# 67-64-1), which is subject to the CERCLA reporting requirements at the 5 000 lb (2 268 kg) threshold.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any substances known to be listed in California.

Europe

RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

SDS Prepared by MG Chemical's Regulatory Department

Date of Revision 13 March 2023 Supersedes 06 March 2020

Reason for Changes: Update to other means of identification.

Reference

1) ACGIH 2022 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2022).

Section continued on the next page

Page 13 of 14

SAI Global File #004008 Burlington, Ontario, Canada

8309-P

CONFORMAL COATING STRIPPER PEN

Abbreviations

ACGIH American Conference of Governmental Industrial Hygienists (USA)

ECHA European Chemicals Agency

EU European Union

EC50 Half maximal effective concentration

Half maximal effective loading EL50

IARC International Agency for Research on Cancer

NOELR No observable effect loading ratio NTP National Toxicology Program

Globally Harmonized System of Classification of Labeling of Chemicals GHS

Lethal Concentration 50% LC50

Lowest published lethal concentration LCLo

LD50 Lethal Dose 50%

Occupational Exposure Limit OEL PEL Permissible Exposure Limit

Safety Data Sheet SDS

Short-Term Exposure Limit STEL

Lowest published toxic concentration TCLo

TWA Time Weighted Average Volatile Organic Content VOC

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAOs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses Manufacturing & Support

1210 Corporate Drive

Burlington, Ontario, Canada

L7L 5R6

Disclaimer

This safety data sheet is provided as an information resource only. M.G. Chemicals, Ltd. believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.

Page **14** of **14**