

832B-A

BLACK EPOXY ENCAPSULATING AND POTTING COMPOUND

# Safety Data Sheet

## Section 1: Identification

### Product Identifier and Other Means of Identification

**Product Identifier:** 832B-A**Other Means of Identification:** Black Epoxy Encapsulating and Potting Compound (Part A)**Related Part #** 832B-375ML, 832B-375MLCA, 832B-450ML, 832B-3L, 832B-12L, 832B-60L

### Recommended Use and Restriction on Use

**Use:** Epoxy resin for use with hardeners**Uses Advised Against:** Not for use as a spray coating

### Details of Manufacturer or Importer

**Manufacturer**

MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADA

**☎** +1-800-340-0772  
**FAX** +1-800-340-0773  
**E-MAIL** [support@mgchemicals.com](mailto:support@mgchemicals.com)  
**WEB** [www.mgchemicals.com](http://www.mgchemicals.com)

**☎** +1-905-331-1396  
**FAX** +1-905-331-2682  
**E-MAIL** [info@mgchemicals.com](mailto:info@mgchemicals.com)

**E-MAIL** (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)

### Emergency Phone Number

**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents)  
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**  
(Service access code: 335388)



**For emergencies involving the transport of dangerous goods;** 24/7 service  
CANADA—Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones

**832B-A****BLACK EPOXY ENCAPSULATING AND POTTING COMPOUND****Section 2: Hazard(s) Identification****Classification of Hazardous Chemical****GHS Categories**

Criteria		Category	Signal Word	Pictograms
Sensitization	Skin	1	Warning	Exclamation
Eye Irritation		2	Warning	Exclamation
Skin Irritation		2	Warning	Exclamation
Hazardous to the Aquatic Environment	Chronic	2	<i>none</i>	Environment
Hazardous to the Aquatic Environment	Acute	2	<i>none</i>	<i>none</i>

*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

**Label Elements**

<b>Signal Word</b>	<b>WARNING</b>
<b>Pictograms</b>	<b>Hazard Statements</b>
	H319: Causes serious eye irritation H315: Causes skin irritation H317: May cause an allergic skin reaction
	H411: Toxic to aquatic life with long lasting effects

*Section continued on the next page*

**832B-A**
**BLACK EPOXY ENCAPSULATING AND POTTING COMPOUND**
*Continued...*

<b>Prevention</b>	<b>Precautionary Statements</b>
P102	Keep out of reach of children.
P261	Avoid breathing fumes and vapors.
P280	Wear protective gloves, eye protection, and face protection.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
<b>Response</b>	<b>Precautionary Statements</b>
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

**Hazards Not Otherwise Classified**

<b>Other Criteria</b>	<b>Hazard Statements/Precautionary Statement</b>	<b>Signal Word</b>	<b>Pictograms</b>
None	None	None	None

**832B-A**
**BLACK EPOXY ENCAPSULATING AND POTTING COMPOUND**
**Section 3: Composition/Information on Ingredients**

CAS #	Chemical Name	%(weight)
25085-99-8	propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	88%
68609-97-2	alkyl glycidyl ether	10%
25068-38-6	bisphenol-A epoxy resin (reaction product) <sup>a)</sup>	1.5%
1333-86-4	carbon black	0.4%

a) Average molecular weight of  $\leq 700$

**Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
<b>IF IN EYES</b>	P305 + P351 + P338, P337 + P313
<b>Immediate Symptoms</b>	<i>redness, irritation, pain</i>
<b>Response</b>	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  If eye irritation persists: Get medical advice or attention.
<b>IF ON SKIN</b>	P302 + P352, P333 + P313, P362 + P364
<b>Immediate Symptoms</b>	<i>redness, irritation, dry skin, allergic contact dermatitis</i>
<b>Response</b>	Wash with plenty of water.  If skin irritation or rash occurs: Get medical advice or attention.  Take off contaminated clothing and wash it before reuse.
<b>IF INHALED</b>	P304 + P340, P312
<b>Immediate Symptoms</b>	<i>cough, irritation of the respiratory track</i>
<b>Response</b>	Remove person to fresh air and keep comfortable for breathing.  If you feel unwell: Get medical advice or attention.
<b>IF SWALLOWED</b>	P301 + P330, P331
<b>Immediate Symptoms</b>	<i>low toxicity: irritation</i>
<b>Response</b>	Rinse mouth. Do NOT induce vomiting.

**832B-A****BLACK EPOXY ENCAPSULATING AND POTTING COMPOUND****Section 5: Fire-Fighting Measures**

<b>Extinguishing Media</b>	In case of fire: Use extinguishing media suitable for surrounding materials.
<b>Specific Hazards</b>	Not flammable or combustible, but burns if involved in a fire. Produces irritating smoke of unknown toxicity in fires.  Prevent fire-fighting wash from entering waterway or sewer system.
<b>Combustion Products</b>	Produces carbon oxides (CO,CO <sub>2</sub> ) and toxic fumes.
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

**Section 6: Accidental Release Measures**

<b>Personal Protection</b>	See personal protection recommendations in Section 8.
<b>Precautions for Response</b>	Avoid breathing fumes or vapors. Remove or keep away all sources of extreme heat or open flames.
<b>Environmental Precautions</b>	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
<b>Containment Methods</b>	Contain with inert and non-flammable absorbent (such as soil, sand, vermiculite).
<b>Cleaning Methods</b>	Collect liquid in a sealable, chemical-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wipe off residues with paper towels and place the used towels in the waste container. Use soap and water to remove the last traces of residue.
<b>Disposal Methods</b>	Dispose of spill waste according to Section 13.

**832B-A****BLACK EPOXY ENCAPSULATING AND POTTING COMPOUND****Section 7: Handling and Storage****Prevention**

Keep out of reach of children.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Avoid breathing fumes or vapors or contact with skin or eyes.

Avoid release to the environment.

**Handling**

Wear protective gloves, protective clothing, and eye protection.

Take off contaminated clothing and wash it before reuse.

Contaminated work clothing should not be allowed out of the workplace.

Wash hands thoroughly after handling.

Collect spillage.

**Storage**

DO NOT FREEZE. Store in a clean and dry area between 5 to 35 °C.

**Section 8: Exposure Controls/Personal Protection****Substances with Occupational Exposure Limit Values**

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
carbon black <sup>a)</sup>	ACGIH	3.5 mg/m <sup>3</sup>	Not established
	U.S.A. OSHA PEL	3.5 mg/m <sup>3</sup>	Not established
	Canada AB	3.5 mg/m <sup>3</sup>	Not established
	Canada BC	3 mg/m <sup>3</sup>	Not established
	Canada ON	3.5 mg/m <sup>3</sup>	Not established
	Canada QC	3.5 mg/m <sup>3</sup>	Not established

*Note:* Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS database<sup>2</sup> and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Respirable airborne particles

**832B-A****BLACK EPOXY ENCAPSULATING AND POTTING COMPOUND****Engineering Controls****Ventilation**

General ventilation is adequate for normal use; keep overall exposure as low as possible.

Because the carbon black is bound to the liquid mixture, it does not present an airborne hazard under normal use. Ensure adequate ventilation if the product is mechanically misted or aerosolized.

**Personal Protective Equipment****Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

**RECOMMENDATION:** Ensure that glasses have side shields for lateral protection.

**Skin Protection**

For likely contacts, use of protective butyl rubber or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

**Respiratory Protection**

For emergencies and exposure above  $0.5 \text{ mg/m}^3$ , use a self-contained breathing apparatus with full face piece operated in a pressure positive mode.

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

**General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.

**832B-A**
**BLACK EPOXY ENCAPSULATING AND POTTING COMPOUND**
**Section 9: Physical and Chemical Properties**

<b>Physical State</b>	Liquid	<b>Lower Flammability Limit</b>	Not available
<b>Appearance</b>	Black	<b>Upper Flammability Limit</b>	Not available
<b>Odor</b>	Mild	<b>Vapor Pressure @20 °C</b>	Not available
<b>Odor Threshold</b>	Not available	<b>Vapor Density</b>	>1 (Air=1)
<b>pH</b>	Not available	<b>Relative Density @25 °C</b>	1.13
<b>Freezing/Melting Point</b>	Not available	<b>Solubility in Water</b>	Negligible
<b>Initial Boiling Point</b> <sup>a)</sup>	≥150 °C [≥302 °F]	<b>Partition Coefficient n-octanol/water</b>	Not available
<b>Flash Point</b> <sup>b)</sup>	113 °C [235 °F]	<b>Auto-ignition Temperature</b> <sup>b)</sup>	≥235 °C [≥455 °F]
<b>Evaporation Rate</b>	Not available	<b>Decomposition Temperature</b>	Not available
<b>Flammability</b>	Non flammable	<b>Viscosity @25 °C</b>	1 800 mm <sup>2</sup> /s

a) Component with the lowest value—bisphenol-A epoxy resin (reaction product)

b) Component with the lowest value— alkyl glycidyl ether closed cup

**Section 10: Stability and Reactivity**

<b>Reactivity</b>	Reacts exothermically with amines.
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures
<b>Conditions to Avoid</b>	Ignition sources, open flames, and incompatible substances
<b>Incompatibilities</b>	Strong oxidizing agents, strong acids, alkaly
<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.



**832B-A****BLACK EPOXY ENCAPSULATING AND POTTING COMPOUND****Section 11: Toxicological Information****Summary of Effects and Symptoms by Routes of Exposure**

<b>Eyes</b>	May cause redness, severe irritation, or pain.
<b>Skin</b>	May cause skin redness, irritation, dry skin, or allergic contact dermatitis.
<b>Inhalation</b>	May cause cough and respiratory irritation.
<b>Ingestion</b>	Low toxicity: may cause irritation. (See inhalation symptoms).
<b>Chronic</b>	Prolonged and repeated exposure may lead to skin sensitization.

**Acute Toxicity (Lethal Exposure Concentrations)**

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	Not available	23 000 mg/kg Rat	Not available
alkyl glycidyl ether	19 200 mg/kg Rat	4 500 mg/kg Rat	Not available
reaction products: bisphenol-A-(epichlorohydrin) and epoxy resin <sup>a)</sup>	11 400 mg/kg Rat	Not available	Not available
carbon black	>15 g/kg Rat	>3 g/kg Rabbit	Not available

*Note:* Toxicity data from the ECHA database were consulted. The data from supplier SDS were also consulted.

a) Referred to as bisphenol-A epoxy resin (reaction product)

**Other Toxicological Effects**

<b>Skin corrosion/irritation</b>	Based on tests on rabbits, the epoxy resins are moderate skin irritants.
<b>Serious eye damage/irritation</b>	Based on tests on rabbits, the epoxy resins are severe eye irritant.
<b>Sensitization</b> (allergic reactions)	Based on animal studies on the epoxy components, this product is a skin sensitizer

*Section continued on the next page*

**832B-A****BLACK EPOXY ENCAPSULATING AND POTTING COMPOUND****Carcinogenicity**

(risk of cancer)

Because the carbon black is bound in the epoxy liquid mixture, it is not available as an airborne hazard (dust, mist, or spray) under normal use.

**Carbon Black [1333-86-4]**

IARC Group 2B: Possibly carcinogenic to humans

ACGIH A4: Not classified as a human carcinogen

CA Prop 65: Listed as a carcinogen (airborne, as unbound particles of respirable size)

NTP: Not listed

**Mutagenicity**

(risk of heritable genetic effects)

Based on available data, the classification criteria are not met.

**Reproductive Toxicity**

(risk to sex functions)

Based on available data, the classification criteria are not met.

**Teratogenicity** (risk of fetus

malformation)

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met. There is less than 0.2% category 1 components, and the kinematic viscosity is >20.5 mm<sup>2</sup>/s at 40 °C.

**832B-A****BLACK EPOXY ENCAPSULATING AND POTTING COMPOUND****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

In Europe, similar epoxy resin mixtures with CAS# 25085-99-8 and 25068-38-6 with average molecular weight of less than 700 are generally classified as chronic category 2 marine pollutant due to LC50 96 h of >1 mg/L but ≤10 mg/L.

Based on available data, carbon black and alkyl glycidyl ether are not classified as environmental hazards according to GHS criteria.

**Acute Ecotoxicity**

See chronic ecotoxicity.

**Chronic Ecotoxicity**

Category 2

Toxic to aquatic life with long lasting effect

Avoid release to the environment. Collect spillage.

**Biodegradability**

Not available

**Bioaccumulation**

Not available

**Other Effects**

Not available

**Section 13: Disposal Considerations**

Dispose of contents in accordance with all local, regional, national, and international regulations.

**832B-A**
**BLACK EPOXY ENCAPSULATING AND POTTING COMPOUND**
**Section 14: Transport Information**
**Ground**

**Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations);  
**USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

**TDG: Sizes under 450 L**

*Part A of 832B-375ML, 832B-450ML,  
832B-3L, 832B-12L, 832B-60L kits*

**NOT REGULATED** in TDG  
per Special Provisions 99(2)

**49 CFR: Sizes greater than 5 L**

*Part A of 832B-60L kit*

**UN number:** UN3082

**Shipping Name:**

ENVIRONMENTALLY HAZARDOUS  
SUBSTANCE, LIQUID, N.O.S.

(propane, 2,2-bis[p-(2,3-  
epoxypropoxy)phenyl]-, polymers)

**Class:** 9

**Packing Group:** III

**Marine Pollutant:** Yes



**Special Provision 99 (2):** These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

**171.4 (c) Exceptions:**

(2) Single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other requirements of this subchapter provided the packagings meet the general requirements in § 173.24 and 173.24a. This exception does not apply to marine pollutants that are a hazardous waste or a hazardous substance. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this subchapter relevant to any additional hazards continue to apply.

**Temperature sensitive—Keep between 5 °C and 35 °C.**

*Section continued on next page*

**832B-A**
**BLACK EPOXY ENCAPSULATING AND POTTING COMPOUND**
**Air**
**Refer to ICAO-IATA Dangerous Goods Regulations.**
**Sizes 5 L and under:**
*Part A of 832B-375ML, 832-450ML,  
832B-3L, 832B-12L kits*
**NOT REGULATED**

On air waybill write:

"Not Restricted, as per  
Special Provisions A197"

**Sizes greater than 5 L:**
*Part A of 832B-60L kit*
**UN number:** UN3082


**Shipping Name:**

ENVIRONMENTALLY HAZARDOUS  
SUBSTANCE, LIQUID, N.O.S.

(propane, 2,2-bis[p-(2,3-  
epoxypropoxy)phenyl]-, polymers)

**Class:** 9

**Packing Group:** III

**Marine Pollutant:** Yes


Special Provision A197: These substances when transported in single or combination packagings containing net quantity per single or inner packaging of less than 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

**Temperature sensitive—Keep between 5 °C and 35 °C.**

**832B-A**
**BLACK EPOXY ENCAPSULATING AND POTTING COMPOUND**
**Sea**
**Refer to IMDG regulations.**
**Sizes 5 L and under**
*Part A of 832B-375ML, 832B-450ML,  
832B-3L, 832B-12L kits*
**NOT REGULATED**
*per 2.10.2.7*
**Sizes greater than 5 L**
*Part A of 832B-60L kit*
**UN number:** UN3082


**Shipping Name:**

ENVIRONMENTALLY HAZARDOUS  
SUBSTANCE, LIQUID, N.O.S.

(i.e. propane, 2,2-bis[p-(2,3-  
epoxypropoxy)phenyl]-, polymers)

**Class:** 9

**Packing Group:** III

**Marine Pollutant:** Yes


**2.10.2.7:** Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provision of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this Code relevant to any additional hazards continue to apply.

**Temperature sensitive—Keep between 5 °C and 35 °C.**

**Note:** Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

**Section 15: Regulatory Information**
**Canada**
**Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL.


**Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

*Section continued on the next page*

**832B-A****BLACK EPOXY ENCAPSULATING AND POTTING COMPOUND****USA****Other Classifications****HMIS<sup>®</sup> RATING**

<b>HEALTH:</b>	<b>* 2</b>
<b>FLAMMABILITY:</b>	<b>1</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	

**NFPA<sup>®</sup> 704 CODES**

*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

**CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

**EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain substances which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

**TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity, USA).

This product contains carbon black, but it is bound and exposures during normal conditions of uses are below the Safe Harbor Threshold.

**Europe****RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

**832B-A****BLACK EPOXY ENCAPSULATING AND POTTING COMPOUND****Section 16: Other Information**

<b>SDS Prepared by</b>	MG Chemicals' Regulatory Department
<b>Date of Review</b>	10 December 2023
<b>Supersedes</b>	28 February 2020
<b>Reason for Changes:</b>	Minor update

**Reference**

1) ACGIH 2023 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2023).

**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

*Section continued on the next page*



**832B-A****BLACK EPOXY ENCAPSULATING AND POTTING COMPOUND**

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

Phone: : +1-905-331-1396

**Mailing Addresses** *Manufacturing & Support*  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

**Disclaimer** This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.