

8330D-A

(PART A)

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: 8330D-A

Other Means of Identification: Silver Conductive Epoxy Adhesive (Part A)

Related Part # 8330D-19G, 8330D-160G

Recommended Use and Restriction on Use

Use: Electrically conductive epoxy adhesive resin part for use with hardeners

Uses Advised Against: Not available

Details of Manufacturer or Importer

Manufacturer

MG Chemicals 1210 Corporate Drive Burlington, Ontario L7L 5R6 **CANADA**

A +1-800-340-0772 FAX +1-800-340-0773 E-MAIL support@mgchemicals.com WEB www.mgchemicals.com

MG Chemicals (Head Office)

9347-193 Street

Surrey, British Columbia V4N 4E7

CANADA

+1-905-331-1396 FAX +1-905-331-2682

E-MAIL info@mgchemicals.com

E-MAIL (Competent Person): sds@mqchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) USA or CANADA—Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service CANADA—Call CANUTEC collect at +1-613-996-6666 or *666 on cellular phones



8330D-A

(PART A)

Section 2: Hazard(s) Identification

Classification of Hazardous Chemical

GHS Categories

Criteria		Category	Signal Word	Pictograms
Sensitization	Skin	1	Warning	Exclamation
Eye Irritation		2	Warning	Exclamation
Skin Irritation		2	Warning	Exclamation
Hazardous to the Aquatic Environment	Chronic	1	Warning	Environment

Note: The degree of severity is ranked within each hazard class from

1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Hazard Statements H317: May cause an allergic skin reaction H319: Causes serious eye irritation H315: Causes skin irritation H410: Very toxic to aquatic life with long lasting effects Prevention Precautionary Statements P102 Keep out of reach of children. P261 Avoid breathing fumes or vapors. P280 Wear protective gloves and eye protection. P272 Contaminated work clothing should not be allowed out of the workplace. P264 Wash hands thoroughly after handling. Avoid release to the environment.	Signal Word	WARNING
H319: Causes serious eye irritation H315: Causes skin irritation H410: Very toxic to aquatic life with long lasting effects Prevention Precautionary Statements P102 Keep out of reach of children. P261 Avoid breathing fumes or vapors. P280 Wear protective gloves and eye protection. P272 Contaminated work clothing should not be allowed out of the workplace. P264 Wash hands thoroughly after handling.	Pictograms	Hazard Statements
H315: Causes skin irritation H410: Very toxic to aquatic life with long lasting effects Prevention Precautionary Statements P102 Keep out of reach of children. P261 Avoid breathing fumes or vapors. P280 Wear protective gloves and eye protection. P272 Contaminated work clothing should not be allowed out of the workplace. P264 Wash hands thoroughly after handling.	<u> </u>	H317: May cause an allergic skin reaction
H410: Very toxic to aquatic life with long lasting effects Prevention Precautionary Statements P102 Keep out of reach of children. P261 Avoid breathing fumes or vapors. P280 Wear protective gloves and eye protection. P272 Contaminated work clothing should not be allowed out of the workplace. P264 Wash hands thoroughly after handling.		H319: Causes serious eye irritation
Prevention Precautionary Statements P102 Keep out of reach of children. P261 Avoid breathing fumes or vapors. P280 Wear protective gloves and eye protection. P272 Contaminated work clothing should not be allowed out of the workplace. P264 Wash hands thoroughly after handling.	•	H315: Causes skin irritation
P102 Keep out of reach of children. P261 Avoid breathing fumes or vapors. P280 Wear protective gloves and eye protection. P272 Contaminated work clothing should not be allowed out of the workplace. P264 Wash hands thoroughly after handling.	¥2>	H410: Very toxic to aquatic life with long lasting effects
P261 Avoid breathing fumes or vapors. P280 Wear protective gloves and eye protection. P272 Contaminated work clothing should not be allowed out of the workplace. P264 Wash hands thoroughly after handling.	Prevention	Precautionary Statements
P280 Wear protective gloves and eye protection. P272 Contaminated work clothing should not be allowed out of the workplace. P264 Wash hands thoroughly after handling.	P102	Keep out of reach of children.
P272 Contaminated work clothing should not be allowed out of the workplace. P264 Wash hands thoroughly after handling.	P261	Avoid breathing fumes or vapors.
P264 Wash hands thoroughly after handling.	P280	Wear protective gloves and eye protection.
	P272	Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.	P264	Wash hands thoroughly after handling.
	P273	Avoid release to the environment.

Section continued on the next page

Page **2** of **15**



SAI Global File #004008 Burlington, Ontario, Canada

8330D-A

(PART A)

Continued...

Response	Precautionary Statements
P302 + P352	IF ON SKIN: Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P391	Collect spillage.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Argyria	Long term exposure to silver powder or compounds can lead to an irreversible blue-grey discoloration of the skin.	Not applicable	Not applicable

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
7440-22-4	silver	76%
28064-14-4	phenol, polymer with formaldehyde, glycidyl ether	22%
17557-23-2	neopentyl glycol diglycidyl ether	2%



SAI Global File #004008 Burlington, Ontario, Canada

8330D-A (PART A)

Section 4: First-Aid Mea	asures
Exposure Condition	GHS Code/Symptoms/Precautionary Statements
IF ON SKIN	P302 + P352, P333 + P313, P362 + P364
Immediate Symptoms	redness, irritation, allergic dermatitis, rash
Response	Wash with plenty of water.
	If skin irritation or rash occurs: Get medical advice or attention.
	Take off contaminated clothing and wash it before reuse.
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	redness, irritation
Response	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	If eye irritation persists: Get medical advice or attention.
IF INHALED	P304 + P340
Immediate Symptoms	Low toxicity—cough, irritation of the respiratory track, sore throat, and asthma in certain pre-sensitized individuals
Response	Remove person to fresh air and keep comfortable for breathing.
IF SWALLOWED	P301 + P330, P331
Immediate Symptoms	Low toxicity: abdominal discomfort, nausea, vomiting
Response	Rinse mouth. Do NOT induce vomiting.

Section 5: Fire-Fighting Measures

In case of fire: Use extinguishing media suitable for surrounding materials.
Not flammable or combustible, but burns if involved in a fire. Produces irritating smoke of unknown toxicity in fires.
Inhalation of silver oxide fumes may cause metal fever and irritate the respiratory tract. The flu-like symptoms of metal fever may be delayed, occurring 4 to 12 hours after exposure.
Prevent fire-fighting wash from entering waterway or sewer system.
Produces carbon oxides (CO, CO_2), and toxic metal fumes.
Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Page **4** of **15**



SAI Global File #004008 Burlington, Ontario, Canada

8330D-A (PART A)

Section 6: Accidental Release Measures

Personal Protection See personal protection recommendations in Section 8.

Precautions for

Response

Avoid breathing fumes or vapors. Remove or keep away all

sources of extreme heat or open flames.

Environmental Precautions

Avoid releasing to the environment. Prevent spill from entering

drains and waterways.

Containment Methods No containment method required—this product is not readily

flowable

Cleaning Methods Collect liquid in a sealable, chemical-resistant container.

> Sprinkle inert absorbent compound onto spill, then sweep into the container. Use soap and water to remove the last traces of

residue.

Disposal Methods Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention Keep out of reach of children.

Avoid breathing fumes or vapors.

Contaminated work clothing should not be allowed out of the

workplace.

Avoid release to the environment.

Handling Wear protective gloves and eye protection.

Take off contaminated clothing and wash it before reuse.

Wash hands thoroughly after handling.

Collect spillage.

Not available Storage

Page **5** of **15**

SAI Global File #004008 Burlington, Ontario, Canada

8330D-A (PART A)

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
silver (metal dust, mist) (metal) (Ag and its compounds) (metal, dust, fumes)	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	0.1 mg/m ³ 0.01 mg/m ³ 0.1 mg/m ³ 0.01 mg/m ³ 0.1 mg/m ³	Not established Not established Not established 0.03 mg/m ³ Not established Not established

Note: The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS² database and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

Engineering Controls

Ve	ntı	lati	n

Keep airborne concentrations below the occupational exposure

limits (OEL).

The silver flakes are inextricably bound to the adhesive mixture; therefore they are not available as airborne hazards under normal use. Ensure adequate ventilation if the product is mechanically aerosolized.

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety

goggles.

RECOMMENDATION: Ensure that glasses have side shields for

lateral protection.

Skin Protection For likely contacts, use of protective butyl rubber, neoprene, or

other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant

gloves.

Section continued on the next page

Page **6** of **15**

SAI Global File #004008 Burlington, Ontario, Canada

8330D-A (PART A)

Respiratory Protection

If exposed to fumes or dust above the exposure limit, wear a suitable respirator meeting local, regional, and national guidelines.

If the product is heated or the worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Solid	Lower Flammability Limit	Not available
Appearance	Silver grey,	Upper Flammability	Not
	paste	Limit	available
Odor	Mild	Vapor Pressure @20°C	Not available
Odor Threshold	Not available	Vapor Density	Not available
pH	Not available	Relative Density @25 °C	3.3
Freezing/Melting	Not	Solubility in	Insoluble
Point	available	Water	
Initial Boiling	Not	Partition Coefficient n-octanol/water	Not
Point	available		available
Flash Point a)	≥150 °C	Auto-ignition	Not
	[≥302 °F]	Temperature	available
Evaporation	Not	Decomposition	Not
Rate	available	Temperature	available
Flammability	Non Flammable	Viscosity @40 °C	>20.5 mm ² /s

a) The closed cup flash point values are based on the phenol, polymer with formaldehyde, glycidyl ether resin component.



SAI Global File #004008 Burlington, Ontario, Canada

8330D-A (PART A)

Section 10: Stability and Reactivity

Reactivity Reacts exothermically with amines.

Chemical Stability Chemically stable at normal temperatures and pressures

Conditions to Avoid ignition sources, open flames, and incompatible substances. Do

Avoid not use in a way that aerosolizes the product.

Incompatibilities Avoid strong oxidizing agents, strong acids, strong bases

Polymerization Will not occur

Decomposition Will not decompose under normal conditions. For thermal

decomposition, see combustion products in Section 5.

Section 11: Toxicological Information

Summary of Effects and Symptoms by Routes of Exposure

Eyes Cause redness and irritation.

Skin Cause skin redness, irritation, or allergic contact dermatitis.

Inhalation Low toxicity—May cause cough, respiratory irritation, sore throat, or

asthma in certain pre-sensitized individuals.

Ingestion Low toxicity—It may cause abdominal discomfort, nausea, and vomiting.

Chronic Prolonged and repeated exposure may lead to skin sensitization.

Prolonged and repeated ingestion or inhalation of silver may yield to an

irreversible blue-grey discoloration of the skin.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50	LD50	LC50
	oral	dermal	inhalation
silver	≥2 000 mg/kg	≥2 000 mg/kg	5.16 mg/L
	Rat	Rat	Rat 4 h (dust)
phenol, polymer with formaldehyde, glycidyl ether	Not	Not	Not
	available	available	available
neopentyl glycol diglycidyl	2 000 mg/kg	2 150 mg/kg	Not
ether	Rat	Rabbit	available

Note: Toxicity data from the RTECS² and ECHA database were consulted. The data from supplier SDS were also consulted.

Section continued on the next page

Page **8** of **15**



SAI Global File #004008 Burlington, Ontario, Canada

8330D-A (PART A)

Other Toxicological Effects

Skin corrosion/irritation Causes skin irritation.

Serious eye Causes severe eye irritation. Contains mechanically

damage/irritation abrasive particles.

Sensitization The epoxy resin components (CAS# 28064-14-4 and (allergic reactions) 17557-23-2) may cause skin sensitization in humans.

Carcinogenicity None of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP. (risk of cancer)

Based on available data, the classification criteria are not Mutagenicity

(risk of heritable genetic effects)

Reproductive Toxicity Based on available data, the classification criteria are not

(risk to sex functions) met.

Teratogenicity (risk of fetus

Based on available data, the classification criteria are not malformation)

STOT-single exposure Based on available data, the classification criteria are not

met.

STOT-repeated exposure Based on available data, the classification criteria are not

Aspiration hazard Based on available data, the classification criteria are not

> met. There is no category 1 components, and the kinematic viscosity is >20.5 mm²/s at 40 °C.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (http://echa.europa.eu), and other reliable sources.

Contains silver particles of less than a 1 mm but more than 100 nm (larger than nanoparticles), which release ionic silver levels that is very toxic to the environment. While massive silver is insoluble in water, its powders is considered sufficiently soluble to give rise to an ecological hazard by EU regulators. The classification that follows takes into account to chronic agueous toxicity of category 1 (M = 10 for silver) of the EU.

In Europe, similar epoxy resin with CAS# 28064-14-4 is generally classified as chronic category 2 marine pollutant due to LC50 96 h of >1 mg/L but ≤10 mg/L.

Based on available data, neopentyl glycol diglycidyl ether is not classified as environmental hazard according to GHS criteria.

Section continued on the next page

Page **9** of **15**



SAI Global File #004008 Burlington, Ontario, Canada

8330D-A (PART A)

Acute Ecotoxicity

Category 1

Very toxic to aquatic life

Chronic Ecotoxicity

Category 1

Very toxic to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

Biodegradability

Not readily biodegradable

Bioaccumulation

Not available

Other Effects

Not available

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

SAI Global File #004008 Burlington, Ontario, Canada

8330D-A (PART A)

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

TDG: Sizes under 450 kg 8330D-19G, 8330D-160G
NOT REGULATED in TDG
per Special Provisions 99

49 CFR: Sizes 5 kg and under

NOT REGULATED in 49 CFR per exception 171.4 (c)(2)

49 CFR: Sizes over 5 kg FOR REFERENCE ONLY
UN number: UN3077

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (silver flakes <1 mm; phenol, polymer with

formaldehyde, glycidyl ether)

Class: 9

Packing Group: III Marine Pollutant: Yes

Special Provision 99 (2): These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

171.4 (c) Exceptions:

(2) Single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other requirements of this subchapter provided the packagings meet the general requirements in §§ 173.24 and 173.24a. This exception does not apply to marine pollutants that are a hazardous waste or a hazardous substance. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this subchapter relevant to any additional hazards continue to apply.

Temperature sensitive—Keep between 5 °C and 35 °C.



SAI Global File #004008 Burlington, Ontario, Canada

8330D-A (PART A)

_		
Λ	П	7
_		

Refer to ICAO-IATA regulations.

Sizes 5 kg and under *8330D-19G, 8330D-160G*

NOT REGULATED

Not Restricted, as per Special Provisions A197

Special Provision A197: These substances when transported in single or combination packagings containing net quantity per single or inner packaging of less than 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Temperature sensitive—Keep between 5 °C and 35 °C.

Sea

Refer to IMDG regulations. Sizes 5 kg and under: Cat. No. 8330D-19G, 8330D-160G NOT REGULATED per 2.10.2.7

2.10.2.7: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provision of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this Code relevant to any additional hazards continue to apply.

Temperature sensitive-Keep between 5 °C and 35 °C.

Note: Shipper must be appropriately <u>trained and certified</u> before involvement with the transport of dangerous goods.



8330D-A

(PART A)

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

USA

Other Classifications

HMIS® RATING

HEALTH:	*	2
FLAMMABILITY:		1
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains silver (CAS# 7440-22-4; reportable quantity = $1\,000\,lb$), which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

Section continued on the next page

Page **13** of **15**



SAI Global File #004008 Burlington, Ontario, Canada

8330D-A (PART A)

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any listed substances in California.

Europe

RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

SDS Prepared by MG Chemical's Regulatory Department

Date of Review 29 June 2020 Supersedes Not applicable

Reason for Changes: First release.

Reference

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Section continued on the next page



SAI Global File #004008 Burlington, Ontario, Canada

8330D-A (PART A)

Abbreviations

American Conference of Governmental Industrial Hygienists (USA) ACGIH

ECHA European Chemicals Agency

Half maximal effective concentration EC50

EL50 Half maximal effective loading

IARC International Agency for Research on Cancer

NOELR No observable effect loading ratio NTP National Toxicology Program

Globally Harmonized System of Classification of Labeling of Chemicals GHS

LC50 Lethal Concentration 50%

Lowest published lethal concentration LCLo

LD50 Lethal Dose 50%

Occupational Exposure Limit OFL PEL Permissible Exposure Limit

SDS Safety Data Sheet

Short-Term Exposure Limit STEL

TCLo Lowest published toxic concentration

Time Weighted Average TWA VOC Volatile Organic Content

Technical Oueries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Phone: +1-905-331-1396

Mailing Addresses Manufacturing & Support

1210 Corporate Drive 9347-193rd Street

Burlington, Ontario, Canada Surrey, British Columbia, Canada

L7L 5R6 V4N 4E7

Disclaimer

This safety data sheet is provided as an information resource only. M.G. Chemicals, Ltd. believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.

Head Office