



(PART B)

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: 8331D-B

Other Means of Identification: Silver Conductive Epoxy Adhesive (Part B)

Related Part # 8331D-14G, 8331D-120G

Recommended Use and Restriction on Use

Use: Electrically conductive epoxy adhesive hardener part for use with resins

Uses Advised Against: Not available

Details of Manufacturer or Importer

Manufacturer

MG Chemicals 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA

***** +1-800-340-0772 +1-800-340-0773 FΔX E-MAIL support@machemicals.com **W**EB www.mgchemicals.com

MG Chemicals (Head Office)

9347-193 Street

Surrey, British Columbia V4N 4E7

CANADA

+1-905-331-1396 +1-905-331-2682 FAX E-MAIL info@mgchemicals.com

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) USA or CANADA—Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service CANADA—Call CANUTEC collect at +1-613-996-6666 or *666 on cellular phones



8331D-B Burlington, Ontario, Canada (PART B)

Section 2: Hazard(s) Identification

Classification of the Chemical Material

GHS Categories

Criteria		Category	Signal Word	Pictograms
Eye Damage		1	Danger	Corrosion
Sensitization	Skin	1	Warning	Exclamation
Irritation	Skin	2	Warning	Exclamation
Hazardous to the Aquatic Environment	Chronic	1	Warning	Environment

Note: The degree of severity is ranked within each hazard class from

1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H318: Causes serious eye damage
^	H317: May cause an allergic skin reaction
	H315: Causes skin irritation
***	H410: Very toxic to aquatic life with long lasting effects

Section continued on the next page

Page 2 of 17



SAI Global File #004008 Burlington, Ontario, Canada

8331D-B (PART B)

Continued...

Prevention	Precautionary Statements
P102	Keep out of reach of children.
P261	Avoid breathing fumes or vapors.
P280	Wear protective gloves and eye protection.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
Response	Precautionary Statements
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.
P362 + P364	Take off immediately all contaminated clothing and wash it before reuse.
P391	Collect spillage.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Argyria	Long term ingestion or inhalation of silver can lead to an irreversible blue-grey discoloration of the skin.	Not applicable	Not applicable



8331D-B (PART B)

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
7440-22-4	silver	67%
109-55-7	3-aminopropyldimethylamine	3%
135108-88-2	methyleneoxide, polymer with benzenamine, hydrogenated	0.8%
100-51-6	benzyl alcohol	0.8%
108-95-2	phenol	0.3%

Section 4: First-Aid Measures

Exposure Condition	GHS Code: Precautionary Statement
IF IN EYES	P305 + P351 + P338, P310
Immediate Symptoms	redness, severe irritation, pain, burns
Response	Rinse cautiously with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	Immediately call a POISON CENTER or doctor.
IF ON SKIN	P302 + P352, P333 + P313, P362 + P364
Immediate Symptoms	redness, rash (allergic contact dermatitis), severe irritation
Response	Wash with plenty of water.
	If skin irritation or rash occurs: Get medical advice or attention.
	Take off contaminated clothing and wash it before reuse.
IF INHALED	P304 + P340
Immediate Symptoms	Low toxicity—cough, irritation of the respiratory track
Response	Remove person to fresh air and keep comfortable for breathing.
IF SWALLOWED	P301 + P330, P331
Immediate Symptoms	Low toxicity
Response	Rinse mouth. Do not induce vomiting.

SAI Global File #004008 Burlington, Ontario, Canada

8331D-B (Part B)

Section 5: Fire-Fighting Measures

Extinguishing Media In case of fire: Use extinguishing media suitable for surrounding

materials.

Specific Hazards Not flammable or combustible, but will burn if involved in a fire.

Produces irritating smoke and toxic smoke in fires.

Inhalation of silver oxide fumes may cause metal fever and irritate the respiratory tract. The flu-like symptoms of metal fever may be delayed, occurring 4 to 12 hours after exposure.

Very toxic to aquatic life: Prevent fire-fighting wash from

entering waterway or sewer system.

Combustion Products Produces carbon oxides (CO, CO₂), nitrogen oxides (NO_x),

amines, silver oxide fumes and other toxic fumes.

Fire-Fighter Wear self-contained breathing apparatus and full fire-fighting

turn-out gear.

Section 6: Accidental Release Measures

Personal Protection Use personal protection recommended in Section 8.

Precautions for

Response

Avoid breathing fumes or vapors. Keep away from extreme heat

or open flames.

Environmental Precautions

Avoid releasing to the environment. Prevent spill from entering

drains and waterways.

Containment Methods

None required—this product is not readily flowable

Cleaning Methods

Collect liquid in a sealable container. Wipe remaining residue with a paper towel and place dirty towels in container. Wash spill area with soap and water to remove the last traces of

residue.

RECOMMENDATION: Use a plastic, stainless steel, or carbon steel container. Avoid containers with copper, aluminum, zinc, or galvanized surfaces since the waste mater can slowly oxidize

them.

Disposal Methods

Dispose spill waste according to Section 13.



SAI Global File #004008 Burlington, Ontario, Canada

8331D-B (PART B)

Section 7: Handling and Storage

Prevention Keep out of reach of children.

Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the

workplace.

Avoid breathing fumes or vapors.

Avoid release to the environment.

Handling Wear protective gloves and eye protection.

Wash hands thoroughly after handling.

Collect spillage.

Storage RECOMMENDATION: Keep in a dry and clean area, away from

incompatible substances.



(PART B)

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country or Vendor	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
silver	ACGIH	0.1 mg/m ³	Not established
(metal dust, mist)	U.S.A. OSHA PEL	0.01 mg/m ³	Not established
(metal)	Canada AB	0.1 mg/m ³	Not established
(Ag and its compounds)	Canada BC	0.01 mg/m ³	0.03 mg/m ³
(metal, dust, fumes)	Canada ON	0.1 mg/m ³	Not established
	Canada QC	0.1 mg/m ³	Not established
benzyl alcohol	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	Not established	Not established
	U.S.A (WEEL)	10 ppm	Not established
	Canada AB	Not established	Not established
	Canada BC	Not established	Not established
	Canada ON	Not established	Not established
	Canada QC	Not established	Not established
phenol	ACGIH	5 ppm (Skin)	Not established
	U.S.A. OSHA PEL	5 ppm (Skin)	Not established
	U.S.A (WEEL)	5 ppm (Skin)	Not established
	Canada AB	5 ppm (Skin)	Not established
	Canada BC	5 ppm (Skin)	Not established
	Canada ON	5 ppm (Skin)	Not established
	Canada QC	5 ppm (Skin)	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS² database and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long-term permissible exposure limits (PEL) for 8 h.

Skin—can be absorbed through the skin

Engineering Controls

Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

RECOMMENDATION: Because silver is bound to the liquid mixture, it does not present an airborne hazard under normal use. If the product is heated, use of local exhaust or full mask with organic vapor cartridge or independent air supply.

Section continued on the next page

Page **7** of **17**



SAI Global File #004008 Burlington, Ontario, Canada

8331D-B (PART B)

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety

goggles.

RECOMMENDATION: Use safety glasses with lateral protection

(side shields).

Skin Protection For likely contacts, use of protective butyl rubber, neoprene, or

other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant

gloves.

Respiratory Protection For over-exposures up to 10 x OEL of fumes and vapors, wear

respirator such as a half-mask respirator with organic vapor

cartridges and particulate filter.

Above 10 x OEL or if the worker is allergic, use a full mask, positive-pressure, air-supplied respirator or a self-contained

breathing apparatus.

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with

an independent air supply.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when

not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.



SAI Global File #004008 Burlington, Ontario, Canada

available

 $>20.5 \text{ mm}^2/\text{s}$

8331D-B (PART B)

Section 9: Physical and Chemical Properties

Physical State	Solid	Lower Flammability Limit	Not available
Appearance	Silver grey, paste	Upper Flammability Limit	Not available
Odor	Amine-like	Vapor Pressure @25°C	Not available
Odor Threshold	Not available	Vapor Density	Not available
рН	Not available	Relative Density @25°C	2.3
Freezing/Melting Point	Not available	Solubility in Water	Practically insoluble
Initial Boiling Point	Not available	Partition Coefficient n-octanol/water	Not available
Flash Point	Not available	Auto-ignition Temperature	Not available
Evaporation	Not	Decomposition	Not

Temperature

Viscosity

@40 °C

Section 10: Stability and Reactivity

Rate

Flammability

Reactivity	Reacts exotl	hermically with ϵ	epoxide groups.
------------	--------------	----------------------------	-----------------

Chemical Stability Chemically stable at normal temperatures and pressures

Conditions to Avoid flames, sparks, other ignition sources and incompatible

Avoid substances.

Incompatibilities Strong oxidizing agents, strong acids, ammonia, and hydrogen

peroxides.

available

Flammable

Non

Polymerization Will not occur

Decomposition For thermal decomposition, see combustion products in Section 5.



(PART B)

Section 11: Toxicological Information

Summary of Effects and Symptoms by Routes of Exposure

Eyes Causes redness, severe eye irritation, pain, or corrosive eye damage.

Contains mechanically abrasive particles.

Skin Causes redness, serious skin irritation, and allergic contact dermatitis.

Inhalation Low toxicity—May cause cough and severe respiratory irritation.

Ingestion Low toxicity

Chronic Prolonged and repeated exposure may lead to skin sensitization.

Long term exposure to silver powder or compounds can lead to an

irreversible blue-grey discoloration of the skin.

Lethal Exposure Concentrations

Chemical Name	LD50	LD50	LC50
	oral	dermal	inhalation
silver	>2 000 mg/kg	>2 000 mg/kg	5.16 mg/L
	Rat	Rat	Rat ≥4 h (dust)
3-aminopropyldimethylamine	377 mg/kg	300 mg/kg	>4.31 mg/L
	Rat	Rat	Rat 4 h (vapor)
methyleneoxide, polymer with benzenamine, hydrogenated	368 mg/kg	>1 000 mg/kg	Not
	Rat	Rat	available
benzyl alcohol	1 620 mg/kg	866 mg/kg	>4.178 mg/L
	Rat	Rabbit	4 h Rat
phenol	650 mg/kg	660 mg/kg	0.316 mg/L
	Rat	Rat	Rat 4 h (vapor)

Note: Toxicity data from the RTECS² and ECHA were consulted. The data from supplier SDS were also consulted.

Section continued on the next page



SAI Global File #004008 Burlington, Ontario, Canada

8331D-B (Part B)

Other Toxicological Effects

Skin corrosion/irritation The 3-aminopropyldimethylamine and methyleneoxide,

polymer with benzenamine, hydrogenated components

cause skin irritation.

Serious eye damage/irritation The 3-aminopropyldimethylamine and methyleneoxide,

polymer with benzenamine, hydrogenated components

cause eye damage.

Respiratory and skin

sensitization (allergic reactions)

The 3-aminopropyldimethylamine and methyleneoxide,

polymer with benzenamine, hydrogenated components

cause skin sensitization.

Carcinogenicity

(risk of cancer)

None of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.

Mutagenicity

(risk of heritable genetic effects)

The phenol (CAS# 108-95-2) is considered a mutagen

according to animal studies.

Reproductive Toxicity

(risk to sex functions)

Based on available data, the classification criteria are

not met.

Teratogenicity

(risk of fetus malformation)

Based on available data, the classification criteria are

not met.

STOT-single exposure

Based on available data, the classification criteria are

not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met. See the argyria warning in the Hazards Not

Otherwise Classified subsection in section 02.

Aspiration hazard

Based on available data, the classification criteria are not met. The mixture does not contain components classified as aspiration hazards and the kinematic viscosity of the mixture is $>20.5 \text{ mm}^2/\text{s}$ at 40 °C.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (http://echa.europa.eu), and other reliable sources.

Contains silver particles of less than a 1 mm but more than 100 nm (larger than nanoparticles), which release ionic silver levels that is very toxic to the environment. While massive silver is insoluble in water, its powders is considered sufficiently soluble to give rise to an ecological hazard by EU48 regulators. The classification takes into account to chronic aqueous toxicity of category 1 (M = 10 for silver) of the EU.

Section continued on the next page

Page **11** of **17**



SAI Global File #004008 Burlington, Ontario, Canada

8331D-B (PART B)

Methyleneoxide, polymer with benzenamine, hydrogenated is hazardous to the aquatic environment with a chronic category 3 classification.

Phenol is hazardous to the aquatic environment with a chronic category 2 classification.

Based on available data, 3-aminopropyldimethylamine and benzyl alcohol are not classified as aquatic environmental toxicants according to GHS criteria.

Acute Ecotoxicity

Category 1

Very toxic to aquatic life

Chronic Ecotoxicity

Category 1

Very toxic to aquatic life with long lasting effect

Avoid release to the environment. Collect spillage.

Persistence and Biodegradability

Not available

Bioaccumulative Potential

Not available

Mobility in Soil

Not available

Other Effects

Not available

Section 13: Disposal Considerations

Dispose of contents in accordance with all local, regional, national, and international regulations.

SAI Global File #004008 Burlington, Ontario, Canada

8331D-B (PART B)

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

TDG: Sizes under 450 kg 8331D-14G, 8331D-120G NOT REGULATED in TDG per Special Provisions 99

49 CFR: Sizes 5 kg and under 8331D-14G, 8331D-120G
NOT REGULATED in 49 CFR per exception 171.4 (c)(2)

49 CFR: Sizes over 5 kg FOR REFERENCE ONLY UN number: UN3077 Shipping Name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (silver flakes <1 mm)

Class: 9

Packing Group: III Marine Pollutant: Yes

Special Provision 99 (2): These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

171.4 (c) Exceptions:

(2) Single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other requirements of this subchapter provided the packagings meet the general requirements in §§ 173.24 and 173.24a. This exception does not apply to marine pollutants that are a hazardous waste or a hazardous substance. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this subchapter relevant to any additional hazards continue to apply.

Section continued on the next page

Page **13** of **17**



SAI Global File #004008 Burlington, Ontario, Canada

8331D-B (PART B)

Air	
Refer to ICAO-IATA regulations.	
Sizes 5 kg and under 8331D-14G, 8331D-120G NOT REGULATED Not Restricted, as per Special Provisions A197	
-	tances when transported in single or combination

Special Provision A197: These substances when transported in single or combination packagings containing net quantity per single or inner packaging of less than 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Sea

Refer to IMDG regulations.	
Sizes 5 kg and under	
8331D-14G, 8331D-120G	
NOT REGULATED	
per 2.10.2.7	

2.10.2.7: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provision of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this Code relevant to any additional hazards continue to apply.

Note: Shipper must be appropriately <u>trained and certified</u> before involvement with the transport of dangerous goods.





(PART B)

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL)/Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL/NDSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

USA

Other Classifications

HMIS® RATING

HEALTH:	*	3
FLAMMABILITY:		1
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product contains silver (CAS# 7440-22-4; reportable quantity = 1 000 lb), which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

This product contains phenol (CAS# 108-95-2); reportable quantity = 1 000 lb), which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

Section continued on the next page

Page **15** of **17**



SAI Global File #004008 Burlington, Ontario, Canada

8331D-B (PART B)

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any substances on the California Proposition 65 list.

Europe

RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment and is therefore not governed by this regulation.

Section 16: Other Information

Prepared by theMG Chemicals' Regulatory Affairs Department

Date of Revision24 June 2020SupersedesNot availableReason for Changes:First release.

Reference

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Section continued on the next page



SAI Global File #004008 Burlington, Ontario, Canada

8331D-B (PART B)

Abbreviations

ACGIH American Conference of Governmental Industrial Hygienists (USA)

EC50 Half maximal effective concentration

GHS Globally Harmonized System of Classification of Labeling of Chemicals

IARC International Agency for Research on Cancer

LC50 Lethal Concentration 50%

LD50 Lethal Dose 50%

NTP National Toxicology Program
OEL Occupational Exposure Limit
PEL Permissible Exposure Limit

SDS Safety Data Sheet

STEL Short-Term Exposure Limit

TCLo Lowest published toxic concentration

TWA Time Weighted Average VOC Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or

problems with this product. Application notes, instructions, and FAQs

are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Phone: +1-905-331-1396

Mailing Addresses Manufacturing & Support Head Office

1210 Corporate Drive 9347–193rd Street

Burlington, Ontario, Canada Surrey, British Columbia, Canada

L7L 5R6 V4N 4E7

Disclaimer This safety data sheet is provided as an information resource only.

M.G. Chemicals, Ltd. believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional,

n7ational, and international regulations.