Burlington, Ontario, Canada



841WB

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: 841WB

Other Means of Identification: Super Shield™ Water Based Nickel Conductive Paint /

Peinture de Nickel Conducteur Super ShieldTM à Base d'Eau

Related Part # 841WB-15ML, 841WB-55ML, 841WB-150ML, 841WB-850ML, 841WB-3.78L

Recommended Use and Restriction on Use

Use: Nickel filled, electrically conductive coating **Uses Advised Against:** Not for sale in the EU.

Details of Manufacturer or Importer

Manufacturer

MG Chemicals 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA

FAX +1-800-340-0772 +1-800-340-0773

E-MAIL <u>support@mgchemicals.com</u> **WEB** <u>www.mgchemicals.com</u>

E-MAIL (Competent Person): sds@mqchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) USA or CANADA—Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service CANADA—Call CANUTEC collect at +1-613-996-6666 or *666 on cellular phones



Section 2: Hazard(s) Identification

Classification of Hazardous Chemical

GHS Categories

Criteria		Category	Signal Word	Pictograms
Reproductive Toxicity		1	Danger	Health
Specific Target Organ Toxicity	Repeated Exposure	1	Danger	Health
Carcinogenicity		2	Warning	Health
Sensitization	Skin	1	Warning	Exclamation
Hazardous to the Aquatic Environment	Chronic	3	none	none

Note: The degree of severity is ranked within each hazard class from

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H360: May damage fertility or the unborn child
	H372: Causes damages to organs (lungs) through prolonged or repeated exposure by inhalation
	H351: Suspected of causing cancer
	H317: May cause allergic skin reaction
None	H412: Harmful to aquatic life with long lasting effects

Section continued on the next page

^{1 (}Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.



Continued ...

Prevention	Precautionary Statements	
P102	Keep out of reach of children.	
P201	Obtain special instructions before use.	
P202	Do not handle until all safety precautions have been read and understood.	
P260	Do not breathe mist, spray, and vapors.	
P270	Do not eat, drink or smoke when using this product.	
P280	Wear protective gloves, protective clothing, and eye protection.	
P272	Contaminated work clothing should not be allowed out of the workplace.	
P264	Wash hands thoroughly after handling.	
P273	Avoid release to the environment.	
Response	Precautionary Statements	
P308 + P313	IF exposed or concerned: Get medical advice or attention.	
P302 + P352	IF ON SKIN: Wash with plenty of water.	
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.	
P362 + P364	Take off contaminated clothing and wash it before reuse.	
P314	Get medical attention or advice if you feel unwell.	
Storage	Precautionary Statements	
P405	Store locked up.	
Disposal	Precautionary Statements	
P501	Dispose of contents in accordance to local, regional, national and international regulations.	

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None



Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
7440-02-0	nickel	48%
872-50-4	1-methyl-2-pyrrolidone	4%
14807-96-6	talc	1%
121-44-8	triethylamine	0.4%

Section 4: First-Aid Measures

Exposure Condition	GHS Code/Symptoms/Precautionary Statements	
IF ON SKIN	P302 + P352, P333 + P313, P362 + P364, P308 + P313	
Immediate Symptoms	dry skin, redness, allergic rash	
Response	Wash with plenty of water.	
	If skin irritation or rash occurs: Get medical advice or attention.	
	Take off contaminated clothing and wash it before reuse.	
	IF exposed or concerned: Get medical advice or attention.	
IF INHALED	P304 + P340, P308 + P313	
Immediate Symptoms	cough, shortness of breath, headache	
Response	Remove person to fresh air and keep comfortable for breathing.	
	IF exposed or concerned: Get medical advice or attention.	
IF IN EYES	P305 + P351 + P338	
Immediate Symptoms	redness, blurred vision, pain	
Response	Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
IF SWALLOWED	P301 + P330 + P331, P308 + P313	
Immediate Symptoms	low toxicity: no symptoms known or expected	
Response	Rinse mouth. Do NOT induce vomiting.	
	IF exposed or concerned: Get medical advice or attention.	



SAI Global File #004008 Burlington, Ontario, Canada

841WB

Section 5: Fire-Fighting Measures

Extinguishing Media In case of fire use extinguishing media suitable for surrounding

material.

Specific Hazards Produces irritating and toxic fumes in fires or in contact with

hot surfaces. May produce very toxic nickel carbonyl gas in the

presence of carbon monoxide in a reducing atmosphere.

Combustion Products Produces carbon oxides (CO, CO₂), nickel oxides fumes, and

nitrogen oxides (NO_x) .

Fire-Fighter Wear self-contained breathing apparatus and full fire-fighting

turn-out gear.

Section 6: Accidental Release Measures

Personal Protection Use personal protection recommendations in Section 8.

Precautions for Response

Do not breathe the mist, spray, and vapors. Remove or keep

away all sources of extreme heat or open flames.

Environmental Precautions

Avoid releasing to the environment. Prevent spill from entering

drains and waterways.

Containment Methods Contain with inert and non-flammable absorbent (such as soil,

sand, vermiculite).

Cleaning Methods Collect liquid in a sealable, waste container. Sprinkle inert

absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces

of residue.

Disposal Methods Dispose of spill waste according to Section 13.



SAI Global File #004008 Burlington, Ontario, Canada

841WB

Section 7: Handling and Storage

Prevention Keep out of reach of children.

Obtain special instructions before use. Do not handle until all

safety precautions have been read and understood.

Do not breathe mist, spray, and vapors. Do not eat, drink, or

smoke when using this product.

Contaminated work clothing should not be allowed out of the

workplace.

Handling Wear protective gloves, protective clothing, and eye protection.

Take off contaminated clothing and wash it before reuse.

Wash hands thoroughly after handling.

Avoid release to the environment.

Storage Store locked up.

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
nickel	ACGIH	1.5 mg/m ³	Not established
	U.S.A. OSHA PEL	1 mg/m ³	Not established
	Canada AB	1.5 mg/m ³	Not established
	Canada BC	0.05 mg/m ³	Not established
	Canada ON	1 mg/m ³	Not established
	Canada QC	1 mg/m ³	Not established
talc (non-asbestos fiber)	ACGIH	2 mg/m ³	Not established
	U.S.A. OSHA PEL	20 mppcf ^{a)}	Not established
	Canada AB	2 mg/m ³	Not established
	Canada BC	2 mg/m ³	Not established
	Canada ON	2 mg/m ³	Not established
	Canada QC	3 mg/m ³	Not established

Section continued on the next page



SAI Global File #004008 Burlington, Ontario, Canada

841WB

Continued...

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
triethylamine	ACGIH	100 mg/m ³	12 mg/m ³
	U.S.A. OSHA PEL	15 ppm	Not established
	Canada AB	1 ppm	3 ppm
	Canada BC	1 ppm	3 ppm
	Canada ON	0.5 ppm	1 ppm
	Canada QC	10 ppm	15 ppm

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Million particles per cubic foot of air, based on impinge samples counted by light-field technique.

Engineering Controls

Ventilation Keep airborne concentrations below the occupational exposure

limits (OEL).

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety

goggles.

RECOMMENDATION: Ensure that glasses have side shields for

lateral protection.

Skin Protection For likely or incidental contacts, use nitrile, neoprene, or other

chemically resistant gloves.

Section continued on the next page



SAI Global File #004008 Burlington, Ontario, Canada

841WB

Respiratory Protection For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges and particulate filter.

> Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	Not applicable
Appearance	Dark grey	Upper Flammability Limit	Not applicable
Odor	Musty	Vapor Pressure ^{a)}	23 hPa [17 mmHg]
Odor Threshold	Not available	Vapor Density	Not available
рH	Not available	Relative Density @25 °C	1.82
Freezing/Melting	Not	Solubility in	Miscible
Point	available	Water	
Initial Boiling	100 °C	Partition Coefficient n-octanol/water	Not
Point	[212 °F]		available
Flash Point	Not	Auto-ignition	Not
	available	Temperature	available
Evaporation	Not	Decomposition	Not
Rate	available	Temperature	available
Flammability	Non	Viscosity	Not
	Flammable	@40 °C	available

a) Calculated using from volatile components parameters and Raoult's Law.

M Chemicals

ISO 9001:2015 Quality Management System

SAI Global File #004008 Burlington, Ontario, Canada

841WB

Section 10: Stability and Reactivity

Reactivity The nickel can react vigorously with acids and liberate hydrogen,

which can form an explosive mixture in air.

Nickel may react with carbon monoxide in a reducing atmosphere to

form a very toxic nickel carbonyl gas.

Chemical Stability

Chemically stable at normal temperatures and pressures

Conditions to Avoid Ignition sources, open flames, excessive heat, and incompatible

substances

Incompatibilities Oxidizing agents, strong acids, acid anhydrides

Polymerization Will not occur

Decomposition Does not decompose under normal conditions. For thermal

decomposition, see combustion products in Section 5.

Section 11: Toxicological Information

Summary of Effects and Symptoms by Routes of Exposure

Eyes May cause redness, blurred vision and pain.

Skin May cause dry skin, redness and allergic rash.

Inhalation May cause cough, shortness of breath and headaches.

Ingestion Low toxicity: no symptoms known or expected.

Chronic Chronic inhalation exposure to nickel dust, mist, or spray may affect the

central nervous system, damage lungs. Nickel is suspected of being a

carcinogen.

Section continued on the next page



Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50	LD50	LC50
	oral	dermal	inhalation
nickel	9 000 mg/kg	Not	10.2 mg/L
	Rat	available	1 h Rat
1-methyl-2-pyrrolidone	3 914 mg/kg	8 000 mg/kg	>5.1 mg/L
	Rat	Rabbit	Rat 4 h (mist)
talc	Not	Not	Not
	available	available	available
triethylamine	730 mg/kg	580 mg/kg	3 496 ppm
	Rat	Rat	1 hr Rat
ATE Mixture	>2 000 mg/kg	>2 000 mg/kg	>100 mg/L

Note: Toxicity data from the ECHA database were consulted. The data from supplier SDSs were also consulted.

Othor	Tavida	loaical	Effects
Ouici	IUXICU	luultai	THE CTS

Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met. Contains mechanically abrasive particles.
Exposure to nickel may cause allergic skin reaction.
Nickel is classified as a suspect carcinogen based on animal intratracheal instillation (intubation) or interperitoneal (in body cavity) injection studies. A reliable 2008 study by Oller et al. shows no carcinogenicity for the nickel metal via normal inhalation route.
Nickel [7440-02-0]
IARC Group 2B: Possibly carcinogenic to humans
ACGIH A5: Not suspected as a human carcinogen
CA Prop 65: Listed as a carcinogen
NTP: Reasonably anticipated to be human carcinogen

Section continued on the next page

Page **10** of **15**



SAI Global File #004008 Burlington, Ontario, Canada

841WB

Mutagenicity

(risk of heritable genetic

effects)

Based on available data, the classification criteria are

not met.

Reproductive Toxicity

(risk to sex functions)

Based on available data, the classification criteria are

not met.

Teratogenicity

(risk of fetus malformation)

At large doses of >4 000 mg/kg, 1-methyl-2-

pyrrolidone shows reproductive effects based on studies

in rats and mice.

1-methyl-2-pyrrolidinone [CAS# 872-50-4]

CA Prop 65: Listed as a reproductive toxicant

STOT-single exposure Based on available data, the classification criteria are

not met.

STOT-repeated exposure Nickel particles can damage the respiratory tract leading

to inflammation, lung fibrosis, and accumulation of

nickel particles in a rat study.

Aspiration hazard There are no category 1 components, and the kinematic

viscosity of the mixture is >20.5 mm²/s at 40 °C.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (http://echa.europa.eu), and other reliable sources.

Nickel powder less than 1 mm diameter is classified as a chronic category 3 aquatic pollutant by ECHA registrants.

Acute Ecotoxicity

Available toxicity data does not meet classification thresholds.

Chronic Ecotoxicity

Category 3

Harmful to aquatic life with long lasting effects.

Avoid release to the environment. Collect spillage.

Biodegradability

The nickel content is not biodegradable.

Section continued on the next page

Page **11** of **15**



SAI Global File #004008 Burlington, Ontario, Canada

841WB

Other Effects

Actual VOC = 5.1% [28 g/L]; Regulated VOC = 477 g/L

Note: Nickel can be recovered from the waste to reclaim the value of the nickel.

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations) and **US DOT 49 CFR** (Parts 100 to 185) **Regulations**.

Not Regulated

Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Not Regulated

Sea

Refer to IMDG Dangerous Goods Regulations.

Not Regulated



Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

USA

Other Classifications

HMIS® RATING

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain products that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains nickel (CAS# 7440-02-0, reportable quantity = 100 lb), which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

Section continued on the next page

Page **13** of **15**

M Chemicals

ISO 9001:2015 Quality Management System

SAI Global File #004008 Burlington, Ontario, Canada

841WB

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA)

This product contains nickel, which is listed as a carcinogen. This product contains 1-methyl-2-pyrrolidinone (CAS# 872-50-4), which is listed as reproductive toxicity.

Europe

RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment and is therefore not governed by this regulation.

Section 16: Other Information

SDS Prepared by MG Chemicals' Regulatory Department

Date of Review 10 April 2024 Supersedes 08 April 2022

Reason for Changes: New part number added.

Reference

1) ACGIH 2024 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2024).

Section continued on the next page



SAI Global File #004008 Burlington, Ontario, Canada

841WB

Abbreviations

ACGIH American Conference of Governmental Industrial Hygienists (USA) **ECHA** European Chemicals Agency EU European Union EC50 Half maximal effective concentration EL50 Half maximal effective loading International Agency for Research on Cancer IARC NOELR No observable effect loading ratio NTP National Toxicology Program Globally Harmonized System of Classification of Labeling of Chemicals GHS LC50 Lethal Concentration 50% LCLo Lowest published lethal concentration LD50 Lethal Dose 50% OFL Occupational Exposure Limit PEL Permissible Exposure Limit SDS Safety Data Sheet Short-Term Exposure Limit STEL TCLo Lowest published toxic concentration TWA Time Weighted Average VOC Volatile Organic Content

Technical Queries

Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Phone: +1-905-331-1396

Mailing Addresses

Manufacturing & Support 1210 Corporate Drive Burlington, Ontario,

Canada L7L 5R6

Disclaimer

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.