

SAI Global File #004008

Burlington, Ontario, Canada

CARBON CONDUCTIVE ASSEMBLY PASTE

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: 847

Other Means of Identification: Carbon Conductive Assembly Paste

Related Part # 847-3ML, 847-25ML, 847-40G, 847-1P, 847-1G

Recommended Use and Restriction on Use

Use: Improves connections between electrical contacts without oil bleeding.

Uses Advised Against: Do not process in a manner the material to form mist or dust

Details of Manufacturer or Importer

Manufacturer

MG Chemicals MG Chemicals (Head Office) 9347-193 Street 1210 Corporate Drive Surrey, British Columbia V4N 4E7 Burlington, Ontario L7L 5R6 CANADA CANADA

***** +1-800-340-0772 ***** +1-905-331-1396 FAX +1-800-340-0773 FAX +1-905-331-2682 support@mgchemicals.com info@mgchemicals.com E-MAIL E-MAIL

WEB www.mgchemicals.com

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) USA or CANADA—Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service CANADA—Call CANUTEC collect at +1-613-996-6666 or *666 on cellular phones

SAI Global File #004008 Burlington, Ontario, Canada

847

CARBON CONDUCTIVE ASSEMBLY PASTE

Section 2: Hazard(s) Identification

Classification of Hazardous Chemical

GHS Categories

Criteria		Category	Signal Word	Pictograms
Hazardous to the Aquatic Environment	Chronic	4	None	None

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity). Severity categories rankings do not allow comparisons between classes.

Label Elements

Signal Word	No signal word
Pictograms	Hazard Statements
No Symbol Mandated	H413: May cause long lasting harmful effects to aquatic life
Prevention	Precautionary Statements
P273	Avoid release to the environment.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None

847

CARBON CONDUCTIVE ASSEMBLY PASTE

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
non-hazardous ^{a)}	synthetic oil	80-90%
1333-86-4	carbon black	15-25%
112945-52-5	amorphous fumed silica	0.1-1%

a) Non-hazardous component under the U.S. OSHA HazCom 2012, the Canadian Controlled Product Regulations (SOR 88-66)

Section 4: First-Aid Measures

Exposure Condition	GHS Code/Symptoms/Precautionary Statements
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms low toxicity: mild irritation, redness, pain	
Response Rinse cautiously with water for 15 minutes. Remove lenses, if present and easy to do. Continue rinsing.	
	If eye irritation persists: Get medical advice or attention.
IF ON SKIN	P302 + P352
Immediate Symptoms	low toxicity: mild irritation
Response	Wash with plenty of water and soap.
IF SWALLOWED	P301 + P330 + P331
Immediate Symptoms	low toxicity—without known symptoms or adverse effects
Response	Rinse mouth. Do NOT induce vomiting.
IF INHALED	P304 + P340
Immediate Symptoms	low toxicity—without known symptoms or adverse effects
Response	Remove person to fresh air and keep comfortable for breathing.



847

ISO 9001:2015 Quality Management System

SAI Global File #004008 Burlington, Ontario, Canada

CARBON CONDUCTIVE ASSEMBLY PASTE

Section 5: Fire-Fighting Measures

Extinguishing Media In case of fire: Use dry chemical, carbon dioxide, chemical

foam, or water spray to extinguish. Do not use water jet.

Will burn if involved in a fire.

Specific Hazards None known

Combustion Products Produces carbon oxides (CO, CO₂), oxide of sulfur, and smoke.

Fire-Fighter Wear self-contained breathing apparatus and full fire-fighting

turn-out gear.

Section 6: Accidental Release Measures

Personal Protection See personal protection recommendations in Section 8.

Precautions for

Remove or keep away all sources of extreme heat or open

flames.

Environmental Precautions

Response

Avoid releasing to the environment. Prevent spill from entering

drains and waterways.

Containment Not applicable

Cleaning Collect liquid in a sealable, oil-resistant container. Sprinkle inert

absorbent compound onto spill, then sweep into the container.

Wipe up further residue with paper towel and place in

container. Wash spill area with soap and water to remove the

last traces of residue.

Disposal Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention Do not eat, drink, or smoke when using this product. Remove

contaminated clothing and protective equipment before entering

eating areas.

Handling Wear protective gloves, protective clothing, and eye protection.

Wash hands thoroughly after handling.

Avoid release to the environment.

Storage No special storage instructions needed.

RECOMMENDATION: Store in clean and dry area away from

incompatible substances.

Page **4** of **13**

SAI Global File #004008

Burlington, Ontario, Canada

847

CARBON CONDUCTIVE ASSEMBLY PASTE

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
carbon black ^{a)}	ACGIH	3.5 mg/m ³	Not established
	U.S.A. OSHA PEL	3.5 mg/m ³	Not established
	Canada AB	3.5 mg/m ³	Not established
	Canada BC	3 mg/m ³	Not established
	Canada ON	3.5 mg/m ³	Not established
	Canada QC	3.5 mg/m ³	Not established

Note: The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS database² and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long-term permissible exposure limits (PEL) for 8 h.

a) Respirable airborne particles

Engineering Controls

W	Δn	lati	Λn
•		alı	u

Keep airborne concentrations below the occupational exposure

limits (OEL).

Because the carbon black is bound to the liquid mixture, it does not present an airborne hazard under normal use. Ensure adequate ventilation if the product is mechanically misted or aerosolized.

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety

goggles.

RECOMMENDATION: Use safety glasses with lateral protection

(side shields).

Skin Protection For likely contacts, use of protective butyl rubber, neoprene,

or other chemically resistant gloves.

For incidental contacts, use nitrile, polyvinyl alcohol (PVA) or

other chemically resistant gloves.

Section continued on the next page

Page **5** of **13**

SAI Global File #004008 Burlington, Ontario, Canada

847

CARBON CONDUCTIVE ASSEMBLY PASTE

Respiratory Protection

For over-exposures up to 10 x OEL of vapors, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	Not applicable
Appearance	Paste,	Upper Flammability	Not
	black	Limit	applicable
Odor	Odorless	Vapor Pressure @20°C	Not applicable
Odor Threshold	Not applicable	Vapor Density	Not applicable
pH	Not available	Relative Density @25 °C	1.06
Freezing/Melting	Not	Solubility in	Slightly
Point	available	Water	soluble
Initial Boiling	Not	Partition Coefficient n-octanol/water	Not
Point	applicable		available
Flash Point a)	285 °C	Auto-ignition	Not
	[545 °F]	Temperature	applicable
Evaporation	Not	Decomposition	Not
Rate	applicable	Temperature	available
Flammability	Non Flammable	Viscosity @25 °C	>20.5 mm ² /s

a) Cleveland Open Cup



SAI Global File #004008 Burlington, Ontario, Canada

847

CARBON CONDUCTIVE ASSEMBLY PASTE

Section 10: Stability and Reactivity

Reactivity Not available

Chemical Stability Chemically stable at normal temperatures and pressures.

Conditions to Avoid Ignition sources and incompatible substances

Incompatibilities Strong oxidizing agents

Polymerization Will not occur

Decomposition Will not decompose under normal conditions. For thermal

decomposition, see combustion products in Section 5.

Section 11: Toxicological Information

Summary of Effects and Symptoms by Routes of Exposure

Eyes May causes mild eye irritation. The amorphous fumed silica are

mechanically abrasive, but will not permanently injure the eye.

Skin May cause mild skin irritation.

Inhalation Not a likely route of exposure. If dust or mist are present, they

may be irritating to the respiratory track.

Ingestion Not a likely route of exposure. It may cause gastrointestinal

discomfort.

Chronic Not applicable.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50	LD50	LC50
	oral	dermal	inhalation
carbon black	>15 g/kg	>3 g/kg	Not
	Rat	Rabbit	available
amorphous fumed silica	3 160 mg/kg	≥2 000 mg/kg	Not
	Rat	Rabbit	available

Note: Toxicity data from the RTECS² and ECHA were consulted. The data from supplier SDSs were also consulted.

Section continued on the next page



(allergic reactions)

(risk of cancer)

847

ISO 9001:2015 Quality Management System

SAI Global File #004008

Burlington, Ontario, Canada CARBON CONDUCTIVE ASSEMBLY PASTE

Other Toxicological Effects

Skin corrosion/irritation Based on available data, the classification criteria are

not met.

Serious eye damage/irritation Based on available data, the classification criteria are

not met.

Sensitization Based on available data, the classification criteria are

not met.

Carcinogenicity The carbon black [1333-86-4] is possibly carcinogenic

by airborne routes of exposures under WHMIS.

Because the carbon black is bound in the liquid mixture, it is not available as an airborne hazard

(dust) under normal use.

Carbon Black [1333-86-4]

IARC Group 2B: Possibly carcinogenic to humans

ACGIH A4: Not classified as a human carcinogen

CA Prop 65: Listed as a carcinogen (airborne, as

unbound particles of respirable size)

NTP: Not listed

Mutagenicity

Based on available data, the classification criteria are (risk of heritable genetic effects)

not met.

Reproductive Toxicity

(risk to sex functions)

Based on available data, the classification criteria are

not met.

Teratogenicity

Based on available data, the classification criteria are (risk of fetus malformation)

not met.

STOT-single exposure Based on available data, the classification criteria are

STOT-repeated exposure Based on available data, the classification criteria are

not met.

Aspiration hazard Based on available data, the classification criteria are

> not met. There are no category 1 components and the kinematic viscosity of the mixture is >20.5 mm²/s at

40 °C.



SAI Global File #004008 Burlington, Ontario, Canada

847

CARBON CONDUCTIVE ASSEMBLY PASTE

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (http://echa.europa.eu), and other reliable sources.

The synthetic oil used has highest environmental impact among listed components according to fish, daphnia magna, and algae data provided by oil suppliers. The acute fish toxicity has a LL50 (Lethal Loading Levels) >100 mg/L. Similarly, its daphnia magna acute toxicity is given as EL50 (Effective Load) >100 mg/L. And for the algae, it occurs at an EL50 >100 mg/L. Other components have higher threshold values from 1 000 mg/L to 10 000 mg/L.

Based on available data, carbon black is not classified as environmental hazard according to GHS criteria.

Acute Ecotoxicity

Available toxicity data does not meet classification thresholds.

Chronic Ecotoxicity

Available toxicity data does not meet classification thresholds.

Biodegradability

Not readily biodegradable.

Other Effects

Not available

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.



SAI Global File #004008

Burlington, Ontario, Canada

847

CARBON CONDUCTIVE ASSEMBLY PASTE

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations) and US DOT 49 CFR (Parts 100 to 185) Regulations.

Not Regulated

Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Not Regulated

Sea

Refer to IMDG Dangerous Goods Regulations.

Not Regulated

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL/NDSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

Section continued on the next page

Page **10** of **13**



SAI Global File #004008 Burlington, Ontario, Canada

847

CARBON CONDUCTIVE ASSEMBLY PASTE

USA

Other Classifications

HMIS® RATING

HEALTH:	*	0
FLAMMABILITY:		1
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product does not contain ingredients that are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product contains carbon black, but it is bound and exposures during normal conditions of uses are below the Safe Harbor Threshold.

Europe

RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Page **11** of **13**



SAI Global File #004008 Burlington, Ontario, Canada

847 CARBON CONDUCTIVE ASSEMBLY PASTE

Section 16: Other Information

SDS Prepared by MG Chemicals' Regulatory Department

04 March 2020 **Date of Revision Supersedes** 22 October 2019

Reason for Changes: Change to emergency phone numbers.

References

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®), MDL Information Systems, Inc.

Abbreviations

ACGIH EC50	American Conference of Governmental Industrial Hygienists (USA) Half maximal effective concentration
EL50	Half maximal effective loading
NOELR	No observable effect loading ratio
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Section continued on the next page

Page 12 of 13



SAI Global File #004008 Burlington, Ontario, Canada

847

CARBON CONDUCTIVE ASSEMBLY PASTE

Mailing Addresses *Manufacturing & Support*

1210 Corporate Drive

Burlington, Ontario, Canada

L7L 5R6

Head Office

9347-193rd Street

Surrey, British Columbia, Canada

V4N 4E7

Disclaimer

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional,

national, and international regulations.