

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: 9460TC

Other Means of Identification: Thermally Conductive 1-Part Epoxy Adhesive / Époxy

Thermoconducteur Monocomposant

Related Part # 9460TC-3ML, 9460TC-10ML

Recommended Use and Restriction on Use

Use: Thermally conductive adhesive

Uses Advised Against: Not for use as a spray coating

Details of Manufacturer or Importer

Manufacturer

MG Chemicals 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA

 #1-800-340-0772

 FAX
 +1-800-340-0773

 E-MAIL
 support@mgchemicals.com

 WEB
 www.mgchemicals.com

MG Chemicals (Head Office)

9347-193 Street

Surrey, British Columbia V4N 4E7

CANADA

+1-905-331-1396 FAX +1-905-331-2682 E-MAIL info@mgchemicals.com

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) USA or CANADA—Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service CANADA—Call CANUTEC collect at +1-613-996-6666 or *666 on cellular phones



Section 2: Hazard(s) Identification

Classification of Hazardous Chemical

GHS Categories

Criteria		Category	Signal Word	Pictograms
Sensitization	Skin	1	Warning	Exclamation
Eye Irritation		2	Warning	Exclamation
Skin Irritation		2	Warning	Exclamation
Hazardous to the Aquatic Environment	Chronic	2	None	Environment

Note: The degree of severity is ranked within each hazard class from

1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	WARNING
Pictograms	Hazard Statements
	H317: May cause an allergic skin reaction
	H319: Causes serious eye irritation
\	H315: Causes skin irritation
***	H411: Toxic to aquatic life with long lasting effects

Section continued on the next page



Continued...

Prevention	Precautionary Statements
P102	Keep out of reach of children.
P261	Avoid breathing fumes or vapors.
P280	Wear protective gloves, and eye protection.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
Response	Precautionary Statements
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P302 + P352	IF ON SKIN: Wash with plenty water.
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None



Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
28064-14-4	phenol, polymer with formaldehyde, glycidyl ether	37%
21645-51-2	aluminum trihydrate	26%
1314-13-2	zinc oxide	17%
9003-35-4	2-methoxy-6-methylphenol	4%
68609-97-2	alkyl glycidyl ether	1%
64742-47-8	distillates (petroleum), hydrotreated light	1%
70700-21-9	monomethyl phosphate ethoxylated	1%

Section 4: First-Aid Measures

Exposure Condition	GHS Code/Symptoms/Precautionary Statements		
IF ON SKIN	P302 + P352, P362 + P364, P333 + P313		
Immediate	redness, irritation, allergic contact dermatitis, rash		
Response	Wash with plenty water.		
	Take off contaminated clothing and wash it before reuse.		
	If skin irritation or rash occurs: Get medical advice or attention.		
IF IN EYES	P305 + P351 + P338, P337 + P313		
Immediate Symptoms	redness, irritation		
Response	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
	If eye irritation persists: Get medical advice or attention.		
IF INHALED	P304 + P340		
Immediate Symptoms	low toxicity: no symptoms known		
Response	Remove person to fresh air and keep comfortable for breathing.		
IF SWALLOWED	P301 + P330, P331		
Immediate Symptoms	abdominal pain, diarrhea, nausea, vomiting		
Response	Rinse mouth. Do NOT induce vomiting.		



SAI Global File #004008 Burlington, Ontario, Canada

9460TC

Section 5: Fire-Fighting Measures

Extinguishing Media In case of fire: Use extinguishing media suitable for

surrounding materials.

Specific Hazards Not flammable or combustible, but burns if involved in a fire.

Produces irritating smoke of unknown toxicity in fires.

Zinc oxide fumes exposure may lead to a metal fume fever.

Prevent fire-fighting wash from entering waterway or sewer

system.

Combustion Products Produces carbon oxides (CO,CO₂), phenolics, zinc oxide

fumes, and other toxic fumes.

Fire-Fighter Wear self-contained breathing apparatus and full fire-fighting

turn-out gear.

Section 6: Accidental Release Measures

Personal Protection See personal protection recommendations in Section 8.

Precautions for

Response

Avoid breathing fumes or vapors. Remove or keep away all

sources of extreme heat or open flames.

Environmental

Precautions

Avoid releasing to the environment. Prevent spill from

entering drains and waterways.

Containment Methods

Not applicable—not readily flowable.

Cleaning Methods

Collect liquid in a sealable, chemical-resistant container. Wipe off residues with paper towels and place the used towels in the waste container. Use soap and water to remove the last

traces of residue.

Disposal Methods

Dispose of spill waste according to Section 13.



Section 7: Handling and Storage

Prevention Keep out of reach of children.

Avoid breathing fumes or vapors.

Contaminated work clothing should not be allowed out of the

workplace.

Avoid release to the environment.

Handling Wear protective gloves and eye protection. Wash hands

thoroughly after handling. Take off contaminated clothing and

wash it before reuse.

Collect spillage.

Storage RECOMMENDATION: Keep in a dry and clean area, away from

incompatible substances.

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country or	Long Term	Short Term
	Vendor	Exposure Limits (PEL)	Exposure Limits (STEL)
aluminum metal	ACGIH	1 mg/m ³	Not established
and insoluble	U.S.A. OSHA PEL	15 mg/m ³	Not established
compounds ^{a)}	Canada AB	10 mg/m ³	Not established
	Canada BC	1 mg/m ³	Not established
	Canada ON	1 mg/m³	Not established
	Canada QC	10 mg/m ³	Not established
zinc oxide	ACGIH	2 mg/m ³	Not established
(dust/mist)	U.S.A. OSHA PEL	2 mg/m ³	10 mg/m ³
	Canada AB	2 mg/m ³	10 mg/m ³
	Canada BC	2 mg/m ³	10 mg/m ³
	Canada ON	2 mg/m ³	10 mg/m ³
fumes	Canada QC	2 mg/m ³	10 mg/m ³
dust	Canada QC	10 mg/m ³	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS database² and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are usually for 15 min and long term permissible exposure limits (PEL) for 8 h.

Section continued on the next page

Page **6** of **16**

SAI Global File #004008 Burlington, Ontario, Canada

9460TC

Engineering Controls

Ventilation Keep airborne concentrations below the occupational exposure

limits (OEL).

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety

goggles.

RECOMMENDATION: Ensure that glasses have side shields for

lateral protection.

Skin Protection For incidental contacts, use nitrile, latex, neoprenee or other

chemically resistant gloves.

Respiratory Protection If exposed to fumes or dust above the exposure limit, wear a

suitable respirator meeting local, regional, and national

guidelines.

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor

cartridge or with an independent air supply.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3.

The respirator should be fitted to the employee by a

professional. Ensure vapor cartridges are stored in sealed

plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Burlington, Ontario, Canada





9460TC

Section 9: Physical and Chemical Properties

Physical State	Solid	Lower Flammability Limit	Not available
Appearance	White, paste	Upper Flammability Limit	Not available
Odor	Mild	Vapor Pressure @20°C	Not available
Odor Threshold	Not available	Vapor Density	Not available
рH	Not available	Relative Density @25°C	1.64
Freezing/Melting Point	Not available	Solubility in Water	Insoluble
Initial Boiling Point ^{a)}	≥150 °C [≥302 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point	Not available	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability	Not Flammable	Viscosity @40 °C	>20.5 mm ² /s

a) The boiling point is based on the phenol, polymer with formaldehyde, glycidyl ether resin component.

Section 10: Stability and Reactivity

Reactivity	Reacts exo	thermically v	with amines.
------------	------------	---------------	--------------

Chemical Chemically stable at normal temperatures and pressures.

Stability

Conditions to AvoidAvoid ignition sources, open flames, and incompatible substances.

Do not use in away that forms mist or aerosolizes the product.

Incompatibilities Avoid oxidizing agents, acids, bases and peroxides.

Polymerization Will not occur

Decomposition Will not decompose under normal conditions. For thermal

decomposition, see combustion products in Section 5.



Section 11: Toxicological Information

Summary of Effects and Symptoms by Routes of Exposure

Eyes May cause redness, and irritation.

Skin Causes skin redness, irritation, or allergic contact dermatitis.

Inhalation Low toxicity: no symptoms known or expected.

Ingestion May cause abdominal pain, diarrhea, nausea, and vomiting.

Chronic Prolonged and repeated exposure may lead to skin sensitization.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50	LD50	LC50
	oral	dermal	inhalation
phenol, polymer with formaldehyde, glycidyl ether	>5 000 mg/kg	>2 000 mg/kg	Not
	Rat	Rat	established
aluminum trihydrate	79 000 mg/kg	Not	Not
	Rat	established	established
zinc oxide	7 950 mg/kg	Not	2 500 mg/m ³
	Mouse	established	Mouse
2-methoxy-6-methylphenol	Not	Not	Not
	established	established	established
alkyl glycidyl ether	19 200 mg/kg	4 000 mg/kg	Not
	Rat	Rabbit	established
distillates (petroleum),	8 000 mg/kg	4 000 mg/kg	Not
hydrotreated light	Rat	Rat	established
monomethyl phosphate ethoxylated	Not	Not	Not
	established	established	established

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier SDS were also consulted.

Section continued on the next page



SAI Global File #004008 Burlington, Ontario, Canada

9460TC

Other Toxicological Effects

Skin corrosion/irritation Phenol, polymer with formaldehyde, glycidyl ether,

> alkyl glycidyl ether, and distillates (petroleum), hydrotreated light are known skin irritants.

Serious eve

damage/irritation

Phenol, polymer with formaldehyde, glycidyl ether, and

2-methoxy-6-methylphenol cause serious eye

irritation.

Sensitization Phenol, polymer with formaldehyde, glycidyl ether; (allergic reactions)

2-methoxy-6-methylphenol; and alkyl glycidyl ether

are known skin sensitizers.

Animal studies show that epoxy components may

cause skin sensitization.

Carcinogenicity None of the ingredients are classified or listed as a (risk of cancer)

carcinogen by IARC, ACGIH, CA Prop 65, or NTP.

Mutagenicity Based on available data, the classification criteria are

(risk of heritable genetic effects) not met.

Reproductive Toxicity

(risk to sex functions)

Teratogenicity (risk of fetus

malformation)

Based on available data, the classification criteria are

Based on available data, the classification criteria are

not met.

not met.

STOT-single exposure Based on available data, the classification criteria are

not met.

STOT-repeated exposure Based on available data, the classification criteria are

not met.

Aspiration hazard Based on available data, the classification criteria are

not met.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (), and other reliable sources.

In Europe, similar epoxy resin mixtures with CAS# 28064-14-4 are generally classified as chronic category 2 marine pollutant due to LC50 96 h of >1 mg/L but ≤ 10 mg/L.

Contains zinc oxide which is an acute and chronic category 1 solid (non-biodegradable, minimal LC50 of 0.042 mg/L) that is very toxic to aquatic life.

The distillate (petroleum) hydrotreated light has a chronic aqueous toxicity of category 2.

Aluminum trihydrate, phenol, polymer with formaldehyde, and alkyl glycidyl ether are not classifiable as ecotoxic hazards under GHS criteria.

Acute Ecotoxicity

See chronic ecotoxicity.

Chronic Ecotoxicity

Category 2

Toxic to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

Biodegradability

Not readily biodegradable

Bioaccumulation

Not available

Other Effects

Not available

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.



Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

TDG: Sizes 5 kg and under 9460TC-3ML, 9460TC-10ML
NOT REGULATED in TDG
per Special Provisions 99

CFR: Sizes 5 kg and under **NOT REGULATED** in 49 CFR per exception 171.4 (c)(2)

Sizes greater than 5 kg FOR REFERENCE ONLY UN number: UN3077

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (zinc oxide, phenol, polymer with formaldehyde, glycidyl ether)

Class: 9

Packing Group: III Marine Pollutant: Yes

Special Provision 99 (2): These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

171.4 (c) Exceptions:

(2) Single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other requirements of this subchapter provided the packagings meet the general requirements in §§ 173.24 and 173.24a. This exception does not apply to marine pollutants that are a hazardous waste or a hazardous substance. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this subchapter relevant to any additional hazards continue to apply.

Section continued on the next page



SAI Global File #004008 Burlington, Ontario, Canada

9460TC

Air

Refer to ICAO-IATA regulations.

Sizes 5 kg and under 9460TC-3ML, 9460TC-10ML

NOT REGULATED

Not Restricted, as per Special Provisions A197

Sizes over 5 kg FOR REFERENCE ONLY UN number: UN3077 Shipping Name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (zinc oxide, phenol, polymer with formaldehyde, glycidyl ether)

Class: 9

Packing Group: III Marine Pollutant: Yes

Special Provision A197: These substances when transported in single or combination packagings containing net quantity per single or inner packaging of less than 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Sea

Refer to IMDG regulations.

Sizes 5 kg and under 9460TC-3ML, 9460TC-10ML

NOT REGULATED

per clause 2.10.2.7

Sizes over 5 kg FOR REFERENCE ONLY UN number: UN3077 Shipping Name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (zinc oxide; phenol, polymer with formaldehyde, glycidyl ether)

Class: 9

Packing Group: III Marine Pollutant: Yes

2.10.2.7: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provision of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this Code relevant to any additional hazards continue to apply.

Note: Shipper must be appropriately <u>trained and certified</u> before involvement with the transport of dangerous goods.

Page 13 of 16



Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

USA

Other Classifications

HMIS® RATING

HEALTH: * 2 FLAMMABILITY: 1 PHYSICAL HAZARD: 0 PERSONAL PROTECTION:

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)


This product contains zinc compounds (CAS# 1314-13-2) which can be subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372 under certain conditions.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

Section continued on the next page

Page **14** of **16**





9460TC

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any substances on the California Proposition 65 list.

Europe

RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

SDS Prepared by Regulatory Affairs Department

Date of Review 22 January 2021
Supersedes Not applicable
Reason for Changes: New release.

Reference

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Section continued on the next page

SAI Global File #004008 Burlington, Ontario, Canada

9460TC

Abbreviations

American Conference of Governmental Industrial Hygienists (USA) ACGIH EC50 Half maximal effective concentration EL50 Half maximal effective loading

IARC International Agency for Research on Cancer

No observable effect loading ratio NOELR NTP National Toxicology Program

Globally Harmonized System of Classification of Labeling of Chemicals GHS

LC50 Lethal Concentration 50%

Lowest published lethal concentration LCLo

LD50 Lethal Dose 50%

Occupational Exposure Limit OEL PEL Permissible Exposure Limit

SDS Safety Data Sheet

STEL Short-Term Exposure Limit

TCLo Lowest published toxic concentration

TWA Time Weighted Average VOC Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAOs

are located at www.mgchemicals.com.

Email: support@mqchemicals.com Telephone: +1-905-331-1396

Head Office **Mailing Addresses** *Manufacturing & Support*

> 1210 Corporate Drive 9347-193rd Street

Burlington, Ontario, Canada Surrey, British Columbia, Canada

L7L 5R6 V4N 4E7

Disclaimer

This safety data sheet is provided as an information resource only. M.G. Chemicals, Ltd. believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional,

national, and international regulations.