

Page 1/11

according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2024 Version number 5 (replaces version 4) Revision: 15.04.2024

1.1	Product identifier
Oth	le name: <u>841AR-Liquid</u> er Means of Identification: er Shield™ Nickel Conductive Paint / Nickel Conductive Paint
841/ UFI: 1.2 No f App	nted Part Number: AR-Liquid, 841AR-15ML, 841AR-55ML, 841AR-150ML, 841AR-900ML, 841AR-3.78L 49K0-P0NQ-G00G-9UK5 Relevant identified uses of the substance or mixture and uses advised against urther relevant information available. Iication of the substance / the mixture trically conductive coating and EMI/RFI shield
	Details of the supplier of the safety data sheet M.G. Chemicals Ltd. ufacturer/Supplier:
1210 Burl CAN	Chemicals Ltd. (Head Office) O Corporate Drive ington, Ontario L7L 5R6 IADA 800-340-0772
Hea Sed UNI	Chemicals me House, 23 Bliston Street gely Dudley DY3 1JA. TED KINGDOM I) 1663 362888 sales@mgchemicals.com
Leve Zon	Chemicalst Ltd. el 2, Vision Exchange, Building Territorials Street, e 1, Central Business, District, rkara CBD 1070, .TA
1.4 Veri Othe Men In E	her information obtainable from: sds@mgchemicals.com Emergency telephone number: sk 3E (Access code: 335388), +(44) 20 3514787 er emergency telephone numbers: +(0) 800 680 0425 nbers of the public seeking specific information on poisons should contact: ngland and Wales: NHS 111 - dial 111 cotland: NHS 24 - dial 111
USA	hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) or CANADA-Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service acces a: 335388)
For	emergencies involving the transport of dangerous goods; 24/7 service IADA-Call CANUTEC collect at +1-613-996-6666 or *666 on cellular phones

(Contd. on page 2)

Printing date 15.04.2024 Version number 5 (replaces version 4) Revision: 15.04.2024 Trade name: 841AR-Liquid (Contd. of page 1) 2 Hazards identification · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. GHS08 health hazard H351 Suspected of causing cancer. Route of exposure: Inhalation. Carc. 2 STOT RE 1 H372 Causes damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation. GHS07 Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. · 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labelling: nickel powder (particle diameter < 1 mm) Hazard statements H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H351 Suspected of causing cancer. Route of exposure: Inhalation. H336 May cause drowsiness or dizziness. H372 Causes damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation. H412 Harmful to aquatic life with long lasting effects. Precautionary statements P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe dust/fume/gas/mist/vapours/spray. (Contd. on page 3) GB

Printing date 15.04.2024	Version number 5 (replaces version 4)	Revision: 15.04.2024

Trade name: 841AR-Liquid

507/	(Contd. of page 2)
P271	Use only outdoors or in a well-ventilated area.
P303+P361	+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.
	Rinse skin with water [or shower].
P305+P351	+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
· Additional	information:
EUH208: C	Contains nickel powder (particle diameter < 1 mm). May produce an allergic
reaction.	
· 2.3 Other h	azards
· Results of	PBT and vPvB assessment
· PBT: Not ap	oplicable.
• vPvB: Not a	
	ion of endocrine-disrupting properties
	Disruptor substance $\geq 0.1\% = none$

3 Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

• 1	Dange	erous	com	ponents:
-----	-------	-------	-----	----------

Bungereue compe		
EINECS: 231-111-4	nickel powder (particle diameter < 1 mm) � Carc. 2, H351; STOT RE 1, H372; � Skin Sens. 1, H317; Aquatic Chronic 3, H412	48.0%
	dimethyl carbonate 🚸 Flam. Liq. 2, H225	16.0%
	acetone	13.0%
	heptan-2-one � Flam. Liq. 3, H226; � Acute Tox. 4, H302; Acute Tox. 4, H332	10.0%
EINECS: 203-603-9	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 tion: For the wording of the listed hazard phrases refer to section	2.0% 16.

4 First aid measures

· 4.1 Description of first aid measures

• General information: Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

(Contd. on page 4)

[—] GB

(Contd. of page 3)

according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2024	Version number 5 (replaces version 4)	Revision: 15.04.2024
--------------------------	---------------------------------------	----------------------

Trade name: 841AR-Liquid

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • 5.2 Special hazards arising from the substance or mixture

- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand diatomite, acid binders, universal binders, sawo

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

• 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed. Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 5)

GB

according to Regulation (EC) No 1907/2006, Article 31 Printing date 15.04.2024 Version number (Contd. of page 4) • 7.3 Specific end use(s) No further relevant information available. 8 Exposure controls/personal protection · 8.1 Control parameters Ingredients with limit values that require monitoring at the workplace: 7440-02-0 nickel powder (particle diameter < 1 mm) WEL Long-term value: 0.5 mg/m³ as Ni; Sk; Carc

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

110-43-0 heptan-2-one

WEL Short-term value: 475 mg/m³, 100 ppm Long-term value: 237 mg/m³, 50 ppm Sk

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)


GB

5 (replaces version 4)	Revision: 15.04.2024

Trade name: 841AR-Liquid

Printing date 15.04.2024 Version number 5 (replaces version 4) Revision: 15.04.2024

Trade name: 841AR-Liquid



Printing date 15.04.2024 Version number 5 (replaces version 4) Revision: 15.04.2024

Trade name: 841AR-Liquid

Oberna in condition	(Contd. of page 6)
Change in condition	Not determined.
Evaporation rate	Not determined.
Information with regard to physical haza	rd
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

10 Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral LD50 16,700 mg/kg (rat) Inhalative LC50/4 h 110 mg/l

616-38-6 dimethyl carbonate

LD50 13,000 mg/kg (rat) Oral >5,000 mg/kg (rabbit) LD50 Dermal 67-64-1 acetone Oral LD50 5,800 mg/kg (rat) LD50 20,000 mg/kg (rabbit) Dermal 110-43-0 heptan-2-one Oral LD50 1,670 mg/kg (rat)

(Contd. on page 8)

(Contd. of page 7)

according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2024 Version number 5 (replaces version 4) Revision: 15.04.2024

Trade name: 841AR-Liquid

Dermal LD50 12,600 mg/kg (rabbit)

108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 8,532 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

- · Serious eye damage/irritation Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Suspected of causing cancer. Route of exposure: Inhalation.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure

Causes damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.

Aspiration hazard Based on available data, the classification criteria are not met.

- · 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

12 Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground. Harmful to aquatic organisms

13 Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · European waste catalogue
- HP3 Flammable
- HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
- HP7 Carcinogenic

(Contd. on page 9)

[—] GB

rade name: 841AR-Liquid	
	(Contd. of page 8)
HP13 Sensitising	
HP14 Ecotoxic	
· Uncleaned packaging:	
Recommendation: Disposal must be mad	le according to official regulations. ; if necessary together with cleansing agents.
4 Transport information	
· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN1263
• 14.2 UN proper shipping name	
ADR	1263 PAINT
·IMDG	PAINT
· IATA	Paint
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
 14.4 Packing group 	
· ADR, IMDG, IATA	11
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler	22
code):	33
· EMS Number:	F-E, <u>S-E</u> B
 Stowage Category 14.7 Maritime transport in bulk accordir 	
to IMO instruments	Not applicable.
• Transport/Additional information:	
· ADR · Limited quantities (LQ)	5L
• Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30
	ml
	Maximum net quantity per outer packaging: 500 ml
· Transport category	2
Tunnel restriction code	D/E
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30
	ml Mariana shararatika sa kasisa 50
	Maximum net quantity per outer packaging: 500 ml
	P21

Printing date 15.04.2024	Version number 5 (replaces version 4)	Revision: 15.04.2024
Trade name: 841AR-Liquid	1	
· UN "Model Regulation	": UN 1263 PAINT, 3, II	(Contd. of page 9)
15 Regulatory informa	ation	
substance or mixture Poisons Act Regulated explosives p		ation specific for the
None of the ingredients in Regulated poisons		
None of the ingredients of • Reportable explosives		
67-64-1 acetone: Listed · Reportable poisons		
None of the ingredients i	is listed.	
 Seveso category P5c F Qualifying quantity (to Qualifying quantity (to REGULATION (EC) No DIRECTIVE 2011/65/EU 	stances - ANNEX I None of the ingredients LAMMABLE LIQUIDS nnes) for the application of lower-tier req nnes) for the application of upper-tier req 1907/2006 ANNEX XVII Conditions of restriction of the use of certain have ic equipment – Annex II	uirements 5,000 t quirements 50,000 t ction: 3, 27
None of the ingredients • REGULATION (EU) 201	is listed. 19/1148 D EXPLOSIVES PRECURSORS (Upper lim	it value for the purpose
None of the ingredients i		
67-64-1 acetone • Regulation (EC) No 27	3/2004 on drug precursors	
	11/2005 laying down rules for the monit ird countries in drug precursors	oring of trade between
· 15.2 Chemical safety a	ssessment: ssment has not been carried out.	

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.

(Contd. on page 11)

GB

Printing date 15.04.2024	Version number 5 (replaces version 4)	Revision: 15.04.2024
--------------------------	---------------------------------------	----------------------

Trade name: 841AR-Liquid

	(Contd. of page 10
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
	66 Repeated exposure may cause skin dryness or cracking.
EUHUO	o nepeated exposure may cause skin dryness of cracking.
· Depart	ment issuing SDS: Product safety department.
	ct: sds@mgchemicals.com
	f previous version: 12.03.2024
	n number of previous version: 4
	viations and acronyms:
	cord relatif au transport international des marchandises dangereuses par route (European Agreeme
	ing the International Carriage of Dangerous Goods by Road)
	ternational Maritime Code for Dangerous Goods
	ernational Air Transport Association obally Harmonised System of Classification and Labelling of Chemicals
	European Inventory of Existing Commercial Chemical Substances
	European List of Notified Chemical Substances
	emical Abstracts Service (division of the American Chemical Society)
	atile Organic Compounds (USA, EU)
	thal concentration, 50 percent
LD50: Lei	thal dose, 50 percent
PBT: Per	rsistent, Bioaccumulative and Toxic
	ry Persistent and very Bioaccumulative
	ite toxicity estimate values
,	2: Flammable liquids – Category 2
	. 3: Flammable liquids – Category 3
	x. 4: Acute toxicity – Category 4
	2: Serious eye damage/eye irritation – Category 2 s. 1: Skin sensitisation – Category 1
	Carcinogenicity – Category 2
	E 3: Specific target organ toxicity (single exposure) – Category 3
	= 0. opecific target organ toxicity (repeated exposure) – Category 1
	Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3