

Page 1/11

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.03.2024 Version number 6 (replaces version 5) Revision: 04.03.2024

1 Identification of the automation and of the company/undertaking
1 Identification of the substance/mixture and of the company/undertaking
1.1 Product identifier
 Trade name: <u>842ER-Part A</u> Other Means of Identification: Super Shield Silver Epoxy Conductive Paint
 Related Part Number: 842ER-A-Liquid, 842ER-A-60ML, 842ER-A-250ML, 842ER-A-900ML, 842ER-A-4.25L UFI: APR0-K04Q-S00P-YC97 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. Application of the substance / the mixture Silver conductive epoxy resin
 1.3 Details of the supplier of the safety data sheet M.G. Chemicals Ltd. Manufacturer/Supplier:
MG Chemicals Ltd. (Head Office) 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA +(1) 800-340-0772
MG Chemicals Heame House, 23 Bliston Street Sedgely Dudley DY3 1JA. UNITED KINGDOM +(44) 1663 362888 sales@mgchemicals.com
MG Chemicalst Ltd. Level 2, Vision Exchange, Building Territorials Street, Zone 1, Central Business, District, Birkirkara CBD 1070, MALTA
 Further information obtainable from: sds@mgchemicals.com 1.4 Emergency telephone number: Verisk 3E (Access code: 335388), +(44) 20 3514787 Other emergency telephone numbers: +(0) 800 680 0425 Members of the public seeking specific information on poisons should contact: In England and Wales: NHS 111 - dial 111 In Scotland: NHS 24 - dial 111
For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) USA or CANADA-Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)
For emergencies involving the transport of dangerous goods; 24/7 service CANADA-Call CANUTEC collect at +1-613-996-6666 or *666 on cellular phones GB

(Contd. on page 2)

Printing date 04.03.2024 Version number 6 (replaces version 5) Revision: 04.03.2024 Trade name: 842ER-Part A (Contd. of page 1) 2 Hazards identification 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. GHS05 corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS09 environment Aquatic Acute 1 H400 Very toxic to aquatic life. Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects. GHS07 Skin Irrit. 2 H315 Causes skin irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness. · 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. Hazard pictograms GHS02 GHS05 GHS07 GHS09 · Signal word Danger - Hazard-determining components of labelling: butan-1-ol oxirane,2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer · Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H318 Causes serious eye damage. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness. H410 Very toxic to aquatic life with long lasting effects. Precautionary statements P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P271 Use only outdoors or in a well-ventilated area. (Contd. on page 3) GB

Printing date 04.03.2024	Version number 6 (replaces version 5)	Revision: 04.03.2024
Trade name: 842ER-Part A		
		(Contd. of page 2)
	ar protective gloves, protective clothing, and e	
	N EYES: Rinse cautiously with water for s	
	tact lenses, if present and easy to do. Continu	ie rinsing.
P310 Imr	nediately call a POISON CENTER/doctor.	
P405 Sto	re locked up.	
 2.3 Other hazards 		
 Results of PBT and v 	PvB assessment	
• PBT: Not applicable.		
vPvB: Not applicable.		
	locrine-disrupting properties	
	ibstance $\geq 0.1\% = none$	
3 Composition/info	rmation on ingredients	

· 3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

	Silver (Powder <0.0001mm) Aquatic Acute 1, H400 (M=1000); Aquatic Chronic 1, H410 (M=100)	46.0%
CAS: 110-19-0 EINECS: 203-745-1	isobutyl acetate 🚸 Flam. Liq. 2, H225, EUH066	33.0%
CAS: 71-36-3 EINECS: 200-751-6	butan-1-ol ♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	8.0%
	o x i r a n e, 2, 2'-[(1-methylethylidene)bis(4, 1 phenyleneoxymethylene)]bis-, homopolymer Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317	- 8.0%
EINECS: 238-877-9	Talc (Mg3H2(SiO3)4) STOT SE 1, H370; STOT RE 1, H372 mponents and components below classification threshold	2.0%
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate	0.3% 16.

4 First aid measures

· 4.1 Description of first aid measures

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor. • After swallowing: If symptoms persist consult doctor.

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

- GB

Printing date 04.03.2024 Version number 6 (replaces version 5) Revision: 04.03.2024

Trade name: 842ER-Part A

(Contd. of page 3)

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. **5.2 Special hazards arising from the substance or mixture**

- Vapors are heavier than air. Vapors may travel to sources of ignition near the ground. They can cause flash fire or ignite explosively.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

• 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent. Dispose contaminated material as waste according to section 13.

Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly. • Information about fire - and explosion protection:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 5)

GB

- GB -

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.03.2024

Version number 6 (replaces version 5)

Revision: 04.03.2024

Trade name: 842ER-Part A

	(Contd. of page 4)
8 Exposure controls/personal	protection
110-19-0 isobutyl acetate WEL Short-term value: 903 mg/m³, 1 Long-term value: 724 mg/m³, 13	
71-36-3 butan-1-ol WEL Short-term value: 154 mg/m³, 5 Sk	0 ppm alid during the making were used as basis.
 8.2 Exposure controls Appropriate engineering controls 	No further data; see section 7. uch as personal protective equipment beasures: les and feed. ontaminated clothing e end of work.
Protective gloves	
preparation. Due to missing tests no recommend the preparation/ the chemical mixture Selection of the glove material on c and the degradation Material of gloves The selection of the suitable gloves of marks of quality and varies from	consideration of the penetration times, rates of diffusion does not only depend on the material, but also on further manufacturer to manufacturer. As the product is a he resistance of the glove material can not be calculated hecked prior to the application.
	to be found out by the manufacturer of the protective
Tightly sealed goggles	
9 Physical and chemical prope	erties
 9.1 Information on basic physical a General Information Physical state 	and chemical properties Fluid (Contd. on page 6)

Printing date 04.03.2024

Version number 6 (replaces version 5)

Revision: 04.03.2024

Trade name: 842ER-Part A

	(Contd. of page 5)
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and	endetermined.
boiling range	116 °C
Flammability	Highly flammable.
Lower and upper explosion limit	riging hannable.
Lower:	1 Vol %
Upper:	11 Vol %
Flash point:	18 °C
Auto-ignition temperature:	345 °C
Decomposition temperature:	Not determined.
	Not determined. Not determined.
pH Viesesity	Not determined.
Viscosity:	Not determined
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	- u · u
water:	Fully miscible.
Partition coefficient n-octanol/water (log	
value)	Not determined.
Vapour pressure at 20 °C:	20 hPa (110-19-0 isobutyl acetate)
Density and/or relative density	
Density at 20 °C:	1.65 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of	of
health and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation
	of explosive air/vapour mixtures are possible.
Solvent content:	
Organic solvents:	41.3 %
VOC (EC)	41.30 %
Solids content:	2.7 %
Change in condition	L ., /0
-	Not determined.
Evaporation rate	
Information with regard to physical hazar	d
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
	(Contd on page 7)

(Contd. on page 7)

- GB

Printing date 04.03.2024 Version number 6 (replaces version 5) Revision: 04.03.2024

Trade name: 842ER-Part A

Substances and mixtures, which smit		(Contd. of page 6
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

10 Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral LD50 9,875 mg/kg (rat)

110-19-0 isobutyl acetate

Oral LD50 13,400 mg/kg (rat)

71-36-3 butan-1-ol

Oral LD50 790 mg/kg (rat)

Dermal LD50 3,400 mg/kg (rabbit)

Inhalative LC50/4 h 8,000 mg/l (rat)

· Skin corrosion/irritation Causes skin irritation.

- · Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.

(Contd. on page 8)

Printing date 04.03.2024	Version number 6 (replaces version 5)	Revision: 04.03.2024
--------------------------	---------------------------------------	----------------------

Trade name: 842ER-Part A

- · **12.3 Bioaccumulative potential** No further relevant information available. (Contd. of page 7)
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Very toxic for aquatic organisms

13 Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · European waste catalogue
- HP3 Flammable

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP14 Ecotoxic

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA
- · 14.2 UN proper shipping name
- · ADR
- · IMDG
- · IATA
- · 14.3 Transport hazard class(es)
- · ADR, IMDG



· Class

UN1263

1263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT, MARINE POLLUTANT Paint

3 Flammable liquids.

(Contd. on page 9)

Printing date 04.03.2024 Version number 6	(replaces version 5) Revision: 04.03.2024	
Trade name: 842ER-Part A		
· Label · IATA	(Contd. of page 8)	
· Class · Label · 14.4 Packing group · ADR, IMDG, IATA · 14.5 Environmental hazards:	3 Flammable liquids. 3 II Product contains environmentally hazardous	
 Marine pollutant: Special marking (ADR): 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category 14.7 Maritime transport in bulk according to IMO instruments 	substances: oxirane,2,2'-[(1-methylethylidene) bis(4,1-phenyleneoxymethylene)]bis-, homopolymer Symbol (fish and tree) Symbol (fish and tree) Warning: Flammable liquids. 33 F-E, <u>S-E</u> B	
· Transport/Additional information:		
 ADR Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml	
 Transport category Tunnel restriction code 	2 D/E	
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500	
· UN "Model Regulation":	Maximum net quantity per outer packaging. See ml UN 1263 PAINT, 3, II, ENVIRONMENTALLY HAZARDOUS	

15 Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

(Contd. on page 10)

[—] GB

rinting date 04.03.2024	Version number 6 (replaces version 5)	Revision: 04.03.2024
rade name: 842ER-Part	Α	
· Regulated poisons		(Contd. of page 9)
None of the ingredient		
None of the ingredient • Reportable poisons	's is listed.	
None of the ingredient	's is listed.	
E1 Hazardous to the P5c FLAMMABLE LIC	Aquatic Environment QUIDS	
P5c FLAMMABLE LIC • Qualifying quantity (• Qualifying quantity (• REGULATION (EC) N • <u>DIRECTIVE 2011/65/</u> electrical and electro	QUIDS (tonnes) for the application of lower-tier re (tonnes) for the application of upper-tier re lo 1907/2006 ANNEX XVII Conditions of rest EU on the restriction of the use of certain onic equipment – Annex II	riction: 3
P5c FLAMMABLE LIC Qualifying quantity (REGULATION (EC) N DIRECTIVE 2011/65/I electrical and electro None of the ingredient REGULATION (EU) 2 Annex I - RESTRICT	QUIDS (tonnes) for the application of lower-tier re (tonnes) for the application of upper-tier re to 1907/2006 ANNEX XVII Conditions of rest EU on the restriction of the use of certain to onic equipment – Annex II (to is is listed. 2019/1148 ED EXPLOSIVES PRECURSORS (Upper lii)	equirements 200 t riction: 3 hazardous substances in
P5c FLAMMABLE LIC Qualifying quantity (Qualifying quantity (REGULATION (EC) N DIRECTIVE 2011/65// electrical and electro None of the ingredient REGULATION (EU) 2 Annex I - RESTRICT of licensing under A None of the ingredient	DUIDS (tonnes) for the application of lower-tier re (tonnes) for the application of upper-tier re to 1907/2006 ANNEX XVII Conditions of rest EU on the restriction of the use of certain to onic equipment – Annex II (s is listed. 2019/1148 ED EXPLOSIVES PRECURSORS (Upper lin rticle 5(3))	equirements 200 t riction: 3 hazardous substances in
P5c FLAMMABLE LIC Qualifying quantity (REGULATION (EC) N DIRECTIVE 2011/65/A electrical and electro None of the ingredient REGULATION (EU) 2 Annex I - RESTRICT of licensing under A None of the ingredient Annex II - REPORTA None of the ingredient	QUIDS (tonnes) for the application of lower-tier re (tonnes) for the application of upper-tier re to 1907/2006 ANNEX XVII Conditions of rest EU on the restriction of the use of certain to onic equipment – Annex II (to a sis listed. ED EXPLOSIVES PRECURSORS (Upper line) rticle 5(3)) The sis listed. BLE EXPLOSIVES PRECURSORS	equirements 200 t riction: 3 hazardous substances in
P5c FLAMMABLE LIC Qualifying quantity (Qualifying quantity (REGULATION (EC) N DIRECTIVE 2011/65/I electrical and electro None of the ingredient REGULATION (EU) 2 Annex I - RESTRICT of licensing under A None of the ingredient Annex II - REPORTA None of the ingredient Regulation (EC) No Regulation (EC) No	DUIDS itonnes) for the application of lower-tier re- itonnes) for the application of upper-tier re- lo 1907/2006 ANNEX XVII Conditions of rest. EU on the restriction of the use of certain in price equipment – Annex II is is listed. 2019/1148 ED EXPLOSIVES PRECURSORS (Upper liner rticle 5(3)) is is listed. BLE EXPLOSIVES PRECURSORS is listed. 273/2004 on drug precursors is is listed. 111/2005 laying down rules for the mon	equirements 200 t riction: 3 hazardous substances in mit value for the purpose
P5c FLAMMABLE LIC Qualifying quantity (Qualifying quantity (REGULATION (EC) N DIRECTIVE 2011/65/I electrical and electro None of the ingredient REGULATION (EU) 2 Annex I - RESTRICT of licensing under A None of the ingredient Annex II - REPORTA None of the ingredient Regulation (EC) No Regulation (EC) No	DUIDS tonnes) for the application of lower-tier re- tonnes) for the application of upper-tier re- to 1907/2006 ANNEX XVII Conditions of rest EU on the restriction of the use of certain is pric equipment – Annex II is is listed. 2019/1148 ED EXPLOSIVES PRECURSORS (Upper liner rticle 5(3)) is is listed. BLE EXPLOSIVES PRECURSORS is is listed. 273/2004 on drug precursors is is listed. 111/2005 laying down rules for the moni- third countries in drug precursors	equirements 200 t riction: 3 hazardous substances in mit value for the purpose

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H370 Causes damage to organs.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 11)

— GB

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.03.2024	Version number 6 (replaces version 5)	Revision: 04.03.2024
rade name: 842ER-Part	4	
		(Contd. of page 10)
EUH066 Repeated exp	osure may cause skin dryness or cracking.	
· Department issuing S	DS: Product safety department.	
· Contact: sds@mgcher		
Date of previous vers		
· Version number of pr		
· Abbreviations and ac		
	sport international des marchandises dangereuses pa	ar route (European Agreemen
Concerning the International (Carriage of Dangerous Goods by Road)	
IMDG: International Maritime		
IATA: International Air Transp		
	ystem of Classification and Labelling of Chemicals	
ELINCS: European List of No	of Existing Commercial Chemical Substances	
	vice (division of the American Chemical Society)	
VOC: Volatile Organic Compo		
LC50: Lethal concentration, 5		
LD50: Lethal dose, 50 percen		
PBT: Persistent, Bioaccumula vPvB: very Persistent and ver		
ATE: Acute toxicity estimate v		
Flam. Liq. 2: Flammable liquid		
Flam. Liq. 3: Flammable liquid		
Acute Tox. 4: Acute toxicity –		
Skin Irrit. 2: Skin corrosion/irri		
Eye Irrit. 2: Serious eye dam	nage/eye irritation – Category 1	
Skin Sens. 1: Skin sensitisatio		
Skin Sens. 1B: Skin sensitisa		
	rgan toxicity (single exposure) – Category 1	
	rgan toxicity (single exposure) – Category 3	
	rgan toxicity (repeated exposure) – Category 1	xn, 1
	o the aquatic environment - acute aquatic hazard – Catego s to the aquatic environment - long-term aquatic hazard – C	
	s to the aquatic environment - long-term aquatic hazard – C	
	ne previous version altered.	
		G