



Printing date 04.03.2024 Version number 4 (replaces version 3)

Revision: 04.03.2024

1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: 842ER-Part B
- · Other Means of Identification: Super Shield Silver Epoxy Conductive Paint
- Related Part Number:

842ER-B-Liquid, 842ER-B-60ML, 842ER-B-250ML, 842ER-B-900ML, 842ER-B-4.25L

- **UFI:** MSR0-20U4-3005-NPV9
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Silver conductive epoxy hardener
- · 1.3 Details of the supplier of the safety data sheet M.G. Chemicals Ltd.
- Manufacturer/Supplier:

MG Chemicals Ltd. (Head Office) 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA +(1) 800-340-0772

MG Chemicals
Heame House, 23 Bliston Street
Sedgely Dudley DY3 1JA.
UNITED KINGDOM
+(44) 1663 362888 sales@mgchemicals.com

MG Chemicalst Ltd. Level 2, Vision Exchange, Building Territorials Street, Zone 1, Central Business, District, Birkirkara CBD 1070, MALTA

- · Further information obtainable from: sds@mgchemicals.com
- · 1.4 Emergency telephone number:

Verisk 3E (Access code: 335388), +(44) 20 3514787 Other emergency telephone numbers: +(0) 800 680 0425

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) USA or CANADA-Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service CANADA-Call CANUTEC collect at +1-613-996-6666 or *666 on cellular phones

GB

Printing date 04.03.2024 Version number 4 (replaces version 3) Revision: 04.03.2024

Trade name: 842ER-Part B

(Contd. of page 1)

2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2

H225 Highly flammable liquid and vapour.



GHS05 corrosion

Eye Dam. 1

H318 Causes serious eye damage.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2

H315 Causes skin irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

STOT SE 3

H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms









GHS02 GHS05 GHS07 GHS09

· Signal word Danger

· Hazard-determining components of labelling:

fatty acids, C18-unsatd., dimers, reactionproducts with polyethylenepolyamines butan-1-ol

3,6-diazaoctanethylenediamin

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P102

Keep out of reach of children.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P271

Use only outdoors or in a well-ventilated area.

(Contd. on page 3)

Printing date 04.03.2024 Version number 4 (replaces version 3) Revision: 04.03.2024

Trade name: 842ER-Part B

(Contd. of page 2)

P280 Wear protective gloves, protective clothing, and eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310

Immediately call a POISON CENTER/doctor.

P405

Store locked up.

· Additional information:

EUH208: Contains 3,6-diazaoctanethylenediamin. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.
- Determination of endocrine-disrupting properties

Endocrine Disruptor substance ≥ 0.1% = none

3 Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.
- Dangerous components:

CAS: 110-19-0 isobutyl acetate

48.0%

3.0%

EINECS: 203-745-1 🏇 Flam. Liq. 2, H225, EUH066

CAS: 68410-23-1 fatty acids, C18-unsatd., dimers, reactionproducts with 34.0%

polyethylenepolyamines

Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317

CAS: 71-36-3 butan-1-ol 8.0%

EINECS: 200-751-6 6 Flam. Liq. 3, H226; 6 Eye Dam. 1, H318; 1 Acute Tox. 4,

H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336

CAS: 67-64-1 6.0%

EINECS: 200-662-2 🚸 Flam. Liq. 2, H225; 🕩 Eye Irrit. 2, H319; STOT SE 3, H336,

ĚUH066

CAS: 112-24-3 3,6-diazaoctanethylenediamin

EINECS: 203-950-6 📀 Skin Corr. 1B, H314; 🗘 Acute Tox. 4, H312; Skin Sens. 1,

H317; Aquatic Chronic 3, H412

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · 4.1 Description of first aid measures
- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)

Printing date 04.03.2024 Version number 4 (replaces version 3) Revision: 04.03.2024

Trade name: 842ER-Part B

(Contd. of page 3)

4.3 Indication of any immediate medical attention and special treatment neededNo further relevant information available.

5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Vapors are heavier than air. Vapors may travel to sources of ignition near the ground. They can cause flash fire or ignite explosively.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

GB

Printing date 04.03.2024 Version number 4 (replaces version 3) Revision: 04.03.2024

Trade name: 842ER-Part B

(Contd. of page 4)

8 Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

110-19-0 isobutyl acetate

WEL Short-term value: 903 mg/m³, 187 ppm Long-term value: 724 mg/m³, 150 ppm

71-36-3 butan-1-ol

WEL Short-term value: 154 mg/m³, 50 ppm

Sk

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

• Respiratory protection: Not required.

Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

Printing date 04.03.2024 Version number 4 (replaces version 3) Revision: 04.03.2024

Trade name: 842ER-Part B

(Contd. of page 5)

9 Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

Fluid Colour:

According to product specification · Odour: Characteristic

· Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

- Boiling point or initial boiling point and

boiling range 56 ℃

· Flammability Highly flammable.

Lower and upper explosion limit

2 Vol % · Lower: · Upper: 12 Vol %

-17 °C (67-64-1 acetone) · Flash point:

330 ℃ Auto-ignition temperature:

· Decomposition temperature: Not determined. · pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic: Not determined.

Solubility

Fully miscible. · water:

· Partition coefficient n-octanol/water (log

value) Not determined.

20 hPa (110-19-0 isobutyl acetate) · Vapour pressure at 20 ℃:

· Density and/or relative density

· Density at 20 °C: 0.9 g/cm³ · Relative density Not determined. · Bulk density: 880 kg/m³ · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid Important information on protection of

health and environment, and on safety.

Ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation

of explosive air/vapour mixtures are possible.

Solvent content:

Organic solvents: 62.0 % · VOC (EC) 62.00 % · Solids content: 1.0 %

Change in condition

Not determined. · Evaporation rate

Information with regard to physical hazard

classes · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void

· Flammable liquids Highly flammable liquid and vapour.

(Contd. on page 7)

Printing date 04.03.2024 Version number 4 (replaces version 3) Revision: 04.03.2024

Trade name: 842ER-Part B

		(Contd. of page 6)
· Flammable solids	Void	
Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
Corrosive to metals	Void	
· Desensitised explosives	Void	

10 Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

 Oral
 LD50
 9,875 mg/kg (rat)

 Dermal
 LD50
 26,833 mg/kg (rabbit)

110-19-0 isobutyl acetate

Oral LD50 13,400 mg/kg (rat)

71-36-3 butan-1-ol

Oral LD50 790 mg/kg (rat)
Dermal LD50 3,400 mg/kg (rabbit)
Inhalative LC50/4 h 8,000 mg/l (rat)

67-64-1 acetone

Oral LD50 5,800 mg/kg (rat)
Dermal LD50 20,000 mg/kg (rabbit)

112-24-3 3,6-diazaoctanethylenediamin

Oral LD50 2,500 mg/kg (rat)
Dermal LD50 805 mg/kg (rabbit)

- Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.

(Contd. on page 8)

Printing date 04.03.2024 Version number 4 (replaces version 3) Revision: 04.03.2024

Trade name: 842ER-Part B

(Contd. of page 7)

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

HP3 Flammable

HP4 Irritant - skin irritation and eye damage

HP13 Sensitising

HP14 Ecotoxic

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA

UN1263

(Contd. on page 9)

Printing date 04.03.2024

Version number 4 (replaces version 3)

Revision: 04.03.2024

Trade name: 842ER-Part B

(Contd. of page 8) · 14.2 UN proper shipping name

1263 PAINT, ENVIRONMENTALLY · ADR **HAZARDOUS**

· IMDG PAINT, MARINE POLLUTANT

·IATA Paint

· 14.3 Transport hazard class(es)

· ADR, IMDG





· Class 3 Flammable liquids.

· Label

· IATA



3 Flammable liquids. · Class

· Label

· 14.4 Packing group

· ADR, IMDG, IATA II

· 14.5 Environmental hazards:

· Marine pollutant:

Symbol (fish and tree) Special marking (ADR): Symbol (fish and tree)

14.6 Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler

code):

F-E,S-E · EMS Number:

· Stowage Category В

14.7 Maritime transport in bulk according

to IMO instruments Not applicable.

· Transport/Additional information:

· ADR

5L · Limited quantities (LQ)

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30

3

33

Maximum net quantity per outer packaging: 500

ml

Transport category 2 Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30

Maximum net quantity per outer packaging: 500

ml

(Contd. on page 10)

Printing date 04.03.2024 Version number 4 (replaces version 3) Revision: 04.03.2024

Trade name: 842ER-Part B

(Contd. of page 9)

UN "Model Regulation":

UN 1263 PAINT, 3, II, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

67-64-1 acetone: Listed

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

67-64-1 acetone

· Regulation (EC) No 273/2004 on drug precursors

67-64-1 acetone: 3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

67-64-1 acetone: 3

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

(Contd. on page 11)

Printing date 04.03.2024 Version number 4 (replaces version 3) Revision: 04.03.2024

Trade name: 842ER-Part B

(Contd. of page 10) H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. · Department issuing SDS: Product safety department. Contact: sds@mgchemicals.com · Date of previous version: 21.11.2023 · Version number of previous version: 3 · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative ATE: Acute toxicity estimate values Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.