

9200FR-A

(PART A)

# Safety Data Sheet

## Section 1: Identification

### Product Identifier and Other Means of Identification

**Product Name:** 9200FR-A**Other Means of Identification:** Flame Retardant Structural Epoxy Adhesive (Part A)**Related Part #** 9200FR-25ML, 9200FR-50ML

### Recommended Use and Restriction on Use

**Use:** Epoxy adhesive resin for use with hardeners**Uses Advised Against:** Not for use as a spray coating

### Details of Manufacturer or Importer

**Manufacturer**MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADA**TEL** +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** [support@mgchemicals.com](mailto:support@mgchemicals.com)**WEB** [www.mgchemicals.com](http://www.mgchemicals.com)**TEL** +1-905-331-1396**FAX** +1-905-331-2682**E-MAIL** [info@mgchemicals.com](mailto:info@mgchemicals.com)**E-MAIL** (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)

### Emergency Phone Number




**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents)  
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**  
(Service access code: 335388)**For emergencies involving the transport of dangerous goods;** 24/7 service  
CANADA—Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones

**9200FR-A**
**(PART A)**
**Section 2: Hazard(s) Identification**
**Classification of Hazardous Chemical**
**GHS Categories**

Criteria		Category	Signal Word	Pictograms
Sensitization	Skin	1	Warning	Exclamation
Eye Irritation		2	Warning	Exclamation
Skin Irritation		2	Warning	Exclamation
Acute Toxicity	Oral	4	Warning	Exclamation
Reproductive Toxicity		2	Warning	Health
Hazardous to the Aquatic Environment	Chronic	2	<i>none</i>	Environment

*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

**Label Elements**

Signal Word	<b>WARNING</b>
Pictograms	<b>Hazard Statements</b>
	H317: May cause an allergic skin reaction H315: Causes skin irritation H319: Causes serious eye irritation H302: Harmful if swallowed
	H361: May damage fertility or the unborn child if swallowed
	H411: Toxic to aquatic life with long lasting effects

*Section continued on the next page*

**9200FR-A**
**(PART A)**
*Continued...*

<b>Prevention</b>	<b>Precautionary Statements</b>
P102	Keep out of reach of children.
P201, P202	Obtain special instructions before use. Do not handle all safety precautions have been read and understood.
P261	Avoid breathing fumes and vapors.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves and eye protection.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
<b>Response</b>	<b>Precautionary Statements</b>
P308 + P313	IF exposed or concerned. Get medical advice or attention.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P301 + P312	IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.
P330	Rinse mouth.
P391	Collect spillage.
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

**Hazards Not Otherwise Classified**

<b>Other Criteria</b>	<b>Hazard Statements/Precautionary Statement</b>	<b>Signal Word</b>	<b>Pictograms</b>
None	None	None	None

**9200FR-A**
**(PART A)**
**Section 3: Composition/Information on Ingredients**

CAS #	Chemical Name	%(weight)
28064-14-4	phenol, polymer with formaldehyde, glycidyl ether	33%
21645-51-2	aluminum trihydrate	20%
68333-79-9	ammonium polyphosphate	19%
25085-99-8	bisphenol-A epoxy resin (reaction product) <sup>a)</sup>	19%
138265-88-0	zinc borate	6%
60506-81-2	dipentaerythritol pentaacrylate	2%

a) Average molecular weight of  $\leq 700$

**Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
<b>IF IN EYES</b>	P305 + P351 + P338, P337 + P313
<b>Immediate Symptoms</b>	<i>redness, irritation, pain</i>
<b>Response</b>	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  If eye irritation persists: Get medical advice or attention.
<b>IF ON SKIN</b>	P302 + P352, P333 + P313, P362 + P364, P308 + P313
<b>Immediate Symptoms</b>	<i>redness, irritation, dry skin, allergic contact dermatitis</i>
<b>Response</b>	Wash with plenty of water.  If skin irritation or rash occurs: Get medical advice or attention.  Take off contaminated clothing and wash it before reuse.  IF exposed or concerned. Get medical advice or attention.
<b>IF INHALED</b>	P304 + P340, P308 + P313
<b>Immediate Symptoms</b>	<i>cough, irritation of the respiratory track</i>
<b>Response</b>	Remove person to fresh air and keep comfortable for breathing.  IF exposed or concerned. Get medical advice or attention.

*Section continued on the next page*

**9200FR-A****(PART A)***Continued...*

<b>IF SWALLOWED</b>	P301 + P330 + P331, P308 + P313
<b>Immediate Symptoms</b>	<i>abdominal discomfort, nausea, vomiting</i>
<b>Response</b>	Rinse mouth. Do NOT induce vomiting. IF exposed or concerned. Get medical advice or attention.

**Section 5: Fire-Fighting Measures**

<b>Extinguishing Media</b>	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
<b>Specific Hazards</b>	Not flammable or combustible, but burns if involved in a fire. Produces irritating smoke of unknown toxicity in fires.  Inhalation of zinc oxide and aluminum oxide fumes may cause metal fever and irritate the respiratory tract. The flu-like symptoms of metal fever may be delayed, occurring 4 to 12 hours after exposure.  Prevent fire-fighting wash from entering waterway or sewer system.
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> ), ammonia, aluminum oxides, zinc oxides and other toxic fumes.
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

**9200FR-A****(PART A)****Section 6: Accidental Release Measures**

<b>Personal Protection</b>	See personal protection recommendations in Section 8.
<b>Precautions for Response</b>	Avoid breathing the fumes and vapors. Remove or keep away all sources of extreme heat or open flames.
<b>Environmental Precautions</b>	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
<b>Containment Methods</b>	Contain with inert and non-flammable absorbent such as soil, sand, or vermiculite.
<b>Cleaning Methods</b>	Collect liquid in a sealable, chemical-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Use soap and water to remove the last traces of residue.
<b>Disposal Methods</b>	Dispose of spill waste according to Section 13.

**Section 7: Handling and Storage**

<b>Prevention</b>	Keep out of reach of children.  Obtain special instructions before use. Do not handle all safety precautions have been read and understood.  Avoid breathing fumes and vapors.  Contaminated work clothing should not be allowed out of the workplace.  Avoid release to the environment.
<b>Handling</b>	Wear protective gloves and eye protection.  Take off contaminated clothing and wash it before reuse.  Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.  Collect spillage.
<b>Storage</b>	Store in a well-ventilated area.

**Section 8: Exposure Controls/Personal Protection**
**Substances with Occupational Exposure Limit Values**

<b>Chemical Name</b>	<b>Country</b>	<b>Long Term Exposure Limits (PEL)</b>	<b>Short Term Exposure Limits (STEL)</b>
aluminum metal and insoluble compounds <sup>a)</sup>	ACGIH	1 mg/m <sup>3</sup>	Not established
	U.S.A. OSHA PEL	15 mg/m <sup>3</sup>	Not established
	Canada AB	10 mg/m <sup>3</sup>	Not established
	Canada BC	1 mg/m <sup>3</sup>	Not established
	Canada ON	1 mg/m <sup>3</sup>	Not established
	Canada QC	10 mg/m <sup>3</sup>	Not established

*Note:* The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Respirable airborne particulate matter

**Engineering Controls**
**Ventilation**

Keep airborne concentrations below the occupational exposure limits (OEL).

*Section continued on the next page*

**9200FR-A****(PART A)****Personal Protective Equipment****Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

**RECOMMENDATION:** Ensure that glasses have side shields for lateral protection.

**Skin Protection**

For likely contacts, use of protective butyl rubber or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

**Respiratory Protection**

For over-exposures up to 10 x OEL of mist and vapors, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

**General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.



**9200FR-A**
**(PART A)**
**Section 9: Physical and Chemical Properties**

<b>Physical State</b>	Liquid	<b>Lower Flammability Limit</b>	Not available
<b>Appearance</b>	Off-white	<b>Upper Flammability Limit</b>	Not available
<b>Odor</b>	Mild	<b>Vapor Pressure @20 °C</b>	Not available
<b>Odor Threshold</b>	Not available	<b>Vapor Density</b>	Not available
<b>pH</b>	Not available	<b>Relative Density @25 °C</b>	1.3
<b>Freezing/Melting Point</b>	Not available	<b>Solubility in Water</b>	Slightly Soluble
<b>Initial Boiling Point</b> <sup>a)</sup>	≥150 °C [≥302 °F]	<b>Partition Coefficient n-octanol/water</b>	Not available
<b>Flash Point</b> <sup>b)</sup>	113 °C [>235 °F]	<b>Auto-ignition Temperature</b>	Not available
<b>Evaporation Rate</b>	Not available	<b>Decomposition Temperature</b>	Not available
<b>Flammability</b>	Non Flammable	<b>Viscosity @25 °C</b>	>20.5 mm <sup>2</sup> /s

a) Component with the lowest value—bisphenol-A epoxy resin (reaction product)

b) Component with the lowest value—dipentaerythritol pentaacrylate

**Section 10: Stability and Reactivity**

<b>Reactivity</b>	Reacts exothermically with amines.
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures
<b>Conditions to Avoid</b>	Avoid ignition sources, open flames, and incompatible substances.
<b>Incompatibilities</b>	Strong oxidizing agents, strong acids, strong bases, amines
<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

**9200FR-A**
**(PART A)**
**Section 11: Toxicological Information**
**Summary of Effects and Symptoms by Routes of Exposure**

<b>Eyes</b>	May cause redness, irritation, or pain.
<b>Skin</b>	May cause skin redness, irritation, dry skin, or allergic contact dermatitis.
<b>Inhalation</b>	Low toxicity—May cause cough and irritation of the respiratory track.
<b>Ingestion</b>	May cause abdominal discomfort, nausea, and vomiting.
<b>Chronic</b>	Prolonged and repeated exposure may lead to skin sensitization.

**Acute Toxicity (Lethal Exposure Concentrations)**

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
phenol, polymer with formaldehyde, glycidyl ether	4 000 mg/kg Rabbit <sup>a)</sup>	Not available	6 000 mg/kg Rabbit <sup>a)</sup>
aluminum trihydrate	Not available	Not available	Not available
ammonium polyphosphate	>300 mg/kg Rat	Not available	Not available
reaction products: bisphenol-A-(epichlorhydrin) and epoxy resin	>15 000 mg/kg Rat <sup>a)</sup>	23 000 mg/kg Rat <sup>a)</sup>	Not available
zinc borate	>10 000 mg/kg Rat <sup>a)</sup>	10 000 mg/kg Rat <sup>a)</sup>	Not available
dipentaerythritol pentaacrylate	Not available	Not available	Not available

*Note:* Toxicity data from the ECHA database and supplier safety data sheets were consulted.

a) Supplier SDS

*Section continued on the next page*

**9200FR-A****(PART A)****Other Toxicological Effects**

<b>Skin corrosion/irritation</b>	Based on the epoxy component data, the mixture is a skin irritant.
<b>Serious eye damage/irritation</b>	Based on component data, the mixture causes serious eye irritation.
<b>Sensitization</b> (allergic reactions)	Based on component data, the mixture is a skin sensitizer based on animal studies.
<b>Carcinogenicity</b> (risk of cancer)	Not classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
<b>Mutagenicity</b> (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
<b>Reproductive Toxicity</b> (risk to sex functions)	Animal ingestion studies show that high doses of zinc borate cause reproductive and developmental effects.
<b>Teratogenicity</b> (risk of fetus malformation)	Based on available data, the classification criteria are not met.
<b>STOT-single exposure</b>	Based on available data, the classification criteria are not met.
<b>STOT-repeated exposure</b>	Based on available data, the classification criteria are not met.
<b>Aspiration hazard</b>	Based on available data, the classification criteria are not met. There is no category 1 components, and the kinematic viscosity is $>20.5 \text{ mm}^2/\text{s}$ at $40 \text{ }^\circ\text{C}$ .

**9200FR-A****(PART A)****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

In Europe, similar epoxy resin mixtures with CAS# 28064-14-4 and 25085-99-8 have an average molecular weight of less than 700 and are generally classified as chronic category 2 aquatic pollutant due to LC50 96 h of >1 mg/L but ≤10 mg/L.

Zinc borate is a category 1 chronic aquatic pollutant with a LC50 96 h 2.4 mg/L for *Oncorhynchus mykiss* (rainbow trout); 76 mg/L 48 h *Daphnia magna* (water flea).

Based on available data, aluminum trihydrate, ammonium polyphosphate and dipentaerythritol pentaacrylate are not classified as environmental hazards according to GHS criteria.

**Acute Ecotoxicity**

Available toxicity data does not meet classification thresholds.

**Chronic Ecotoxicity**

Category 2

Toxic to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

**Biodegradability**

Not available

**Bioaccumulation**

Not available

**Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, national, and international regulations.

**9200FR-A**

**(PART A)**

**Section 14: Transport Information**

**Ground**

**Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Sizes under 5 L  
9200FR-25ML, 9200FR-50ML  
**NOT REGULATED** in TDG  
per Special Provisions 99(2)

*FOR REFERENCE ONLY*

**UN number:** UN3082  
**Shipping Name:** ENVIRONMENTALLY  
HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(phenol, polymer with formaldehyde,  
glycidyl ether, bisphenol-A, zinc borate)

Sizes 5 L and under  
**NOT REGULATED** in 49 CFR  
per exception 171.4 (c)(2)

**Class:** 9  
**Packing Group:** III  
**Marine Pollutant:** Yes

**Special Provision 99 (2):** These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

**Air**

**Refer to ICAO-IATA regulations.**

Sizes 5 L and under  
9200FR-25ML, 9200FR-50ML  
**NOT REGULATED**  
Not Restricted, as per Special  
Provisions A197

**Special Provision A197:** These substances when transported in single or combination packagings containing net quantity per single or inner packaging of less than 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

*Section continued on the next page*

**9200FR-A**

**(PART A)**

**Sea**

**Refer to IMDG regulations.**

Sizes 5 L and under  
 9200FR-25ML, 9200FR-50ML  
**NOT REGULATED**  
 per 2.10.2.7

**2.10.2.7:** Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provision of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this Code relevant to any additional hazards continue to apply.

**Section 15: Regulatory Information**

**Canada**

**Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL.

**Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.


**USA**

**Other Classifications**

**HMIS® RATING**

<b>HEALTH:</b>	<b>*</b>	<b>2</b>
<b>FLAMMABILITY:</b>		<b>1</b>
<b>PHYSICAL HAZARD:</b>		<b>2</b>
<b>PERSONAL PROTECTION:</b>		

**NFPA® 704 CODES**



*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

*Section continued on the next page*

**9200FR-A****(PART A)****CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

**EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain substances which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

**TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any listed substances in California.

**Europe****RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

**Section 16: Other Information**

<b>SDS Prepared by</b>	Regulatory Department
<b>Date of Review</b>	14 July 2023
<b>Supersedes</b>	20 March 2020
<b>Reason for Changes:</b>	Minor changes

*Section continued on the next page*

**9200FR-A****(PART A)****Reference**

1) ACGIH 2023 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2023).

**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

Phone: +1-905-331-1396

**Mailing Addresses** *Manufacturing & Support*  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

**Disclaimer**

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.