# 413C



# **Heavy Duty Flux Remover**

413C Heavy Duty Flux Remover is specially formulated to dissolve and remove the most stubborn, encrusted, hard, baked-on fluxes and residues left on parts after soldering. It penetrates quickly to remove non-ionic and ionic contaminants left on the non-component sides of circuit boards. It can also work aggressively on isolated and hard-to-reach areas that require spot cleaning. It is also available in aerosol format.

413C is the best flux cleaner for removing rosin, non-rosin, no-clean fluxes, non-ionic and ionic contamination.

For plastic safe versions, visit 4050A and 4140A flux removers.

Read the product SDS before using this product (downloadable at www.mgchemicals.com).

#### **Features and Benefits**

- RoHS Compliant
- Quickly dissolves burnt-on flux
- · Fast dry time
- Zero residue

## **Available Packaging**

Cat. No.	Packaging	Net Vol.	Net Wt.
413C-1L	Bottle	945 mL	793 g
413C-20L	Pail	18.9 L	15.8 kg

#### **Contact Information**

MG Chemicals, 1210 Corporate Drive Burlington, Ontario, Canada L7L 5R6

Email: support@mgchemicals.com

Phone: North America: +(1)800-340-0772

International: +(1) 905-331-1396 Europe: +(44)1663 362888



### **Properties**

Viscosity @ 25 °C	<20.5 mm <sup>2</sup> /s
Density	0.84 g/mL
Shelf Life	5 y
Flash Point	11 °C
Boiling Point	83 °C
Auto-ignition Temperature	456 °C
Water Miscibility	Miscible

# **Storage and Handling**

Store between 4 and 40 °C in a well-ventilated place and keep cool. Do not freeze.

## **Disclaimer**

This information is believed to be accurate. It is intended for professional end-users who have the skills required to evaluate and use the data properly. M.G. Chemicals Ltd. does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.