



Kit Revision Date: 21 December 2020

## 9200 STRUCTURAL EPOXY ADHESIVE KIT

### MG Chemicals Multipart Product Kit

This product is a kit made up of multiple parts. Each part is an independently packaged chemical component and has independent hazard assessments.

#### **Kit Content**

<i>Part</i>	<i>Product Name</i>	<i>Product Use</i>
A	9200-A	Epoxy adhesive resin for use with hardeners
B	9200-B	Epoxy adhesive hardener for use with resins

*Safety Data Sheets for each part listed above follow this cover sheet.*

#### **Transportation Instruction**

Before offering this product kit for transport, read Section 14 for all parts listed above.

9200-A

STRUCTURAL EPOXY ADHESIVE

# Safety Data Sheet

## Section 1: Identification

### Product Identifier and Other Means of Identification

**Product Name:** 9200-A**Other Means of Identification:** Structural Epoxy Adhesive**Related Part #** 9200-25ML, 9200-50ML, 9200-1.7L

### Recommended Use and Restriction on Use

**Use:** Epoxy adhesive resin for use with hardeners**Uses Advised Against:** Not for use as a spray coating

### Details of Manufacturer or Importer

**Manufacturer**MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADAMG Chemicals (Head Office)  
9347-193 Street  
Surrey, British Columbia V4N 4E7  
CANADA**☎** +1-800-340-0772  
**FAX** +1-800-340-0773  
**E-MAIL** [support@mgchemicals.com](mailto:support@mgchemicals.com)  
**WEB** [www.mgchemicals.com](http://www.mgchemicals.com)**☎** +1-905-331-1396  
**FAX** +1-905-331-2682  
**E-MAIL** [info@mgchemicals.com](mailto:info@mgchemicals.com)**E-MAIL** (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)

### Emergency Phone Number



**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents)  
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**  
(Service access code: 335388)**For emergencies involving the transport of dangerous goods;** 24/7 service  
CANADA—Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones

**9200-A**
**STRUCTURAL EPOXY ADHESIVE**
**Section 2: Hazard(s) Identification**
**Classification of Hazardous Chemical**
**GHS Categories**

Criteria		Category	Signal Word	Pictograms
Sensitization	Skin sensitizer	1	Warning	Exclamation
Eye Irritation		2	Warning	Exclamation
Skin Irritation		2	Warning	Exclamation
Hazardous to the aquatic environment	Chronic	2	<i>none</i>	Environment

*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

**Label Elements**

<b>Signal Word</b>	<b>WARNING</b>
<b>Pictograms</b>	<b>Hazard Statements</b>
	H319: Causes serious eye irritation H315: Causes skin irritation H317: May cause an allergic skin reaction
	H411: Toxic to aquatic life with long lasting effects
<b>Prevention</b>	<b>Precautionary Statements</b>
P102	Keep out of reach of children.
P261	Avoid breathing fumes, mist, or vapors.
P280	Wear protective gloves and eye protection or face protection.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.

*Section continued on the next page*

**9200-A**
**STRUCTURAL EPOXY ADHESIVE**
*Continued...*

<b>Response</b>	<b>Precautionary Statements</b>
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
<b>Storage</b>	<b>Precautionary Statements</b>
none	none
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

**Hazards Not Otherwise Classified**

<b>Other Criteria</b>	<b>Hazard Statements/Precautionary Statement</b>	<b>Signal Word</b>	<b>Pictograms</b>
None	None	None	None

**Section 3: Composition/Information on Ingredients**

<b>CAS #</b>	<b>Chemical Name</b>	<b>%(weight)</b>
28064-14-4	phenol, polymer with formaldehyde, glycidyl ether	46%
25068-38-6	bisphenol-A epoxy resin (reaction product) <sup>a)</sup>	32%
14807-96-6	talca (non-asbestos fiber)	17%
60506-81-2	dipentaerythritol pentaacrylate	2%

 a) Average molecular weight of  $\leq 700$

**9200-A**
**STRUCTURAL EPOXY ADHESIVE**
**Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
<b>IF IN EYES</b>	P305 + P351 + P338, P337 + P313
<b>Immediate Symptoms</b>	<i>redness, irritation, pain</i>
<b>Response</b>	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  If eye irritation persists: Get medical advice or attention.
<b>IF ON SKIN</b>	P302 + P352, P333 + P313, P362 + P364
<b>Immediate or Delayed Symptoms</b>	<i>redness, irritation, dry skin, allergic contact dermatitis</i>
<b>Response</b>	Wash with plenty of water.  If skin irritation or rash occurs: Get medical advice or attention.  Take off contaminated clothing and wash it before reuse.
<b>IF INHALED</b>	P304 + P340
<b>Immediate Symptoms</b>	<i>cough, irritation of the respiratory track</i>
<b>Response</b>	Remove person to fresh air and keep comfortable for breathing.
<b>IF SWALLOWED</b>	P301 + P330, P331
<b>Immediate Symptoms</b>	<i>abdominal discomfort, nausea, vomiting</i>
<b>Response</b>	Rinse mouth. Do NOT induce vomiting.

**Section 5: Fire-Fighting Measures**

<b>Extinguishing Media</b>	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
<b>Specific Hazards</b>	Not flammable or combustible, but burns if involved in a fire. Produces irritating smoke of unknown toxicity in fires.  Prevent fire-fighting wash from entering waterway or sewer system.
<b>Combustion Products</b>	Produces carbon oxides (CO,CO <sub>2</sub> ) and toxic fumes.
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

*Section continued on the next page*

**9200-A****STRUCTURAL EPOXY ADHESIVE****Section 6: Accidental Release Measures**

<b>Personal Protection</b>	See personal protection recommendations in Section 8.
<b>Precautions for Response</b>	Avoid breathing the fumes, mist, or vapors. Remove or keep away all sources of extreme heat or open flames.
<b>Environmental Precautions</b>	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
<b>Containment Methods</b>	Contain with inert and non-flammable absorbent such as soil, sand, or vermiculite.
<b>Cleaning Methods</b>	Collect liquid in a sealable, chemical-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash residue with a paper towel wetted with alcohol, ethyl lactate, or another suitable organic solvent; and place dirty towels in container. Use soap and water to remove the last traces of residue.
<b>Disposal Methods</b>	Dispose of spill waste according to Section 13.

**Section 7: Handling and Storage**

<b>Prevention</b>	Keep out of reach of children. Avoid breathing fumes, mist, or vapors or contact with skin or eyes. Avoid release to the environment.
<b>Handling</b>	Wear protective gloves, protective clothing, and eye protection. Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands thoroughly after handling. Collect spillage.
<b>Storage</b>	Store in a well-ventilated area.

9200-A

STRUCTURAL EPOXY ADHESIVE

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
talc (without asbestos fibers)	ACGIH	2 mg/m <sup>3</sup>	Not established
	U.S.A. OSHA PEL	20 mppcf <sup>a)</sup>	Not established
	Canada AB	2 mg/m <sup>3</sup>	Not established
	Canada BC	2 mg/m <sup>3</sup>	Not established
	Canada ON	2 mg/m <sup>3</sup>	Not established
	Canada QC	3 mg/m <sup>3</sup>	Not established

Note: The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from by RTECS<sup>2</sup> database and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Millions of particles per cubic foot air, based on impinge samples counted by light-field technique.

Engineering Controls

**Ventilation** Keep airborne concentrations below the occupational exposure limits (OEL).

Personal Protective Equipment

**Eye protection** Wear appropriate protective eyeglasses or chemical safety goggles.

**Recommendation:** Ensure that glasses have side shields for lateral protection.

**Skin Protection** For likely contacts, use of protective butyl rubber or other chemically resistant gloves.  
For incidental contacts, use nitrile or other chemically resistant gloves.

Section continued on the next page

**9200-A**
**STRUCTURAL EPOXY ADHESIVE**

**Respiratory Protection** For over-exposures up to 10 x OEL of mist, vapors, or spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

**General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.

**Section 9: Physical and Chemical Properties**

<b>Physical State</b>	Liquid	<b>Lower Flammability Limit</b>	Not available
<b>Appearance</b>	Light grey	<b>Upper Flammability Limit</b>	Not available
<b>Odor</b>	Mild	<b>Vapor Pressure @20 °C</b>	Not available
<b>Odor Threshold</b>	Not available	<b>Vapor Density</b>	Not available
<b>pH</b>	Not available	<b>Relative Density @25 °C</b>	1.3
<b>Freezing/Melting Point</b>	Not available	<b>Solubility in Water</b>	Negligible
<b>Initial Boiling Point</b> <sup>a)</sup>	≥150 °C [≥302 °F]	<b>Partition Coefficient n-octanol/water</b>	Not available
<b>Flash Point</b> <sup>b)</sup>	>113 °C [>235 °F]	<b>Auto-ignition Temperature</b>	Not available
<b>Evaporation Rate</b>	Not available	<b>Decomposition Temperature</b>	Not available
<b>Flammability</b>	Not applicable	<b>Viscosity @25 °C</b>	>20.5 mm <sup>2</sup> /s

a) Component with the lowest value—bisphenol-A epoxy resin (reaction product)

b) Component with the lowest value—dipentaerythritol pentaacrylate



**9200-A****STRUCTURAL EPOXY ADHESIVE****Section 10: Stability and Reactivity**

<b>Reactivity</b>	Reacts exothermically with amines.
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures
<b>Conditions to Avoid</b>	Avoid ignition sources, open flames, and incompatible substances.
<b>Incompatibilities</b>	Strong oxidizing agents, strong acids, strong bases, amines
<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

**Section 11: Toxicological Information****Summary of Effects and Symptoms by Routes of Exposure**

<b>Eyes</b>	May cause redness, irritation, or pain.
<b>Skin</b>	May cause skin redness, irritation, dry skin, or allergic contact dermatitis.
<b>Inhalation</b>	May cause cough and irritation of the respiratory track.
<b>Ingestion</b>	May cause abdominal discomfort, nausea, and vomiting.
<b>Chronic</b>	Prolonged and repeated exposure may lead to skin sensitization.

**9200-A**
**STRUCTURAL EPOXY ADHESIVE**
**Acute Toxicity (Lethal Exposure Concentrations)**

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
phenol, polymer with formaldehyde, glycidyl ether	4 000 mg/kg Rabbit <sup>a)</sup>	Not available	6 000 mg/kg Rabbit <sup>a)</sup>
reaction products: bisphenol-A-(epichlorohydrin) and epoxy resin <sup>b)</sup>	11 400 mg/kg Rat	Not available	Not available
talc (non-asbestos fiber)	Not available	Not available	Not available
dipentaerythritol pentaacrylate	Not available	Not available	Not available

*Note:* Toxicity data from the RTECS<sup>2</sup> and ECHA were consulted. The data from supplier SDSs were also consulted.

a) Supplier SDS

b) Referred to as bisphenol-A epoxy resin (reaction product)

**Other Toxicological Effects**

<b>Skin corrosion/irritation</b>	Based on component data, the mixture is a skin irritant.
<b>Serious eye damage/irritation</b>	Based on component data, the mixture causes serious eye irritation.
<b>Sensitization</b> (allergic reactions)	Based on component data, the mixture is a skin sensitizer based on animal studies.
<b>Carcinogenicity</b> (risk of cancer)	Not classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
<b>Mutagenicity</b> (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
<b>Reproductive Toxicity</b> (risk to sex functions)	Based on available data, the classification criteria are not met.
<b>Teratogenicity</b> (risk of fetus malformation)	Based on available data, the classification criteria are not met.
<b>STOT-single exposure</b>	Based on available data, the classification criteria are not met.

*Section continued on the next page*

**9200-A****STRUCTURAL EPOXY ADHESIVE****STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met. There is no category 1 components, and the kinematic viscosity is  $>20.5 \text{ mm}^2/\text{s}$  at  $40 \text{ }^\circ\text{C}$ .

**Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

In Europe, similar epoxy resin mixtures with CAS# 25068-38-6 and 28064-14-4 have an average molecular weight of less than 700 are generally classified as chronic category 2 marine pollutant due to LC50 96 h of  $>1 \text{ mg/L}$  but  $\leq 10 \text{ mg/L}$ .

Based on available data, talc and dipentaerythritol pentaacrylate are not classified as environmental hazards according to GHS criteria.

**Acute Ecotoxicity**

Category 2

Toxic to aquatic life

**Chronic Ecotoxicity**

Category 2

Toxic to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

**Biodegradability**

Not available

**Bioaccumulation**

Not available

**Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, national, and international regulations.

**9200-A**

**STRUCTURAL EPOXY ADHESIVE**

**Section 14: Transport Information**

**Ground**

**Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Sizes under 450 L

*Part A of 9200-25ML, 9200-50ML kits*

**NOT REGULATED** in TDG  
per Special Provisions 99

*FOR REFERENCE ONLY*

**UN number:** UN3082

**Shipping Name:** ENVIRONMENTALLY  
HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S. (silver particles <1 mm)

Sizes 5 L and under

**NOT REGULATED** in 49 CFR  
per exception 171.4 (c)(2)

**Class:** 9

**Packing Group:** III

**Marine Pollutant:** Yes

**Special Provision 99 (2):** These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

**Air**

**Refer to ICAO-IATA regulations.**

Sizes 5 L and under

*Part A of 9200-25ML, 9200-50ML kits*

**NOT REGULATED**

Not Restricted, as per Special  
Provisions A197

**Special Provision A197:** These substances when transported in single or combination packagings containing net quantity per single or inner packaging of less than 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

*Section continued on the next page*

**9200-A**

**STRUCTURAL EPOXY ADHESIVE**

**Sea**

**Refer to IMDG regulations.**

Sizes 5 L and under  
 Part A of 9200-25ML, 9200-50ML kits  
**NOT REGULATED**  
 per 2.10.2.7

**2.10.2.7:** Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provision of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this Code relevant to any additional hazards continue to apply.

**Section 15: Regulatory Information**

**Canada**

**Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL.

**Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.


**USA**

**Other Classifications**

**HMIS® RATING**

<b>HEALTH:</b>	<b>* 2</b>
<b>FLAMMABILITY:</b>	<b>1</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	

**NFPA® 704 CODES**



*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

*Section continued on the next page*

**9200-A****STRUCTURAL EPOXY ADHESIVE****CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

**EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain substances which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

**TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any listed substances in California.

**Europe****RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

**Section 16: Other Information**

<b>SDS Prepared by</b>	Regulatory Department
<b>Date of Review</b>	04 March 2020
<b>Supersedes</b>	16 November 2018
<b>Reason for Changes:</b>	Change to emergency phone numbers.

**Reference**

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

*Section continued on the next page*

**9200-A****STRUCTURAL EPOXY ADHESIVE****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

**Mailing Addresses** *Manufacturing & Support*  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

*Head Office*  
9347-193rd Street  
Surrey, British Columbia, Canada  
V4N 4E7

**Disclaimer**

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.

9200-B

STRUCTURAL EPOXY ADHESIVE

# Safety Data Sheet

## Section 1: Identification

### Product Identifier and Other Means of Identification

**Product Name:** 9200-B**Other Means of Identification:** Structural Epoxy Adhesive**Related Part #** 9200-25ML, 9200-50ML, 9200-1.7L

### Recommended Use and Restriction on Use

**Use:** Epoxy adhesive hardener for use with resins**Uses Advised Against:** Not for use as a spray coating

### Details of Manufacturer or Importer

**Manufacturer**MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADAMG Chemicals (Head Office)  
9347-193 Street  
Surrey, British Columbia V4N 4E7  
CANADA**TEL** +1-800-340-0772**TEL** +1-905-331-1396**FAX** +1-800-340-0773**FAX** +1-905-331-2682**E-MAIL** [support@mgchemicals.com](mailto:support@mgchemicals.com)**E-MAIL** [info@mgchemicals.com](mailto:info@mgchemicals.com)**WEB** [www.mgchemicals.com](http://www.mgchemicals.com)**E-MAIL** (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)

### Emergency Phone Number

**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents)USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**

(Service access code: 335388)

**For emergencies involving the transport of dangerous goods;** 24/7 serviceCANADA—Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones






**9200-B**
**STRUCTURAL EPOXY ADHESIVE**
**Section 2: Hazard(s) Identification**
**Classification of Hazardous Chemical**
**GHS Categories**

Criteria		Category	Signal Word	Pictograms
Serious Eye Damage		1	Danger	Corrosion
Skin Corrosion		1	Danger	Corrosion
Reproductive Toxicity		2	Warning	Health
Sensitization	Skin	1	Warning	Exclamation
Hazardous to the aquatic environment	Chronic	2	<i>none</i>	Environment


*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

**Label Elements**

Signal Word	<b>DANGER</b>	
Pictograms	<b>Hazard Statements</b>	
	H314: Causes severe skin burns and eye damage	
	H361: May damage fertility or the unborn child if swallowed	
	H317: May cause an allergic skin reaction	

*Section continued on the next page*

**9200-B**
**STRUCTURAL EPOXY ADHESIVE**
*Continued...*

<b>Pictograms</b>	<b>Hazard Statements</b>
	H411: Toxic to aquatic life with long lasting effects
<b>Prevention</b>	<b>Precautionary Statements</b>
P102 P201, P202 P260 P280 P264 P272 P273	Keep out of reach of children. Obtain special instructions before use. Do not handle all safety precautions have been read and understood. Do not breathe fumes, mist, or vapors. Wear protective gloves, protective clothing, and eye protection or face protection. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.
<b>Response</b>	<b>Precautionary Statements</b>
P310 P305 + P351 + P338 P301 + P330 + P352 P333 + P313 P363 P301 + P330 + P331 P304 + P340 P308 + P313 P391	For all routes of exposure: Immediately call a POISON CENTER or doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash with plenty of water [or shower]. If skin irritation or rash occurs: Get medical advice or attention. Wash contaminated clothing before reuse. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice or attention. Collect spillage.

*Section continued on the next page*

**9200-B**
**STRUCTURAL EPOXY ADHESIVE**
*Continued...*

<b>Storage</b>	<b>Precautionary Statements</b>
P405	Store locked up.
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

**Hazards Not Otherwise Classified**

<b>Other Criteria</b>	<b>Hazard Statements/Precautionary Statement</b>	<b>Signal Word</b>	<b>Pictograms</b>
None	None	None	None

**Section 3: Composition/Information on Ingredients**

<b>CAS #</b>	<b>Chemical Name</b>	<b>%(weight)</b>
68683-29-4	ATBN polymer	32%
7727-43-7	barium sulfate	30%
68410-23-1	fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	24%
68082-29-1	fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	7%
112-24-3	triethylenetetramine	3%
140-31-8	2-piperazin-1-ylethylamine (AEP)	2%

**Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
<b>IF IN EYES</b>	P305 + P351 + P338, P310
<b>Immediate Symptoms</b>	<i>redness, severe irritation, pain, burns</i>
<b>Response</b>	Rinse cautiously with water for 30 minutes or more. Remove contact lenses, if present and easy to do. Continue rinsing.  Immediately call a POISON CENTER or doctor.
<b>IF ON SKIN (or hair)</b>	P301 + P330 + P352, P310, P333 + P313, P363
<b>Immediate or Delayed Symptoms</b>	<i>redness, irritation, rash (allergic contact dermatitis), pain, burns, blistering</i>
<b>Response</b>	Take off immediately all contaminated clothing. Wash with plenty of water [shower]. Immediately call a POISON CENTER or doctor.  If skin irritation or rash occurs: Get medical advice or attention.  Wash contaminated clothing before reuse.
<b>IF SWALLOWED</b>	P301 + P330 + P331, P310
<b>Immediate Symptoms</b>	<i>irritation, abdominal pain, nausea, vomiting, burns to the digestive tract</i>
<b>Response</b>	Rinse mouth. Do not induce vomiting.  Immediately call a POISON CENTER or doctor.
<b>IF INHALED</b>	P304 + P340, P310
<b>Immediate Symptoms</b>	<i>cough, irritation of the respiratory track, burning sensation</i>
<b>Delayed Symptoms</b>	<i>asthma, difficulty breathing</i>
<b>Response</b>	Remove person to fresh air and keep comfortable for breathing.  Immediately call a POISON CENTER or doctor.

**Advice to Physicians**

In case of exposure to nitrogen oxides (NO<sub>x</sub>) combustion products or triethylenetetramine vapors during a fire, the symptoms may be delayed. For significant exposures, the exposed person should be kept under medical surveillance for 48 hours.

**9200-B****STRUCTURAL EPOXY ADHESIVE****Section 5: Fire-Fighting Measures**

<b>Extinguishing Media</b>	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
<b>Specific Hazards</b>	Not flammable or combustible, but burns if involved in a fire. Produces irritating and toxic fumes in fires or in contact with hot surfaces.  Inhalation of toxic smoke during fire may have delayed effects. Exposed person may need to be put under surveillance for 48 h.  Toxic for aquatic environment: Prevent fire-fighting wash from entering waterway or sewer system.
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> ) and nitrogen oxides (NO <sub>x</sub> ).
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

**Section 6: Accidental Release Measures**

<b>Personal Protection</b>	Use personal protection recommended in Section 8.
<b>Precautions for Response</b>	Do not breathe fumes, mist, or vapors.
<b>Environmental Precautions</b>	Avoid releasing to the environment. Prevent spill from entering drains and waterways. Do not flush to sewer.
<b>Containment Methods</b>	Contain with inert and non-flammable absorbent (such as soil, sand, vermiculite).
<b>Cleaning Methods</b>	Collect liquid in a sealable container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wipe residue with a paper towel wetted with a suitable organic solvent such as alcohol or ethyl lactate, and place dirty towels in container. Wash spill area with soap and water to remove the last traces of residue.
<b>Disposal Methods</b>	Dispose spill waste according to Section 13.

**9200-B**
**STRUCTURAL EPOXY ADHESIVE**
**Section 7: Handling and Storage**

<b>Prevention</b>	Keep out of reach of children. Do not breathe fumes, mist, or vapors. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.
<b>Handling</b>	Wear protective gloves, protective clothing, and eye protection or face protection. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Collect spillage.
<b>Storage</b>	Store locked up.

**Section 8: Exposure Controls/Personal Protection**
**Substances with Occupational Exposure Limit Values**

<b>Chemical Name</b>	<b>Country or Vendor</b>	<b>Long Term Exposure Limits (PEL)</b>	<b>Short Term Exposure Limits (STEL)</b>
Barium sulfate	ACGIH	10 mg/m <sup>3</sup>	Not established
	U.S.A. OSHA PEL	15 mg/m <sup>3</sup> (Dust)	Not established
	Canada AB	10 mg/m <sup>3</sup>	Not established
	Canada BC	10 mg/m <sup>3</sup> (Dust)	Not established
	Canada ON	10 mg/m <sup>3</sup>	Not established
	Canada QC	10 mg/m <sup>3</sup>	Not established
triethylenetetramine	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	Not established	Not established
	U.S.A (WEEL)	1 ppm	Not established
	Canada AB	Not established	Not established
	Canada BC	Not established	Not established
	Canada ON	0.5 mg/m <sup>3</sup> (Skin) <sup>a)</sup>	Not established
Canada QC	Not established	Not established	

*Note:* Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from by RTECS<sup>2</sup> database and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Skin—can be absorbed through the skin.

*Section continued on the next page*

**9200-B****STRUCTURAL EPOXY ADHESIVE****Engineering Controls**

**Ventilation** Keep airborne concentrations below the occupational exposure limits (OEL).

**Personal Protective Equipment**

**Eye protection** Wear appropriate protective eyeglasses or chemical safety goggles.

**RECOMMENDATION:** Use safety glasses with lateral protection (side shields).

**Skin Protection** For likely contacts, use of protective butyl rubber, neoprene, or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

**Respiratory Protection** For over-exposures up to 10 x OEL of mist, vapors, or spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

**General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.

**9200-B**
**STRUCTURAL EPOXY ADHESIVE**
**Section 9: Physical and Chemical Properties**

<b>Physical State</b>	Liquid	<b>Lower Flammability Limit</b>	Not available
<b>Appearance</b>	Amber	<b>Upper Flammability Limit</b>	Not available
<b>Odor</b>	Ammonia-like	<b>Vapor Pressure @20 °C<sup>a)</sup></b>	<0.001 kPa [<0.01 mmHg]
<b>Odor Threshold</b>	Not available	<b>Vapor Density</b>	Not available
<b>pH</b>	Not available	<b>Relative Density @25 °C</b>	1.18
<b>Freezing/Melting Point</b>	Not available	<b>Solubility in Water</b>	Slightly soluble
<b>Initial Boiling Point</b>	Not available	<b>Partition Coefficient</b>	Not available
<b>Flash Point<sup>a)</sup></b>	>122 °C [>252 °F]	<b>Auto-ignition Temperature</b>	Not available
<b>Evaporation Rate</b>	Not available	<b>Decomposition Temperature</b>	Not available
<b>Flammability</b>	Not applicable	<b>Viscosity @25 °C</b>	>20.5 mm <sup>2</sup> /s

a) Literature value for triethylenetetramine

**Section 10: Stability and Reactivity**

<b>Reactivity</b>	Reacts exothermically with ketones, halogenated hydrocarbons, cyanides, nitriles, and epoxides. May attack metals such as aluminum, zinc, copper, and their alloys.
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures
<b>Conditions to Avoid</b>	Ignition sources, open flames, and incompatible substances
<b>Incompatibilities</b>	Strong oxidizing agents, strong acids
<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.



**Section 11: Toxicological Information**
**Summary of Effects and Symptoms by Routes of Exposure**

<b>Eyes</b>	May cause redness, severe irritation, pain, or burns.
<b>Skin</b>	May cause redness, serious skin irritation, allergic contact dermatitis, and chemical burns. Triethylenetetramine can be absorbed through skin leading to toxic effects.  When heated, hot triethylenetetramine vapors may also result in itching of the face with skin redness (erythema) and swelling (edema).
<b>Inhalation</b>	May cause cough, irritation of the respiratory track, or burning sensation.
<b>Ingestion</b>	May cause irritation, abdominal pain, nausea, vomiting, burns to the digestive tract (see inhalation symptoms).
<b>Chronic</b>	Prolonged and repeated exposure to uncured epoxy hardener may lead to skin sensitization.

**Acute Toxicity (Lethal Exposure Concentrations)**

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	>5 000 mg/kg <sup>a)</sup>	>5 000 mg/kg <sup>a)</sup>	Not available
fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	>5 000 mg/kg <sup>a)</sup>	>5 000 mg/kg <sup>a)</sup>	Not available
triethylenetetramine	2 500 mg/kg Rat	805 mg/kg Rabbit	Not available
2-piperazin-1-ylethylamine (AEP)	2 106 mg/kg Rat	866 mg/kg Rabbit	Not available

*Note:* Toxicity data from the RTECS<sup>2</sup> and ECHA were consulted. The data from supplier SDSs were also consulted.

a) Supplier SDS

*Section continued on the next page*

**9200-B****STRUCTURAL EPOXY ADHESIVE****Other Toxicological Effects**

<b>Skin corrosion/irritation</b>	Triethylenetetramine and 2-piperazin-1-ylethylamine causes skin burns.
<b>Serious eye damage/irritation</b>	Triethylenetetramine and 2-piperazin-1-ylethylamine causes severe eye damage.
<b>Respiratory and skin sensitization</b> (allergic reactions)	The epoxy hardener components may cause skin sensitization according to animal studies.
<b>Carcinogenicity</b> (risk of cancer)	None of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
<b>Mutagenicity</b> (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
<b>Reproductive Toxicity</b> (risk to sex functions)	Based on animal studies 2-piperazin-1-ylethylamine has been shown to be a developmental toxicant if swallowed.
<b>Teratogenicity</b> (risk of fetus malformation)	Based on available data, the classification criteria are not met.
<b>STOT-single exposure</b>	Based on available data, the classification criteria are not met.
<b>STOT-repeated exposure</b>	Based on available data, the classification criteria are not met.
<b>Aspiration hazard</b>	Based on available data, the classification criteria are not met. There are no category 1 components, and the kinematic viscosity is >20.5 mm <sup>2</sup> /s at 40 °C.

**Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

The fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines (CAS# 68410-23-1) and fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine (CAS# 68082-29-1) were classified as a chronic category 2 environmental toxicant (not readily biodegradable, LC50 range of 1–10 mg/L for fish; EC0 bacterial >10 and ≤100 mg/L).

Literature values for the triethylenetetramine (CAS # 112-24-3) suggest an acute category 3 aquatic toxicity (LC50, IC50, and EC50 values of >100 mg/L for fish and between 10 and 100 mg/L for algae).

*Section continued on the next page*

**9200-B****STRUCTURAL EPOXY ADHESIVE****Acute Ecotoxicity**

Category 2

Toxic to aquatic life

**Chronic Ecotoxicity**

Category 2

Toxic to aquatic life with long lasting effect

Avoid release to the environment. Collect spillage.

**Biodegradability**

Not readily biodegradable

**Bioaccumulation**

Not available

**Other Effects**

Not available

**Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, national, and international regulations.

**9200-B**

**STRUCTURAL EPOXY ADHESIVE**


**Section 14: Transport Information**

**Ground**

**Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations);  
**USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Sizes 1 L and under  
*Part B of 9200-25ML, 9200-50ML,  
9200-1.7L kits*

**Limited Quantity**



Sizes greater than 1 L

**UN number:** UN2735  
**Shipping Name:** AMINES, LIQUID,  
CORROSIVE, N.O.S. \*  
(containing triethylenetetramine,  
dimer fatty acid (C18)poly amido  
amine resin)  
**Class:** 8  
**Packing Group:** II  
**Marine Pollutant:** Yes



**Air**

**Refer to ICAO-IATA Dangerous Goods Regulations.**

Sizes 0.1 L and under  
*Part B of 9200-25ML, 9200-50ML  
kits*

**Limited Quantity**



Sizes greater than 0.1 L up to 1 L  
*Part B of 9200-1.7L kit*

**UN number:** UN2735  
**Shipping Name:** AMINES, LIQUID,  
CORROSIVE, N.O.S. \*  
(containing triethylenetetramine,  
dimer fatty acid (C18)poly amido  
amine resin)  
**Class:** 8  
**Packing Group:** II  
**Marine Pollutant:** Yes






*Section continued on the next page*

**9200-B**

**STRUCTURAL EPOXY ADHESIVE**

**Sea**

<b>Refer to IMDG regulations.</b>	
<p>Sizes 1 L and under Part B of 9200-25ML, 9200-50ML, 9200-1.7L kits <b>Limited Quantity</b></p> 	<p>Sizes greater than 1 L</p> <p><b>UN number:</b> UN2735 <b>Shipping Name:</b> AMINES, LIQUID, CORROSIVE, N.O.S. * (containing triethylenetetramine, dimer fatty acid (C18)poly amido amine resin) <b>Class:</b> 8 <b>Packing Group:</b> II <b>Marine Pollutant:</b> Yes</p>  

**Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.**

**Section 15: Regulatory Information**

**Canada**

**Domestic Substance List (DSL)/Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL/NDSL.


**Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

*Section continued on the next page*

**9200-B****STRUCTURAL EPOXY ADHESIVE****USA****Other Classifications****HMIS<sup>®</sup> RATING**

<b>HEALTH:</b>	<b>* 3</b>
<b>FLAMMABILITY:</b>	<b>1</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	

**NFPA<sup>®</sup> 704 CODES**

*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

**CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

**EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain substances that are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

**TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any listed substances in California.

**Europe****RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

**Section 16: Other Information**

<b>SDS Prepared by</b>	Regulatory Department
<b>Date of Revision</b>	18 December 2020
<b>Supersedes</b>	04 March 2020
<b>Reason for Changes:</b>	Update classification based on new data.

**Reference**

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

*Section continued on the next page*

**9200-B****STRUCTURAL EPOXY ADHESIVE**

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

**Mailing Addresses** *Manufacturing & Support*  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

*Head Office*  
9347-193rd Street  
Surrey, British Columbia, Canada  
V4N 4E7

**Disclaimer**

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.