

8618

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: 8618

Other Means of Identification: Ultra Thermal Paste, 6 W/m·K

Related Part # 8618-10ML, 8618-85ML, 8618-300ML

Recommended Use and Restriction on Use

Use: Grease For Electronics

Uses Advised Against: Not available

Details of Manufacturer or Importer

Manufacturer

MG Chemicals 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA

= +1-800-340-0772 = +1-905-331-1396 **FAX** +1-800-340-0773 **FAX** +1-905-331-2682

E-MAIL <u>support@mgchemicals.com</u> **WEB** <u>www.mgchemicals.com</u>

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) USA or CANADA—Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

8618

Section 2: Hazard(s) Identification

Classification of Hazardous Chemical

GHS Categories

Based on available data, this product does not meet the HCS 2012 or WHMIS 2015 classification criteria.

Label Elements

Signal Word	No signal word
Pictograms	Hazard Statements
None mandated	None

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
7429-90-5	aluminum powder	60-80% *

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

8618

Section 4: First-Aid Measures

Exposure Condition	GHS Code/Symptoms/Precautionary Statements
IF IN EYES	P305 + P351 + P338
Immediate Symptoms	Low toxicity: redness, mild irritation
Response	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF ON SKIN	P302 + P352
Immediate Symptoms	Low toxicity: mild irritation
Response	Wash with plenty of water.
IF INHALED	P304 + P340
Immediate Symptoms	Low toxicity
Response	Remove person to fresh air and keep comfortable for breathing.
IF SWALLOWED	P301 + P330, P331
Immediate Symptoms	Low toxicity
Response	Rinse mouth. Do NOT induce vomiting.

Section 5: Fire-Fighting Measures

Extinguishing Media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Specific Hazards	Not flammable or combustible, but burns if involved in a fire.
Combustion Products	Produces aluminim oxides (Al_2O_3) and carbon oxides (CO , CO_2).
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.



SAI Global File #004008 Burlington, Ontario, Canada

8618

Section 6: Accidental Release Measures

Personal Protection See personal protection recommendations in Section 8.

Precautions for This product makes surfaces slippery and must be cleaned

Response thoroughly.

Environmental Precautions

Not applicable

Containment Methods Not applicable—not readily flowable

Cleaning Methods Collect waste in a waste container. Use soap and water to

remove the last traces of residue.

Disposal Methods Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention Keep out of reach of children.

Avoid eye or skin contact.

Handling Wear protective gloves and eye protection.

Wash hands thoroughly after handling.

Storage Not available

8618

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country or Vendor	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
aluminum metal and	ACGIH	1 mg/m ³	Not established
insoluble compounds	U.S.A. OSHA PEL	10 mg/m ³	10 mg/m ³
	Canada AB	10 mg/m ³	Not established
	Canada BC	Not established	Not established
	Canada ON	1 mg/m ³	Not established
	Canada QC	5 mg/m ³	Not established

Note: The ACGIH1, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from supplier SDSs were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

Engineering Controls

Ventilation Normal ventilation is generally adequate, except in enclosed or

low lying area.

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety

goggles.

RECOMMENDATION: Ensure that glasses have side shields for

lateral protection.

Skin Protection For likely contacts, use of protective nitrile gloves or other

chemically resistant gloves.

Respiratory Protection Under normal conditions of uses, no respiratory protection

should be required due the low exposure to vapors.

Above 10 x OEL, use a positive-pressure, air-supplied

respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3.

The respirator should be fitted to the employee by a

professional.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.



8618

Section 9: Physical and Chemical Properties

Physical State	Solid	Lower Flammability Limit	Not applicable
Appearance	Grey	Upper Flammability Limit	Not applicable
Odor	None	Vapor Pressure @20 °C	Not available
Odor Threshold	Not available	Vapor Density	Not applicable
pH	Not applicable	Relative Density @25 °C	2.40
Freezing/Melting	Not	Solubility in	Insoluble
Point	available	Water	
Initial Boiling	>200 °C	Partition Coefficient n-octanol/water	Not
Point	[392 °F]		available
Flash Point	>200 °C	Auto-ignition	Not
	[392 °F]	Temperature	available
Evaporation	Not	Decomposition	Not
Rate	available	Temperature	available
Flammability	Non	Viscosity	Not
	Flammable	@40°C	available

Section 10: Stability and Reactivity

Reactivity Reacts with water and alcohols, and violently with oxidants, stro

acids , strong bases , and chlorinated hydrocarbons causing fire and $% \left(1\right) =\left(1\right) \left(1\right$

explosion hazard.

Chemical Stability

Stable under normal conditions of temperature and pressure.

Conditions to

Ignition sources, excessive heat, and incompatible substances

Avoid

Incompatibilities Strong oxidizing agents.

Polymerization Will not occur

Decomposition Will not decompose under normal conditions. For thermal

decomposition, see combustion products in Section 5.

Page **6** of **12**



8618

Section 11: Toxicological Information

Summary of Effects and Symptoms by Routes of Exposure

Eyes May cause redness and mild irritation.

Skin May cause mild irritation.

InhalationLow Toxicity—No known toxic effects.IngestionLow Toxicity—No known toxic effects.

Chronic Low Toxicity—No known long term effects.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50	LD50	LC50
	oral	dermal	inhalation
aluminum powder	>5 000 mg/kg	Not	Not
	Rat	available	available
Mixture ATE	>5 000 mg/kg	Not available	Not available

Note: Toxicity data from ECHA databases were consulted. The data from supplier SDSs were also consulted.

Other Toxicological Effects

Skin corrosion/irritation	Based on available data, the classification criteria are
	not met.

Serious eyeBased on available data, the classification criteria are not met.

Sensitization Based on available data, the classification criteria are

(allergic reactions) not met.

CarcinogenicityNone of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.

Mutagenicity Based on available data, the classification criteria are

(risk of heritable genetic effects) not met.

Section continued on the next page



SAI Global File #004008 Burlington, Ontario, Canada

8618

Reproductive Toxicity Based on available data, the classification criteria are

(risk to sex functions) not met.

Teratogenicity Based on available data, the classification criteria are

(risk of fetus malformation) not met.

STOT-single exposure Based on available data, the classification criteria are

not met.

STOT-repeated exposure Based on available data, the classification criteria are

not met.

Aspiration hazard Not applicable. There are no category 1 components,

and the kinematic viscosity is $> 20.5 \text{ mm}^2/\text{s}$.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (http://echa.europa.eu), and other reliable sources.

Based on available data, amorphous silica isn't classified as aquatic environmental toxicants according to GHS criteria.

Acute Ecotoxicity

Based on available data, the classification criteria are not met.

Chronic Ecotoxicity

Based on available data, the classification criteria are not met.

Biodegradability

Not available

Bioaccumulation

Not available

Other Effects

Not available



SAI Global File #004008 Burlington, Ontario, Canada

8618

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Non Regulated

Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Non Regulated

Sea

Refer to IMDG regulations.

Non Regulated

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

Section continued on the next page

8618

USA

Other Classifications

HMIS® RATING

HEALTH:	*	1
FLAMMABILITY:		0
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains does not contain substances which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are listed on the TSCA active list.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any of the listed substances.

Europe

RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.



SAI Global File #004008 Burlington, Ontario, Canada

8618

Section 16: Other Information

SDS Prepared by Regulatory Department

Date of Review 19 April 2023
Supersedes Not applicable

Reason for Changes: First version of SDS for 8618.

Reference

1) ACGIH 2022 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2022).

Abbreviations

ACGIH EC50 EL50 IARC NOELR NTP GHS LC50 LCL0	American Conference of Governmental Industrial Hygienists (USA) Half maximal effective concentration Half maximal effective loading International Agency for Research on Cancer No observable effect loading ratio National Toxicology Program Globally Harmonized System of Classification of Labeling of Chemicals Lethal Concentration 50% Lowest published lethal concentration
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Section continued on the next page



SAI Global File #004008 Burlington, Ontario, Canada

8618

Technical Queries Contact us regarding any questions, improvement suggestions, or

problems with this product. Application notes, instructions, and FAQs

are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Phone: +1-905-331-1396

Mailing Addresses *Manufacturing & Support*

1210 Corporate Drive

Burlington, Ontario, Canada

L7L 5R6

Disclaimer

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.