

401B

AEROSOL

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: 401B**Other Means of Identification:** Nu-trol™ Control Cleaner (Aerosol)**Related Part #** 401B-250G

Recommended Use and Restriction on Use

Use: Cleans and lubricates electrical contacts**Uses Advised Against:** Do NOT use on live circuits or in presence of ignition source

Details of Manufacturer or Importer

ManufacturerMG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADAMG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA**☎** +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** support@mgchemicals.com**WEB** www.mgchemicals.com**☎** +1-905-331-1396**FAX** +1-905-331-2682**E-MAIL** info@mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**

(Service access code: 335388)




For emergencies involving the transport of dangerous goods; 24/7 serviceCANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

401B
AEROSOL
Section 2: Hazard(s) Identification
Classification of Hazardous Chemical
GHS Categories

Criteria	Category	Signal Word	Pictograms
Flammable Aerosol	1	Danger	Flame
Aspiration Hazard	1	Danger	Health
Reproductive Toxicity	2	Warning	Health
Gases Under Pressure	Liquefied gas	Warning	Gas cylinder
Skin Irritation	2	Warning	Exclamation
Specific Target Organ Toxicity Single Exposure	3	Warning	Exclamation
Hazardous to the Aquatic Environment Chronic	2	none	Environment



Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H222: Extremely Flammable aerosol
	H280: Contains gas under pressure; may explode if heated
	H304: May be fatal if swallowed and enters airways H361: Suspected of damaging fertility or the unborn child

Section continued on the next page

401B
AEROSOL
Continued...

Pictograms	Hazard Statements
	H315: Causes skin irritation H336: May cause drowsiness or dizziness
	H411: Toxic to aquatic life with long lasting effects
Prevention	Precautionary Statements
P102 P201, P202 P210 P211 P251 P261 P271 P280 P264 P273	Keep out of reach of children. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing mist, vapors or spray. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye protection. Wash hands thoroughly after handling. Avoid release to the environment.
Response	Precautionary Statements
P308 + P313 P301 + P310, P331 P302 + P352 P332 + P313 P362 + P364 P304 + P340	IF exposed or concerned: Get medical advice or attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Section continued on the next page

401B
AEROSOL
Continued...

Response	Precautionary Statements
P312	Call a POISON CENTER or doctor if you feel unwell.
P391	Collect spillage.
Storage	Precautionary Statements
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].
P403	Store in a well-ventilated place.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Simple Asphyxiant	May displace oxygen and cause rapid suffocation.	Warning	None
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
8042-47-5	white mineral oil (petroleum)	35%
75-37-6	1,1-difluoroethane ^{a)}	30%
107-83-5	methyl-2-pentane	10–30%
96-14-0	methyl-3-pentane	5–10%
79-29-8	dimethyl-2,3-butane	3–7%
75-83-2	dimethyl-2,2-butane	3–7%
109-66-0	pentane	1–5%
110-54-3	n-hexane	1–5%

a) Also known as HFC-152a.

401B
AEROSOL
Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
IF SWALLOWED	P301 + P310, P331
Immediate Symptoms	<i>nausea, vomiting, abdominal pain, drowsiness, dizziness, weakness</i>
Response	Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.
IF ON SKIN	P302 + P352, P332 + P313, P362 + P364
Immediate Symptoms	<i>dry skin, redness, irritation</i>
Response	Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice or attention.
IF INHALED	P304 + P340, P312
Immediate Symptoms	<i>drowsiness, dizziness, headache, nausea, cough, blurry vision, fatigue</i>
Response	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.
IF IN EYES	P305 + P351 + P338, P308 + P313
Immediate Symptoms	<i>low toxicity: redness, pain</i>
Response	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice or attention.

401B

AEROSOL

Section 5: Fire-Fighting Measures

Extinguishing Media	Use dry chemical, carbon dioxide, or chemical foam to extinguish. Use water spray to cool containers.
Specific Hazards	<p>Aerosol containers may erupt with force at temperatures above 50 °C [122 °F].</p> <p>The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.</p> <p>Produces irritating and toxic fumes in fires or in contact with hot surfaces.</p> <p>The liquid may float on water and ignite.</p> <p>Prevent fire-fighting wash from entering waterway or sewer system.</p>
Combustion Products	Produces carbon oxides (CO, CO ₂).
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	<p>Avoid breathing the mist, spray or vapors.</p> <p>Remove or keep away all sources of extreme heat or open flames.</p>
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
Containment Methods	Not applicable
Cleaning Methods	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.
Disposal Methods	Dispose of spill waste according to Section 13.

401B
AEROSOL
Section 7: Handling and Storage
Prevention

Keep out of reach of children.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Avoid breathing mist, vapors or spray. Use only outdoors or in a well-ventilated area.

Do not pierce or burn, even after use.

Do not spray on an open flame or other ignition source.

Handling

Wear protective gloves and eye protection.

Wash hands thoroughly after handling.

Avoid release to the environment.

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].

Store in a well-ventilated place.

Store locked up.

Section 8: Exposure Controls/Personal Protection
Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
white mineral oil (petroleum)	ACGIH	5 mg/m ³	Not established
	U.S.A. OSHA PEL	Not established	Not established
	Canada AB	5 mg/m ³	10 mg/m ³
	Canada BC	Not established	Not established
	Canada ON	5 mg/m ³	10 mg/m ³
	Canada QC	5 mg/m ³	10 mg/m ³
1,1-difluoroethane	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	Not established	Not established
	Canada	Not established	Not established

Section continued on the next page

401B
AEROSOL
Continued...

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
methyl-2-pentane <i>Hexane isomers</i> <i>(except n-Hexane)</i>	ACGIH	500 ppm	1 000 ppm
	U.S.A. OSHA PEL	(500 ppm) ^{a)}	(1 000 ppm) ^{a)}
	Canada AB	500 ppm	1 000 ppm
	Canada BC	200 ppm	Not established
	Canada ON	500 ppm	1 000 ppm
methyl-3-pentane <i>Hexane isomers</i> <i>(except n-Hexane)</i>	ACGIH	500 ppm	1 000 ppm
	U.S.A. OSHA PEL	(500 ppm) ^{a)}	(1 000 ppm) ^{a)}
	Canada AB	500 ppm	1 000 ppm
	Canada BC	200 ppm	Not established
	Canada ON	500 ppm	1 000 ppm
dimethyl-2,3-butane <i>Hexane isomers</i> <i>(except n-Hexane)</i>	ACGIH	500 ppm	1 000 ppm
	U.S.A. OSHA PEL	(500 ppm) ^{a)}	(1 000 ppm) ^{a)}
	Canada AB	500 ppm	1 000 ppm
	Canada BC	200 ppm	Not established
	Canada ON	500 ppm	1 000 ppm
dimethyl-2,2-butane <i>Hexane isomers</i> <i>(except n-Hexane)</i>	ACGIH	500 ppm	1 000 ppm
	U.S.A. OSHA PEL	(500 ppm) ^{a)}	(1 000 ppm) ^{a)}
	Canada AB	500 ppm	1 000 ppm
	Canada BC	200 ppm	Not established
	Canada ON	500 ppm	1 000 ppm
pentane	ACGIH	600 ppm	Not established
	U.S.A. OSHA PEL	1 000 ppm	Not established
	Canada AB	600 ppm	Not established
	Canada BC	600 ppm	Not established
	Canada ON	600 ppm	Not established
n-hexane	ACGIH	50 ppm	Not established
	U.S.A. OSHA PEL	50 ppm	Not established
	Canada AB	50 ppm	Not established
	Canada BC	50 ppm	Not established
	Canada ON	50 ppm	Not established
	Canada QC	50 ppm	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from RTECS² database and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Value vacated (retracted) under court order, but still in effect in some states.

Section continued on the next page

401B**AEROSOL****Engineering Controls**

Ventilation Keep airborne concentrations below the occupational exposure limits (OEL).

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Ensure that glasses have side shields for lateral protection.

Skin Protection For likely contacts, use of protective butyl rubber or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

Respiratory Protection For over-exposures up to 10 x OEL of mist, vapors or spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

401B
AEROSOL
Section 9: Physical and Chemical Properties

Physical State	Liquid, in aerosol format	Lower Flammability Limit	1%
Appearance	Clear	Upper Flammability Limit	9%
Odor	Mild hydrocarbon	Vapor Pressure @20 °C	132 hPa [99 mmHg]
Odor Threshold	Not available	Vapor Density	2.98 (Air = 1)
pH	Not available	Relative Density @25 °C	0.77
Freezing/Melting Point	Not available	Solubility in Water	Immiscible
Initial Boiling Point	49 °C [120 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point ^{a)}	-28 °C [-20 °F]	Auto-ignition Temperature	Not available
Evaporation Rate	0.8 (Ether = 1)	Decomposition Temperature	Not available
Flammability	Extremely Flammable	Viscosity @40 °C	<20.5 mm ² /s

a) Closed cup flash point

Section 10: Stability and Reactivity

Reactivity	Not available
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Avoid open flames, ignition sources, temperatures above 50 °C [122 °F], and incompatible substances
Incompatibilities	Strong oxidizing agents, alkaline and alkaline-earth metals, powdered aluminium, zinc, magnesium and beryllium
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

401B
AEROSOL
Section 11: Toxicological Information
Summary of Effects and Symptoms by Routes of Exposure

Eyes	Low toxicity: May cause redness and pain.
Skin	Causes dry skin, redness, and irritation.
Inhalation	May cause dizziness, drowsiness, headaches, nausea, cough, blurry vision, and fatigue.
Ingestion	May cause nausea, vomiting, and abdominal pain. See inhalation symptoms.
Chronic	Prolonged or repeated exposure may cause skin dryness and a dermatitis.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
white mineral oil (petroleum)	>5 000 mg/kg Rat	Not available	Not available
1,1-difluoroethane	Not available	Not available	>437 500 ppm 4 h Rat
methyl-2-pentane	Not available	Not available	3 125 ppm 4 h Rat ^{a)}
methyl-3-pentane	Not available	Not available	Not available
dimethyl-2,3-butane	Not available	Not available	Not available
dimethyl-2,2-butane	Not available	Not available	Not available
pentane	>2 000 mg/kg Rat	Not available	>25.3 mg/L 4 h Rat (vapor)
n-hexane	15 840 mg/kg Rat	2 000 mg/kg Rabbit	48 000 ppm 4 h Rat

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier SDS were also consulted.

a) Supplier SDS

Section continued on the next page

401B

AEROSOL

Other Toxicological Effects

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Based on available data, the classification criteria are not met.
Sensitization (allergic reactions)	Based on available data, the classification criteria are not met.
Carcinogenicity (risk of cancer)	Not classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	The n-hexane component causes harm to fertility according to animal studies.
Teratogenicity (risk of fetus malformation)	The n-hexane component causes harm to fetus according to animal studies.
STOT-single exposure	Hexane isomers can affect the central nervous system by inhalation causing drowsiness or dizziness.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Mixture is a class 1 aspiration hazard. It contains over 10% class 1 aspiration hazard components and has a mixture viscosity of <math><20.5 \text{ mm}^2/\text{s}</math> at 40 °C.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Similar mixtures of isoalkanes C6-C7 with <math><5\%</math> n-hexane have a LC50 of 11.4 mg/L for rainbow trout (*Oncorhynchus mykiss*) 96 h, and an EL50 of 3.0 mg/L water flea (*Daphnia magna*) 48 h.

According to data available, white mineral oil is not classifiable as a danger to the aquatic environment.

The 1,1-difluoroethane substance is not classifiable as an environmental toxicant (with minimal LC50 96 h of 296 mg/L for unspecified fish; 147 mg/L 24 h *Daphnia magna* (water flea); 48 mg/L calculated for algae).

Section continued on the next page

401B**AEROSOL****Acute Ecotoxicity**

See chronic ecotoxicity.

Chronic Ecotoxicity

Category 2

Toxic to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

Biodegradability

Not available

Other Effects

Actual VOC (Volatile Organic Compounds) content according to the US (EPA) and Canadian (CEPA) authorities.

Actual VOC = 70% [539 g/L]

Section 13: Disposal Information

Dispose of contents and container in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information**Ground****Refer to TDG** (Canadian Transportation of Dangerous Goods regulations) and **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.****Limited Quantity****UN number:** UN1950**Shipping Name:**

AEROSOLS, flammable

Class: 2.1**Packing Group:** Not applicable**Marine Pollutant:** Yes*Section continued on the next page*

401B**AEROSOL****Air****Refer to ICAO-IATA Dangerous Goods Regulations.****Limited Quantity****UN number:** UN1950**Shipping Name:**

AEROSOLS, flammable

Class: 2.1**Packing Group:** Not applicable**Marine Pollutant:** Yes**Sea****Refer to IMDG regulations.****Limited Quantity****UN number:** UN1950**Shipping Name:**

AEROSOLS, flammable

Class: 2.1**Packing Group:** Not applicable**Marine Pollutant:** Yes

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

Section 15: Regulatory Information**Canada****Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL.


Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

Section continued on the next page

401B
AEROSOL
USA
Other Classifications
HMIS® RATING

HEALTH:	*	2
FLAMMABILITY:		3
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES


Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain ingredients that are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product contains n-hexane, which is listed as reproductively toxic.

Europe
RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment and is therefore not governed by this regulation.

401B**AEROSOL****Section 16: Other Information**

SDS Prepared by the	Regulatory Affairs Department
Date of Review	02 March 2020
Supersedes	25 February 2020
Reason for Changes:	Update to emergency phone number.

Reference

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
ECHA	European Chemicals Agency
EU	European Union
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Section continued on the next page

401B**AEROSOL**

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Phone: +1-905-331-1396

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.