

4351

# Safety Data Sheet

## Section 1: Identification



### Product Identifier and Other Means of Identification

**Product Identifier:** Thinner 1**Other Means Of Identification:** Not available**Related Part #** 4351-50ML, 4351-1L, 4351-4L, 4351-20L

### Recommended Use and Restriction on Use

**Use:** Mild thinner and paint remover for coatings and paints**Uses Advised Against:** Not available

### Details of Manufacturer or Importer

**Manufacturer**MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADAMG Chemicals (Head Office)  
9347-193 Street  
Surrey, British Columbia V4N 4E7  
CANADA +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** [support@mgchemicals.com](mailto:support@mgchemicals.com)**WEB** [www.mgchemicals.com](http://www.mgchemicals.com) +1-905-331-1396**FAX** +1-905-331-2682**E-MAIL** [info@mgchemicals.com](mailto:info@mgchemicals.com)**E-MAIL** (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)

### Emergency Phone Number



**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents)  
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**  
(Service access code: 335388)**For emergencies involving the transport of dangerous goods;** 24/7 service  
CANADA—Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones

**4351**
**Section 2: Hazards Identification**
**Classification of the Hazardous Material**
**GHS Categories**

Criteria	Category	Signal Word	Pictograms
Flammable Liquid	2	Danger	Flame
Eye Irritation	2	Warning	Exclamation
Specific Target Organ Toxicity Single Exposure	3	Warning	Exclamation
Skin Irritation	3	Warning	None

*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity). Severity categories rankings do not allow comparisons between classes.

**Label Elements**

<b>Signal Word</b>	<b>DANGER</b>
<b>Pictograms</b>	<b>Hazard Statements</b>
	H225: Highly flammable liquid and vapor
	H319: Causes serious eye irritation H336: May cause drowsiness and dizziness
No Symbol Mandated	H316: Causes mild skin irritation

*Section continued on the next page*

## 4351

*Continued ...*

<b>Prevention</b>	<b>Precautionary Statements</b>
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, and lighting equipment.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist, vapors or spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, eye protection, and face protection.
P264	Wash hands thoroughly after handling.
<b>Response</b>	<b>Precautionary Statements</b>
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, water fog, or chemical foam to extinguish.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER or doctor if you feel unwell.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water (or shower).
P332 + P313	If skin irritation occurs: Get medical advice or attention.
<b>Storage</b>	<b>Precautionary Statements</b>
P403 + P235	Store in a well-ventilated area. Keep cool.
P405	Store locked up.
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

*Section continued on the next page*

# 4351

## Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

## Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
67-63-0	propan-2-ol <sup>a)</sup>	75-85%
123-86-4	n-butyl acetate	22-25%

a) Commonly known as isopropyl alcohol (IPA)

## Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
<b>IF IN EYES</b>	P305 + P351 + P338, P337 + P313
<b>Immediate Symptoms</b>	<i>irritation, redness, pain</i>
<b>Response</b>	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  If eye irritation persists: Get medical attention.
<b>IF ON SKIN</b>	P303 + P361+ P353, P332 + P313
<b>Immediate Symptoms</b>	<i>irritation, dry skin, redness</i>
<b>Response</b>	Wash with plenty of water or shower. Take off contaminated clothing and wash it before reuse.  If skin irritation occurs: Get medical advice or attention.
<b>IF INHALED</b>	P304 + P340, P312
<b>Immediate Symptoms</b>	<i>respiratory system irritation, dizziness, drowsiness, headaches, weakness, unconsciousness</i>
<b>Response</b>	Remove person to fresh air and keep comfortable for breathing.  If feeling unwell: Call a POISON CENTER or doctor.

Section continued on the next page

**4351***Continued...*

<b>IF SWALLOWED</b>	P301 + P330 + P331, P312
<b>Immediate Symptoms</b>	<i>respiratory system irritation, nausea, headaches, weakness, unconsciousness</i>
<b>Response</b>	Rinse mouth. Do not induce vomiting. Call a POISON CENTRE or doctor if you feel unwell.

**Section 5: Fire-Fighting Measures**

<b>Extinguishing Media</b>	In case of fire: use dry chemical, carbon dioxide, or chemical foam to extinguish. Use water spray to cool containers.
<b>Specific Hazards</b>	The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion. Material may float and ignite on surface of water.
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> ), halogenated compounds, and hydrogen fluorides
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turnout gear.

**Section 6: Accidental Release Measures**

<b>Personal Protection</b>	Use personal protection recommended in Section 8.
<b>Precautions for Response</b>	Remove or keep away all sources of ignition or extreme heat. Avoid breathing the vapors/mist/spray.
<b>Environmental Precautions</b>	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
<b>Containment Methods</b>	Contain with inert absorbent (such as soil, sand, vermiculite).
<b>Cleaning Methods</b>	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.
<b>Disposal Methods</b>	Dispose spill waste according to Section 13.

**4351**
**Section 7: Handling and Storage**
**Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

For metal containers, ground and bond container and receiving equipment.

Take precautionary measures against static discharge. Use explosion-proof electrical, ventilating, and lighting equipment.

Avoid breathing fumes, mist or vapors.

Use only outdoors or in well-ventilated area. In cases of inadequate ventilation wear respiratory protection.

Do not eat, drink, or smoke when using this product.

**Handling**

Wear protective gloves, protective clothing, eye protection, and face protection.

Wash hands thoroughly after handling.

**Storage**

Keep container tightly closed. Keep away from oxidizing materials.

Store in a well-ventilated area. Keep cool.

Store locked up.

**Section 8: Exposure Controls/Personal Protection**
**Substances with Occupational Exposure Limit Values**

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
propan-2-ol	ACGIH	200 ppm (TWA)	400 ppm
	U.S.A. OSHA PEL	400 ppm	Not established
	Canada AB	200 ppm	400 ppm
	Canada BC	200 ppm	400 ppm
	Canada ON	200 ppm	400 ppm
	Canada QC	400 ppm	500 ppm

*Section continued on the next page*

## 4351

*Continued ...*

<b>Chemical Name</b>	<b>Country</b>	<b>Long Term Exposure Limits (PEL)</b>	<b>Short Term Exposure Limits (STEL)</b>
n-butyl acetate	ACGIH	150 ppm	Not established
	U.S.A. OSHA PEL	150 ppm	Not established
	Canada AB	150 ppm	200 ppm
	Canada BC	20 ppm	200 ppm
	Canada ON	150 ppm	Not established
	Canada QC	150 ppm	200 ppm

*Note:* Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS database<sup>2</sup> and from suppliers' SDSs were also consulted. Short term exposure limits (STEL) are usually for 15 min and long term permissible exposure limits (PEL) for 8 h.

### Engineering Controls

#### Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

### Personal Protective Equipment

#### Eye protection

Wear appropriate protective eyeglasses or chemical safety goggles.

**RECOMMENDATION:** Ensure that glasses have side shields for lateral protection.

#### Skin Protection

Wear appropriate protective clothing to prevent skin contact.

**RECOMMENDATION:** Use of protective gloves in butyl rubber, nitrile rubber, or other chemically resistant gloves.

#### Respiratory Protection

If exposed to high levels of fumes, mist or vapors, wear respirator such as a half-mask respirator with organic vapor cartridge.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

### General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

**4351**
**Section 9: Physical and Chemical Properties**

<b>Physical State</b>	Liquid	<b>Lower Flammability Limit</b> <sup>b)</sup>	1.7%
<b>Appearance</b>	Colorless	<b>Upper Flammability Limit</b> <sup>b)</sup>	9%
<b>Odor</b>	Alcohol-like	<b>Vapor Pressure @20 °C</b>	Not available
<b>Odor Threshold</b>	Not available	<b>Vapor Density</b>	≥2 (Air =1)
<b>pH</b>	Not available	<b>Relative Density @23 °C</b>	0.80
<b>Freezing/Melting Point</b>	Not available	<b>Solubility in Water</b>	Partially soluble
<b>Initial Boiling Point</b>	≥81.8 °C [≥179 °F]	<b>Partition Coefficient n-octanol/water</b>	Not available
<b>Flash Point</b> <sup>a)</sup>	12 °C [54 °F]	<b>Auto-ignition Temperature</b> <sup>c)</sup>	407 °C [765 °F]
<b>Evaporation Rate</b>	1.5 (ButAc = 1)	<b>Decomposition Temperature</b>	Not available
<b>Flammability</b>	Highly Flammable	<b>Viscosity @40 °C</b>	<3 mm <sup>2</sup> /s

a) Closed cup value based on propan-2-ol literature value

b) Lower and Upper Explosive Limits of mixture calculated using Le Chatelier principle and component LFL and UFL limits

c) Auto-ignition value based on n-butyl acetate literature value

**Section 10: Stability and Reactivity**

<b>Reactivity</b>	May form explosive mixture with aluminum powder when heated at temperatures ≥49 °C [≥120 °F].
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures
<b>Conditions to Avoid</b>	Ignition sources, excessive heat, and incompatible substances. Vapors may form explosive mixture with air.
<b>Incompatibilities</b>	Strong oxidizing agents, strong acids, strong bases, aluminum at temperatures ≥49 °C [≥120 °F]

*Section continued on the next page*



## 4351

<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5

### Section 11: Toxicological Information

#### Summary of Effects and Symptoms by Routes of Exposure

<b>Eyes</b>	Causes serious eye irritation, redness or pain.
<b>Skin</b>	Cause mild to moderate skin irritation.
<b>Inhalation</b>	May cause drowsiness or dizziness. Excessive exposure may cause narcotic effects. May cause irritation of nose and throat and upper respiratory system.
<b>Ingestion</b>	May be harmful if swallowed. See inhalation symptoms.
<b>Chronic</b>	Prolonged or repeated exposure may defat skin and cause skin dryness and cracking, and local redness and discomfort.

#### Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
propan-2-ol	3 600 mg/kg Rat	12 800 mg/kg Rabbit	16 000 ppm 8 h Rat
n-butyl acetate	>10 768 mg/kg Rat	>17 600 mg/kg Rabbit	390 ppm 4 h Rat

*Note:* Toxicity data from the RTECS<sup>2</sup> and ECHA databases were consulted. The data from supplier SDSs were also consulted.

#### Other Toxicological Effects

<b>Skin corrosion/irritation</b>	N-butyl acetate causes skin irritation (moderately irritating to rabbit skin: Draize test 500 mg and 24 h). Propan-2-ol is a mild skin irritant.
<b>Serious eye damage/irritation</b>	Propan-2-ol and n-butyl acetate Draize tests causes severe eye irritation for rabbits.
<b>Sensitization</b> (allergic reactions)	Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b> (risk of cancer)	Not classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.

*Section continued on the next page*

## 4351

<b>Mutagenicity</b> (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
<b>Reproductive Toxicity</b> (risk to sex functions)	Not classifiable as a reproductive hazard under GHS. Fetotoxicity for n-butyl acetates is observed in female rats for inhalation at extremely high doses of 1 500 ppm.
<b>Teratogenicity</b> (risk of fetus malformation)	Based on available data, the classification criteria are not met.
<b>STOT-single exposure</b>	Inhalation of propan-2-ol and n-butyl acetate may affect the central nervous system and may cause drowsiness, dizziness, and narcotic effects
<b>STOT-repeated exposure</b>	Based on available data, the classification criteria are not met.
<b>Aspiration hazard</b>	The liquid content does not meet the aspiration hazard criteria. The mixture doesn't contain category 1 substances.

### Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

The 2-propanol component is not classifiable as an environmental toxicant with minimal LC50 of 9 640 mg/L 96 h for *Pimephales promelas* (fathead minnow); EC50 of 5 102 mg/L 24 h *Daphnia magna* (water flea); EC50 >2 000 mg/L 72 h *Desmodesmus subcapitatus* (green algae).

The n-butyl acetate ingredient is an acute category 3 environmental toxicant liquid (biodegradable, with minimal LC50 of 18 mg/L for fathead minnow).

#### Acute Ecotoxicity

Available toxicity data does not meet classification thresholds.

#### Chronic Ecotoxicity

Available toxicity data does not meet classification thresholds.

#### Biodegradability

Not available

#### Other Effects

Regulated Volatile Organic Compound (VOC) content = 100% (800 g/L)

# 4351

## Section 13: Disposal Information


Dispose of contents in accordance with all local, regional, national, and international regulations.

## Section 14: Transport Information

### Ground

**Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Sizes 5 L and under  
4351-50ML, 4351-1L, 4351-4L  
**Limited Quantity**



Sizes greater than 5 L  
4351-20L

**UN number:** UN1263  
**Shipping Name:**  
PAINT RELATED MATERIAL  
**Class:** 3  
**Packing Group:** II  
**Marine Pollutant:** No



### Air

**Refer to ICAO-IATA Dangerous Goods Regulations.**

Sizes up to 5 L (passenger), 60 L (cargo)  
4351-50ML, 4351-1L, 4351-4L, 4351-20L



**UN number:** UN1263  
**Shipping Name:**  
PAINT RELATED MATERIAL  
**Class:** 3  
**Packing Group:** II  
**Marine Pollutant:** No



*Section continued on the next page*

# 4351

## Sea

<b>Refer to IMDG regulations.</b>	
Sizes 5 L and under 4351-50ML, 4351-1L, 4351-4L <b>Limited Quantity</b> 	Sizes greater than 5 L 4351-20L <b>UN number:</b> UN1263 <b>Shipping Name:</b> PAINT RELATED MATERIAL <b>Class:</b> 3 <b>Packing Group:</b> II <b>Marine Pollutant:</b> No 

**Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.**

## Section 15: Regulatory Information

### Canada

#### Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL/NDSL.

#### Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.


### USA

#### Other Classifications

##### HMIS® RATING

<b>HEALTH:</b>	<b>2</b>
<b>FLAMMABILITY:</b>	<b>3</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	

##### NFPA® 704 CODES



*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

*Section continued on the next page*

## 4351

### CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

### EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains  $\geq 75\%$  propan-2-ol (CAS # 67-63-0) which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

This product contains  $\geq 22\%$  n-butyl acetate (CAS# 123-86-4), which is subject to the CERCLA reporting requirements at the 5 000 lb (2 268 kg) threshold.

### TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

### California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA)

This product does not contain any of the listed substances.

### SCAQMD Rule 1143 (California South Coast District)

Within the boundaries of the South Coast Air Quality Management District (in California), this product is for commercial and industrial use only, and must not be displayed for retail sale to consumers.

## Europe

### RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

### WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

## Section 16: Other Information

<b>SDS Prepared by</b>	MG Chemical's Regulatory Department
<b>Date of Revision</b>	06 March 2020
<b>Supersedes</b>	10 February 2020
<b>Reason for Changes:</b>	Update to the emergency phone number information.

*Section continued on the next page*

## 4351

### References

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

### Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

**Mailing Addresses** *Manufacturing & Support*  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

*Head Office*  
9347-193rd Street  
Surrey, British Columbia, Canada  
V4N 4E7

### Disclaimer

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.