

841WB

# Safety Data Sheet

## Section 1: Identification



### Product Identifier and Other Means of Identification

**Product Name:** 841WB**Other Means of Identification:** Super Shield™ Water Based Nickel Conductive Paint /  
Water Based Nickel Conductive Paint**Related Part #** 841WB-15ML, 841WB-150ML, 841WB-850ML, 841WB-3.78L

### Recommended Use and Restriction on Use

**Use:** Nickel filled, electrically conductive coating**Uses Advised Against:** Not available

### Details of Manufacturer or Importer

**Manufacturer**MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADAMG Chemicals (Head Office)  
9347-193 Street  
Surrey, British Columbia V4N 4E7  
CANADA +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** [support@mgchemicals.com](mailto:support@mgchemicals.com)**WEB** [www.mgchemicals.com](http://www.mgchemicals.com) +1-905-331-1396**FAX** +1-905-331-2682**E-MAIL** [info@mgchemicals.com](mailto:info@mgchemicals.com)**E-MAIL** (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)

### Emergency Phone Number



**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents)  
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**  
(Service access code: 335388)**For emergencies involving the transport of dangerous goods;** 24/7 service  
CANADA—Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones

**841WB**
**Section 2: Hazard(s) Identification**
**Classification of Hazardous Chemical**
**GHS Categories**

Criteria	Category	Signal Word	Pictograms
Reproductive Toxicity	1	Danger	Health
Specific Target Organ Toxicity Repeated Exposure	1	Danger	Health
Carcinogenicity	2	Warning	Health
Sensitization Skin	1	Warning	Exclamation
Hazardous to the Aquatic Environment Chronic	3	<i>none</i>	<i>none</i>

*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

**Label Elements**

<b>Signal Word</b>	<b>DANGER</b>
<b>Pictograms</b>	<b>Hazard Statements</b>
	H360: May damage fertility or the unborn child H372: Causes damages to organs (lungs) through prolonged or repeated exposure by inhalation H351: Suspected of causing cancer
	H317: May cause allergic skin reaction
<i>None</i>	H412: Harmful to aquatic life with long lasting effects

*Section continued on the next page*

**841WB**
*Continued ...*

<b>Prevention</b>	<b>Precautionary Statements</b>
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe mist, spray, and vapors.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves, protective clothing, and eye protection.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
<b>Response</b>	<b>Precautionary Statements</b>
P308 + P313	IF exposed or concerned: Get medical advice or attention.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P314	Get medical attention or advice if you feel unwell.
<b>Storage</b>	<b>Precautionary Statements</b>
P405	Store locked up.
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of contents in accordance to local, regional, national and international regulations.

**Hazards Not Otherwise Classified**

<b>Other Criteria</b>	<b>Hazard Statements/Precautionary Statement</b>	<b>Signal Word</b>	<b>Pictograms</b>
None	None	None	None

**841WB**
**Section 3: Composition/Information on Ingredients**

CAS #	Chemical Name	%(weight)
7440-02-0	nickel	48%
14807-96-6	talc	2%
126-33-0	sulpholane	1%

**Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
<b>IF ON SKIN</b>	P302 + P352, P333 + P313, P362 + P364, P308 + P313
<b>Immediate Symptoms</b>	<i>dry skin, redness, allergic rash</i>
<b>Response</b>	Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice or attention.
<b>IF INHALED</b>	P304 + P340, P308 + P313
<b>Immediate Symptoms</b>	<i>cough, shortness of breath, headache</i>
<b>Response</b>	Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice or attention.
<b>IF IN EYES</b>	P305 + P351 + P338
<b>Immediate Symptoms</b>	<i>redness, blurred vision, pain</i>
<b>Response</b>	Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>IF SWALLOWED</b>	P301 + P330 + P331, P308 + P313
<b>Immediate Symptoms</b>	<i>low toxicity: no symptoms known or expected</i>
<b>Response</b>	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF exposed or concerned: Get medical advice or attention.

841WB

**Section 5: Fire-Fighting Measures**

<b>Extinguishing Media</b>	In case of fire use extinguishing media suitable for surrounding material.
<b>Specific Hazards</b>	Produces irritating and toxic fumes in fires or in contact with hot surfaces. May produce very toxic nickel carbonyl gas in the presence of carbon monoxide in a reducing atmosphere.
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> ), nickel oxides fumes, and nitrogen oxides (NO <sub>x</sub> ).
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

**Section 6: Accidental Release Measures**

<b>Personal Protection</b>	Use personal protection recommendations in Section 8.
<b>Precautions for Response</b>	Do not breathe the mist, spray, and vapors. Remove or keep away all sources of extreme heat or open flames.
<b>Environmental Precautions</b>	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
<b>Containment Methods</b>	Contain with inert and non-flammable absorbent (such as soil, sand, vermiculite).
<b>Cleaning Methods</b>	Collect liquid in a sealable, waste container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.
<b>Disposal Methods</b>	Dispose of spill waste according to Section 13.

841WB

**Section 7: Handling and Storage****Prevention**

Keep out of reach of children.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Do not breathe mist, spray, and vapors.

Do not eat, drink, or smoke when using this product.

Contaminated work clothing should not be allowed out of the workplace.

**Handling**

Wear protective gloves, protective clothing, and eye protection.

Take off contaminated clothing and wash it before reuse.

Wash hands thoroughly after handling.

Avoid release to the environment.

**Storage**

Store locked up.

**Section 8: Exposure Controls/Personal Protection****Substances with Occupational Exposure Limit Values**

<b>Chemical Name</b>	<b>Country/ Provinces</b>	<b>Long Term Exposure Limits (PEL)</b>	<b>Short Term Exposure Limits (STEL)</b>
nickel	ACGIH	1.5 mg/m <sup>3</sup>	Not established
	U.S.A. OSHA PEL	1 mg/m <sup>3</sup>	Not established
	Canada AB	1.5 mg/m <sup>3</sup>	Not established
	Canada BC	0.05 mg/m <sup>3</sup>	Not established
	Canada ON	1 mg/m <sup>3</sup>	Not established
	Canada QC	1 mg/m <sup>3</sup>	Not established

*Section continued on the next page*

**841WB**
*Continued...*

<b>Chemical Name</b>	<b>Country/ Provinces</b>	<b>Long Term Exposure Limits (PEL)</b>	<b>Short Term Exposure Limits (STEL)</b>
talc (non-asbestos fiber)	ACGIH	2 mg/m <sup>3</sup>	Not established
	U.S.A. OSHA PEL	20 mppcf <sup>a)</sup>	Not established
	Canada AB	2 mg/m <sup>3</sup>	Not established
	Canada BC	2 mg/m <sup>3</sup>	Not established
	Canada ON	2 mg/m <sup>3</sup>	Not established
	Canada QC	3 mg/m <sup>3</sup>	Not established

*Note:* Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from by RTECS database<sup>2</sup> and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Million particles per cubic foot of air, based on impinge samples counted by light-field technique.

**Engineering Controls**
**Ventilation**

Keep airborne concentrations below the occupational exposure limits (OEL).

**Personal Protective Equipment**
**Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

**RECOMMENDATION:** Ensure that glasses have side shields for lateral protection.

**Skin Protection**

For likely or incidental contacts, use nitrile, neoprene, or other chemically resistant gloves.

*Section continued on the next page*

---

**841WB**

**Respiratory Protection** For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges and particulate filter.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

### General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.



**841WB**
**Section 9: Physical and Chemical Properties**

<b>Physical State</b>	Liquid	<b>Lower Flammability Limit</b>	Not applicable
<b>Appearance</b>	Dark grey	<b>Upper Flammability Limit</b>	Not applicable
<b>Odor</b>	Musty	<b>Vapor Pressure</b> <sup>a)</sup>	23 hPa [17 mmHg]
<b>Odor Threshold</b>	Not available	<b>Vapor Density</b>	Not available
<b>pH</b>	Not available	<b>Relative Density @25 °C</b>	1.81
<b>Freezing/Melting Point</b>	Not available	<b>Solubility in Water</b>	Miscible
<b>Initial Boiling Point</b>	100 °C [212 °F]	<b>Partition Coefficient n-octanol/water</b>	Not available
<b>Flash Point</b>	Not available	<b>Auto-ignition Temperature</b>	Not available
<b>Evaporation Rate</b>	Not available	<b>Decomposition Temperature</b>	Not available
<b>Flammability</b>	Non Flammable	<b>Viscosity @40 °C</b>	Not available

a) Calculated using from volatile components parameters and Raoult's Law.

**Section 10: Stability and Reactivity**

<b>Reactivity</b>	<p>The nickel can react vigorously with acids and liberate hydrogen, which can form an explosive mixture in air.</p> <p>Nickel may react with carbon monoxide in a reducing atmosphere to form a very toxic nickel carbonyl gas.</p>
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures
<b>Conditions to Avoid</b>	Ignition sources, open flames, excessive heat, and incompatible substances
<b>Incompatibilities</b>	Oxidizing agents, strong acids, acid anhydrides

*Section continued on the next page*

**841WB**

<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Does not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

**Section 11: Toxicological Information**
**Summary of Effects and Symptoms by Routes of Exposure**

<b>Eyes</b>	May cause redness, mild irritation and/or pain.
<b>Skin</b>	May cause dry skin, redness and/or allergic rash.
<b>Inhalation</b>	May cause cough, shortness of breath and/or headaches.
<b>Ingestion</b>	Low toxicity: no symptoms known or expected.
<b>Chronic</b>	Chronic inhalation exposure to nickel dust, mist, or spray may affect the central nervous system, damage lungs. Nickel is suspected of being a carcinogen.

**Acute Toxicity (Lethal Exposure Concentrations)**

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
nickel	9 000 mg/kg Rat	Not available	10.2 mg/L 1 h Rat
talc	Not available	Not available	Not available
sulpholane	2 130 mg/kg Rat	2 000 mg/kg Rat	12 000 mg/L 4 h Rat

*Note:* Toxicity data from the RTECS<sup>2</sup> and ECHA databases were consulted. The data from supplier SDSs were also consulted.

*Section continued on the next page*

841WB

**Other Toxicological Effects**

<b>Skin corrosion/irritation</b>	Based on available data, the classification criteria are not met.
<b>Serious eye damage/irritation</b>	Based on available data, the classification criteria are not met. Contains mechanically abrasive particles.
<b>Sensitization</b> (allergic reactions)	Exposure to nickel may cause allergic skin reaction.
<b>Carcinogenicity</b> (risk of cancer)	Nickel is classified as a suspect carcinogen based on animal intratracheal instillation (intubation) or interperitoneal (in body cavity) injection studies. A reliable 2008 study by Oller et al. shows no carcinogenicity for the nickel metal via normal inhalation route. <b>Nickel [7440-02-0]</b> IARC Group 2B: Possibly carcinogenic to humans ACGIH A5: Not suspected as a human carcinogen CA Prop 65: Listed as a carcinogen NTP: Reasonably anticipated to be human carcinogen
<b>Mutagenicity</b> (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
<b>Reproductive Toxicity</b> (risk to sex functions)	Sulophane may damage fertility.
<b>Teratogenicity</b> (risk of fetus malformation)	Sulophane may damage the unborn child.
<b>STOT-single exposure</b>	Based on available data, the classification criteria are not met.
<b>STOT-repeated exposure</b>	Nickel particles can damage the respiratory tract leading to inflammation, lung fibrosis, and accumulation of nickel particles in a rat study.
<b>Aspiration hazard</b>	There are no category 1 components, and the kinematic viscosity of the mixture is $>20.5 \text{ mm}^2/\text{s}$ at $40 \text{ }^\circ\text{C}$ .

**841WB****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Nickel powder less than 1 mm diameter is classified as a chronic category 3 aquatic pollutant by ECHA registrants.

**Acute Ecotoxicity**

Available toxicity data does not meet classification thresholds.

**Chronic Ecotoxicity**

Category 3

Harmful to aquatic life with long lasting effects.

Avoid release to the environment. Collect spillage.

**Biodegradability**

The nickel content is not biodegradable.

**Other Effects**

Actual VOC (Volatile Organic Compounds) content according to the US (EPA) and Canadian (CEPA) authorities.

Actual VOC = 1.6% [28 g/L]; Regulated VOC = 147 g/L

*Note:* Nickel can be recovered from the waste to reclaim the value of the nickel.

**Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, national, and international regulations.

**841WB****Section 14: Transport Information****Ground****Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations) and **US DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Not Regulated

**Air****Refer to ICAO-IATA Dangerous Goods Regulations.**

Not Regulated

**Sea****Refer to IMDG Dangerous Goods Regulations.**

Not Regulated

**Section 15: Regulatory Information****Canada****Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL.

**Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

*Section continued on the next page*

841WB


## USA

## Other Classifications

## HMIS® RATING

HEALTH:	*	2
FLAMMABILITY:		0
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

## NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

**CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain products that are listed as hazardous air pollutants.

**EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains nickel (CAS# 7440-02-0, reportable quantity = 100 lb), which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

**TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity, USA)

This product contains nickel, which is listed as a carcinogen.

*Section continued on the next page*

**841WB****Europe****RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

**Section 16: Other Information**

**SDS Prepared by** MG Chemicals' Regulatory Department

**Date of Review** 27 February 2020

**Supersedes** 10 October 2019

**Reason for Changes:** Change of emergency phone number.

**Reference**

1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
ECHA	European Chemicals Agency
EU	European Union
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%

*Section continued on the next page*

**841WB**

OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

**Mailing Addresses** *Manufacturing & Support*  
1210 Corporate Drive  
Burlington, Ontario,  
Canada  
L7L 5R6

*Head Office*  
9347-193rd Street  
Surrey, British Columbia,  
Canada  
V4N 4E7

**Disclaimer**

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.