

842AR

SUPER SHIELD™ SILVER CONDUCTIVE COATING (AEROSOL)

# Safety Data Sheet

## Section 1: Identification

### Product Identifier and Other Means of Identification

**Product Identifier:** 842AR**Other Means of Identification:** Super Shield™ Silver Conductive Coating (Aerosol)**Related Part #** 842AR-140G

### Recommended Use and Restriction on Use

**Use:** Electrically conductive coating and EMI/RFI shielding**Uses Advised Against:** Not available

### Details of Manufacturer or Importer

**Manufacturer**MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADAMG Chemicals (Head Office)  
9347-193 Street  
Surrey, British Columbia V4N 4E7  
CANADA**☎** +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** [support@mgchemicals.com](mailto:support@mgchemicals.com)**WEB** [www.mgchemicals.com](http://www.mgchemicals.com)**☎** +1-905-331-1396**FAX** +1-905-331-2682**E-MAIL** [info@mgchemicals.com](mailto:info@mgchemicals.com)**E-MAIL** (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)

### Emergency Phone Number

**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents)USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**

(Service access code: 335388)

**For emergencies involving the transport of dangerous goods;** 24/7 serviceCANADA—Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones



**842AR**
**SUPER SHIELD™ SILVER CONDUCTIVE COATING (AEROSOL)**
**Section 2: Hazard(s) Identification**
**Classification of Hazardous Chemical**
**GHS Categories**

Criteria	Category	Signal Word	Pictograms
Flammable Aerosol	2	Warning	Flame
Gas Under Pressure	Liquefied gas	Warning	Gas cylinder
Eye Irritation	2	Warning	Exclamation
Specific Target Organ Toxicity Single Exposure	3	Warning	Exclamation
Hazardous to the Aquatic Environment Chronic	1	Warning	Environment

*Note:* The degree of severity is ranked within each hazard class from



1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

**Label Elements**

<b>Signal Word</b>	<b>WARNING</b>
<b>Pictograms</b>	<b>Hazard Statements</b>
	H223: Flammable aerosol
	H280: Contains gas under pressure; may explode if heated

*Section continued on the next page*

**842AR**
**SUPER SHIELD™ SILVER CONDUCTIVE COATING (AEROSOL)**
*Continued...*

<b>Pictograms</b>	<b>Hazard Statements</b>
	H319: Causes serious eye irritation H336: May cause drowsiness and dizziness
	H410: Very toxic to aquatic life with long lasting effects
<b>Prevention</b>	<b>Precautionary Statements</b>
P102 P210 P211 P251 P261 P264 P271 P280 P273	Keep out of reach of children. Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing mist, vapors, and spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection. Avoid release to the environment.
<b>Response</b>	<b>Precautionary Statements</b>
P305 + P351 + P338 P337 + P313 P304 + P340 P312	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

*Section continued on the next page*

**842AR**
**SUPER SHIELD™ SILVER CONDUCTIVE COATING (AEROSOL)**

Continued...

<b>Storage</b>	<b>Precautionary Statements</b>
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].
P403	Store in a well-ventilated place.
P405	Store locked up.
P391	Collect spillage.
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of contents and container in accordance to local, regional, and international regulations.

**Hazards Not Otherwise Classified**

<b>Other Criteria</b>	<b>Hazard Statements/Precautionary Statement</b>	<b>Signal Word</b>	<b>Pictograms</b>
Simple Asphyxiant	May displace oxygen and cause rapid suffocation.	Warning	None
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None
Argyria	Long term exposure to silver powder or compounds can lead to an irreversible blue-grey discoloration of the skin.	None	None

**Section 3: Composition/Information on Ingredients**

<b>CAS #</b>	<b>Chemical Name</b>	<b>%(weight)</b>
7440-22-4	silver	32%
67-64-1	acetone	17%
74-98-6	propane	13%
616-38-6	dimethyl carbonate	10%
75-28-5	isobutane	7%
123-86-4	n-butyl acetate	6%
110-43-0	heptan-2-one <sup>a)</sup>	6%
14807-96-6	talc (non-asbestos fiber)	0.4%

a) Commonly known as methyl amyl ketone (MAK)

842AR

SUPER SHIELD™ SILVER CONDUCTIVE COATING (AEROSOL)

**Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
<b>IF IN EYES</b>	P305 + P351 + P338, P337 + P313
<b>Immediate Symptoms</b>	<i>redness, severe irritation, pain</i>
<b>Response</b>	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
<b>IF INHALED</b>	P304 + P340, P312
<b>Immediate Symptoms</b>	<i>cough, drowsiness, dizziness, headaches, nausea</i>
<b>Response</b>	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.
<b>IF SWALLOWED</b>	P301 + P330 + P331
<b>Immediate Symptoms</b>	<i>nausea, sore throat, abdominal pain, diarrhea, drowsiness, dizziness</i>
<b>Response</b>	Rinse mouth. Do NOT induce vomiting.
<b>IF ON SKIN</b>	P302 + P352
<b>Immediate Symptoms</b>	<i>redness, mild irritation, dry skin</i>
<b>Response</b>	Wash with plenty of water.

**Section 5: Fire-Fighting Measures**

<b>Extinguishing Media</b>	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish. Use water spray to cool containers.
<b>Specific Hazards</b>	Aerosols containers may erupt with force at temperatures above 50 °C [122 °F]. The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion. Prevent fire-fighting wash from entering waterway or sewer system.
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> ) and metal oxide fumes.
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

**842AR****SUPER SHIELD™ SILVER CONDUCTIVE COATING (AEROSOL)****Section 6: Accidental Release Measures**

<b>Personal Protection</b>	See personal protection recommendations in Section 8.
<b>Precautions for Response</b>	Avoid breathing mist, spray, and vapors. Remove or keep away all sources of extreme heat or open flames.
<b>Environmental Precautions</b>	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
<b>Containment Methods</b>	Not applicable
<b>Cleaning Methods</b>	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.
<b>Disposal Methods</b>	Dispose of spill waste according to Section 13.

**Section 7: Handling and Storage**

<b>Prevention</b>	Keep out of reach of children.  Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.  Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  Avoid breathing mist, vapors, and spray. Use only outdoors or in a well-ventilated area.  Do not pierce or burn, even after use.
<b>Handling</b>	Do not spray on an open flame or other ignition source.  Wear protective gloves, protective clothing, and eye protection.  Wash hands thoroughly after handling.
<b>Storage</b>	Avoid release to the environment. Collect spillage.  Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].  Store in a well-ventilated place.  Store locked up.

**842AR**
**SUPER SHIELD™ SILVER CONDUCTIVE COATING (AEROSOL)**
**Section 8: Exposure Controls/Personal Protection**
**Substances with Occupational Exposure Limit Values**

<b>Chemical Name</b>	<b>Country/ Provinces</b>	<b>Long Term Exposure Limits (PEL)</b>	<b>Short Term Exposure Limits (STEL)</b>
silver <i>(metal dust, mist)</i> <i>(metal)</i> <i>(Ag and its compounds)</i> <i>(metal, dust, fumes)</i>	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	0.1 mg/m <sup>3</sup> 0.01 mg/m <sup>3</sup> 0.1 mg/m <sup>3</sup> 0.01 mg/m <sup>3</sup> 0.1 mg/m <sup>3</sup> 0.1 mg/m <sup>3</sup>	Not established Not established Not established 0.03 mg/m <sup>3</sup> Not established Not established
acetone	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	500 ppm 1 000 ppm 500 ppm 250 ppm 500 ppm 750 ppm	750 ppm Not established 750 ppm 500 ppm 750 ppm 1 000 ppm
propane  <i>Aliphatic hydrocarbon gas</i>	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	See footnote <sup>a)</sup> 1 000 ppm 1 000 ppm 1 000 ppm 1 000 ppm 1 000 ppm	Not established Not established Not established Not established Not established Not established
isobutane <i>Alkane (C2-C4)</i> <i>Aliphatic hydrocarbon gas</i>	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	See footnote <sup>a)</sup> Not established 1 000 ppm 1 000 ppm 800 ppm Not established	Not established Not established Not established Not established Not established Not established
n-butyl acetate	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	150 ppm 150 ppm (Vacated) 150 ppm 20 ppm 150 ppm 150 ppm	Not established Not established 200 ppm 200 ppm Not established 200 ppm
heptan-2-one <i>methyl amyl ketone</i>	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	50 ppm 100 ppm 50 ppm 50 ppm 25 ppm 50 ppm	Not established Not established Not established Not established Not established Not established

*Section continued on the next page*

**842AR**
**SUPER SHIELD™ SILVER CONDUCTIVE COATING (AEROSOL)**

Continued...

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
talc (without asbestos fibers)	ACGIH	2 mg/m <sup>3</sup>	Not established
	U.S.A. OSHA PEL	20 mppcf <sup>a)</sup>	Not established
	Canada AB	2 mg/m <sup>3</sup>	Not established
	Canada BC	2 mg/m <sup>3</sup>	Not established
	Canada ON	2 mg/m <sup>3</sup>	Not established
	Canada QC	3 mg/m <sup>3</sup>	Not established

*Note:* Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS database<sup>2</sup> and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) See Appendix F: Minimal Oxygen Content in ACGIH<sup>1</sup>

### Engineering Controls

**Ventilation**

Keep airborne concentrations below the occupational exposure limits (OEL).

### Personal Protective Equipment

**Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

**RECOMMENDATION:** Ensure that glasses have side shields for lateral protection.

**Skin Protection**

For likely contacts, use of protective butyl rubber or other chemically resistant gloves.

**Respiratory Protection**

For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.



**842AR**
**SUPER SHIELD™ SILVER CONDUCTIVE COATING (AEROSOL)**
**General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.

**Section 9: Physical and Chemical Properties**

<b>Physical State</b>	Liquid, in an aerosol format	<b>Lower Flammability Limit</b> <sup>b)</sup>	2.5%
<b>Appearance</b>	Light gray	<b>Upper Flammability Limit</b> <sup>b)</sup>	12.5%
<b>Odor</b>	Acetone-like	<b>Vapor Pressure @20 °C</b> <sup>c)</sup>	14 kPa [108 mmHg]
<b>Odor Threshold</b> <sup>a)</sup>	5 ppm	<b>Vapor Density</b>	≥1.5 (Air =1)
<b>pH</b>	Not available	<b>Relative Density @25 °C</b>	1.48
<b>Freezing/Melting Point</b>	Not available	<b>Solubility in Water</b>	Partially miscible
<b>Initial Boiling Point</b> <sup>a)</sup>	≥56 °C [≥132 °F]	<b>Partition Coefficient n-octanol/water</b>	Not available
<b>Flash Point</b> <sup>a)</sup>	-17 °C [1.4 °F]	<b>Auto-ignition Temperature</b> <sup>d)</sup>	≥330 °C [≥626 °F]
<b>Evaporation Rate</b>	Fast	<b>Decomposition Temperature</b>	Not available
<b>Flammability</b>	Flammable	<b>Viscosity @25 °C</b>	>20.5 mm <sup>2</sup> /s

a) The values for the boiling point, closed cup flash point, and odor threshold are based on the acetone component.

b) Lower and Upper Explosive Limits of mixture calculated using Le Chatelier principle and liquid component LFL and UFL limits

c) For liquid component excluding the propellant

**842AR**
**SUPER SHIELD™ SILVER CONDUCTIVE COATING (AEROSOL)**
**Section 10: Stability and Reactivity**

<b>Reactivity</b>	Not available
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures
<b>Conditions to Avoid</b>	Temperatures above 50 °C [122 °F], open flames, and incompatible substances
<b>Incompatibilities</b>	Oxidizing agents, strong acids, peroxides, alkali or alkali earth metals
<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

**Section 11: Toxicological Information**
**Summary of Effects and Symptoms by Routes of Exposure**

<b>Eyes</b>	May cause redness, severe irritation, and pain.
<b>Inhalation</b>	May cause cough, drowsiness, dizziness, headaches, nausea, or unconsciousness.
<b>Ingestion</b>	May cause nausea, sore throat, abdominal pain, and diarrhea (also see inhalation symptoms).
<b>Skin</b>	May cause skin redness, mild irritation, and dry skin.
<b>Chronic</b>	Prolonged or repeated exposure may cause skin dryness, cracking, as well as defatting the skin. Exposure to silver powder may also cause argyria, an irreversible blue-grey discoloration of the skin.

**Acute Toxicity (Lethal Exposure Concentrations)**

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
silver	>2 000 mg/kg Rat	>2 000 mg/kg Rat	5.16 mg/m <sup>3</sup> 4 h Rat (dust)
acetone	5 800 mg/kg Rat	20 mL/kg Rabbit <sup>a)</sup>	16 000 ppm 4 h Rat <sup>a)</sup>

*Section continued on the next page*

**842AR**
**SUPER SHIELD™ SILVER CONDUCTIVE COATING (AEROSOL)**
*Continued...*

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
propane	Not Applicable	Not Applicable	>800 000 ppm 4 h Rat
dimethyl carbonate	>6.4 g/kg Rat & Mouse	>5 000 mg/kg Rabbit	Not available
isobutane	Not applicable	Not applicable	>570 000 ppm 4 h Rat
n-butyl acetate	>10 768 mg/kg Rat	>17 600 mg/kg Rabbit	390 ppm 4 h Rat
heptan-2-one	1 670 mg/kg Rat	12 600 µL/kg Rabbit	>16.7 mg/kg 4 h Rat
talc (non-asbestos fiber)	Not available	Not available	Not available

*Note:* Toxicity data from the RTECS<sup>2</sup> and ECHA databases were consulted. The data from supplier SDSs were also consulted.

a) Supplier safety data sheet

**Other Toxicological Effects**

<b>Skin corrosion/irritation</b>	Based on available data, the classification criteria are not met.
<b>Serious eye damage/irritation</b>	Acetone is a known serious eye irritant. Mixture contains mechanically abrasive particles.
<b>Sensitization</b> (allergic reactions)	Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b> (risk of cancer)	Based on available data, the classification criteria are not met.
<b>Mutagenicity</b> (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
<b>Reproductive Toxicity</b> (risk to sex functions)	Based on available data, the classification criteria are not met.
<b>Teratogenicity</b> (risk of fetus malformation)	Based on available data, the classification criteria are not met.

*Section continued on the next page*

**842AR****SUPER SHIELD™ SILVER CONDUCTIVE COATING (AEROSOL)**

<b>STOT-single exposure</b>	Inhalation of acetone, n-butyl acetate, heptan-2-one may affect the central nervous system.
<b>STOT-repeated exposure</b>	Based on available data, the classification criteria are not met.
<b>Aspiration hazard</b>	Based on available data, the classification criteria are not met. There is less than 10% category 1 components.

**Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Contains silver of less than a 1 mm but more than 100 nm (larger than nanoparticles), which release ionic silver levels that are very toxic to the environment. While massive silver are insoluble in water, the powders are considered sufficiently soluble to give rise to an ecological hazard by EU regulators. The classification that follows takes into account to chronic aqueous toxicity of category 1 (M = 10 for silver) of the EU.

Acetone and heptan-2-one are not classifiable as an environmental toxicant (with minimal LC50 of >100 mg/L).

- Acetone has a minimal LC50 96 h of 5 540 mg/L for *Oncorhynchus mykiss* (rainbow trout) and an EC50 48 h of 13 500 mg/L for *Daphnia magna* (water flea).
- Heptan-2-one has a minimal LC50 96 h of 126 mg/L for *Pimephales promelas* (fathead minnow).

There is insufficient data to classify dimethyl carbonate for aqueous toxicity.

The n-butyl acetate ingredient is an acute category 3 environmental toxicant (biodegradable, with minimal LC50 of 18 mg/L for fathead minnow).

Based on available data talc (non-asbestos fiber) is classified as aquatic environmental toxicants according to GHS criteria.

**Acute Ecotoxicity**

Category 1

Very toxic to aquatic life

*Section continued on the next page*

**842AR****SUPER SHIELD™ SILVER CONDUCTIVE COATING (AEROSOL)****Chronic Ecotoxicity**

Category 1

Very toxic to aquatic life with long lasting effects.

Avoid release to the environment. Collect spillage.

**Biodegradability**

Solvent part expected to be biodegradable, but not the polymer or metal filler. The volatile solvent constituents will oxidize rapidly in air by photochemical reaction.

**Other Effects**

Actual VOC (Volatile Organic Compounds) content according to the US (EPA) and Canadian (CEPA) authorities.

Actual VOC = 34% [361 g/L]

**Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, national, and international regulations.

**Section 14: Transport Information****Ground****Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations);  
**USA CFR 49 Regulations** (Parts 100 to 185).**Limited Quantity***FOR REFERENCE ONLY***UN number:** UN1950**Shipping Name:** AEROSOL,  
flammable**Class:** 2.1**Packing Group:** Not applicable**Marine Pollutant:** Yes*Section continued on the next page*

**842AR****SUPER SHIELD™ SILVER CONDUCTIVE COATING (AEROSOL)****Air****Refer to ICAO-IATA Dangerous Goods Regulations.****Limited Quantity**See package  
instruction Y203Max Net Qty/Pkg  
30 kg G*FOR REFERENCE ONLY***UN number:** UN1950**Shipping Name:** AEROSOL,  
flammable**Class:** 2.1**Packing Group:** Not applicable**Marine Pollutant:** Yes**Sea****Refer to IMDG regulations.****Limited Quantity***FOR REFERENCE ONLY***UN number:** UN1950**Shipping Name:** AEROSOL,  
flammable**Class:** 2.1**Packing Group:** Not applicable**Marine Pollutant:** Yes

**Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.**

**Section 15: Regulatory Information****Canada****Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL.


**Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

*Section continued on the next page*

**842AR**
**SUPER SHIELD™ SILVER CONDUCTIVE COATING (AEROSOL)**
**USA**
**Other Classifications**
**HMIS® RATING**

<b>HEALTH:</b>	<b>* 2</b>
<b>FLAMMABILITY:</b>	<b>3</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	

**NFPA® 704 CODES**


*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

**CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain products that are listed as hazardous air pollutants.

**EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains silver (CAS# 7440-22-4; reportable quantity = 1 000 lb) which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

This product contains acetone (CAS# 67-64-1) and n-butyl acetate (CAS# 123-86-4), which are subject to the CERCLA reporting requirements at the 5 000 lb (2 268 kg) threshold.

**TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity)

This product does not contain any substances on the California Proposition 65 list.

**Europe**
**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

**842AR****SUPER SHIELD™ SILVER CONDUCTIVE COATING (AEROSOL)****Section 16: Other Information**

<b>SDS Prepared by</b>	MG Chemicals' Regulatory Department
<b>Date of Review</b>	03 March 2020
<b>Supersedes</b>	08 January 2020
<b>Reason for Changes:</b>	Update to the emergency phone number information.

**Reference**

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
ECHA	European Chemicals Agency
EU	European Union
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

*Section continued on the next page*



**842AR****SUPER SHIELD™ SILVER CONDUCTIVE COATING (AEROSOL)**

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

**Mailing Addresses** *Manufacturing & Support*  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

*Head Office*  
9347-193rd Street  
Surrey, British Columbia, Canada  
V4N 4E7

**Disclaimer**

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.