

844AR

ACRYLIC ESD COATING (AEROSOL)

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: 844AR**Other Product Identifier:** Acrylic ESD Coating (Aerosol)**Part Numbers:** 844AR-340G

Recommended Use and Restriction on Use

Use: Static protection for electronic components**Uses Advised Against:** Not available

Details of Manufacturer or Importer

Manufacturer

MG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA

MG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA

☎ 1-800-340-0772**FAX** 1-800-340-0773**E-MAIL:** support@mgchemicals.com**WEB** www.mgchemicals.com**☎** 1-905-331-1396**FAX** 1-905-331-2682**E-MAIL:** info@mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**
(Service access code: 335388)




For emergencies involving the transport of dangerous goods; 24/7 service
CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

844AR
ACRYLIC ESD COATING (AEROSOL)
Section 2: Hazard(s) Identification
Classification of Hazardous Chemical
GHS Categories

Criteria	Category	Signal Word	Pictograms
Sensitization Skin	1	Warning	Exclamation
Eye Irritation	2	Warning	Exclamation
Specific Target Organ Toxicity Single Exposure	3	Warning	Exclamation
Flammable Aerosol	2	Warning	Flame
Gas Under Pressure Liquefied Gas	Liquefied Gas	Warning	Gas cylinder

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity). Severity categories do not allow comparisons between classes.

Label Elements

Signal Word	WARNING
Pictograms	Hazard Statements
	H223: Flammable aerosol
	H280: Contains gas under pressure; may explode if heated
	H319: Causes serious eye irritation H336: May cause drowsiness or dizziness H317: May cause an allergic skin reaction

Section continued on the next page

844AR
ACRYLIC ESD COATING (AEROSOL)
Continued...

Prevention	Precautionary Statements
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing mist, vapors, and spray.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated clothing should not be allowed out of the workplace.
P280	Wear protective gloves and eye protection.
P264	Wash hands thoroughly after handling.
Response	Precautionary Statements
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P302 + P352	IF ON SKIN: Wash with plenty of water
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER or doctor if you feel unwell.
P362 + P364	Take off contaminated clothing and wash it before reuse.
Storage	Precautionary Statements
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].
P403	Store in a well-ventilated place.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

Section continued on the next page

844AR
ACRYLIC ESD COATING (AEROSOL)
Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Simple Asphyxiants	May displace oxygen and cause rapid suffocation.	Warning	None
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
141-78-6	ethyl acetate	50%
74-98-6	propane	13%
18282-10-5	tin oxide	13%
67-64-1	acetone	10%
75-28-5	isobutane	7%
67-63-0	propan-2-ol ^{a)}	3%
108-65-6	1-methoxy-2-propyl acetate	1%
25619-56-1	barium bis(dinonylnaphthalenesulphonate)	0.3%

a) Commonly known as isopropyl alcohol (IPA)

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>redness, irritation, pain, blurred vision</i>
Response	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Section continued on the next page

844AR
ACRYLIC ESD COATING (AEROSOL)

Continued...

IF INHALED	P304 + P340, P312
Immediate Symptoms	<i>cough, sore throat, dizziness, drowsiness, headaches, weakness, unconsciousness</i>
Response	Remove person to fresh air and keep comfortable for breathing. If feeling unwell: Call a POISON CENTRE or doctor.
IF ON SKIN	P302 + P352, P362 + P364, P313 + P333
Immediate Symptoms	<i>dry skin, mild irritation, allergic dermatitis</i>
Response	Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice or attention.
IF SWALLOWED	P301 +P330, P331
Immediate Symptoms	<i>nausea, vomiting, abdominal pain</i>
Response	Rinse mouth. Do NOT induce vomiting.

Section 5: Fire-Fighting Measures

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish. Use water spray to cool containers.
Specific Hazards	Aerosols containers may erupt with force at temperatures above 50 °C [122 °F]. The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.
Combustion Products	Produces carbon oxides (CO, CO ₂) and other toxic fumes.
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

844AR

ACRYLIC ESD COATING (AEROSOL)**Section 6: Accidental Release Measures**

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	Avoid breathing the mist, spray, and vapors. Remove or keep away all sources of extreme heat or open flames.
Environmental Precautions	Prevent spill from entering drains and waterways.
Containment Methods	Not applicable
Cleaning Methods	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.
Disposal Methods	Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention	Keep out of reach of children. Keep away from heat, hot surfaces sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing the mist, spray, and vapors. Use only outdoors or in a well-ventilated area. Contaminated clothing should not be allowed out of the workplace.
Handling	Wear protective gloves and eye protection. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse.
Storage	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F]. Store in a well-ventilated place. Store locked up.

844AR
ACRYLIC ESD COATING (AEROSOL)
Section 8: Exposure Controls/Personal Protection
Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
ethyl acetate	ACGIH	400 ppm	Not established
	U.S.A. OSHA PEL	400 ppm	Not established
	Canada AB	400 ppm	Not established
	Canada BC	150 ppm	Not established
	Canada ON	Not established	Not established
	Canada QC	400 ppm	Not established
propane	ACGIH	See footnote ^{a)}	Not established
	U.S.A. OSHA PEL	1 000 ppm	Not established
	Canada AB	1 000 ppm	Not established
	Canada BC	1 000 ppm	Not established
	Canada ON	1 000 ppm	Not established
	Canada QC	1 000 ppm	Not established
tin oxide and inorganic compounds	ACGIH	2 mg/m ³	Not established
	U.S.A. OSHA PEL	2 mg/m ³	Not established
	Canada AB	2 mg/m ³	Not established
	Canada BC	2 mg/m ³	Not established
	Canada ON	2 mg/m ³	Not established
	Canada QC	2 mg/m ³	Not established
acetone	ACGIH	500 ppm	750 ppm
	U.S.A. OSHA PEL	1 000 ppm	Not established
	Canada AB	500 ppm	750 ppm
	Canada BC	250 ppm	500 ppm
	Canada ON	500 ppm	750 ppm
	Canada QC	750 ppm	1 000 ppm
isobutane <i>alkane (C2-C4)</i> <i>aliphatic hydrocarbon gas</i>	ACGIH	See footnote ^{a)}	Not established
	U.S.A. OSHA PEL	Not established	Not established
	Canada AB	1 000 ppm	Not established
	Canada BC	1 000 ppm	Not established
	Canada ON	800 ppm	Not established
	Canada QC	Not established	Not established

Section continued on the next page

844AR
ACRYLIC ESD COATING (AEROSOL)
Continued...

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
propan-2-ol	ACGIH	200 ppm (TWA)	400 ppm
	U.S.A. OSHA PEL	400 ppm	Not established
	Canada AB	200 ppm	400 ppm
	Canada BC	200 ppm	400 ppm
	Canada ON	200 ppm	400 ppm
	Canada QC	400 ppm	500 ppm
1-methoxy-2-propanol acetate	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	Not established	Not established
	U.S.A. California ^{a)}	100 ppm	150 ppm
	Canada AB	Not established	Not established
	Canada BC	50 ppm	75 ppm
	Canada ON	50 ppm	Not established
	Canada QC	Not established	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS² database and from suppliers' SDSs were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Refer to the ACGIH Appendix F: Minimum Oxygen Content for Asphyxia TLV Basis

Engineering Controls

Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

Personal Protective Equipment

Eye protection

Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Use safety glasses with lateral protection (side shields).

Skin Protection

Wear appropriate protective clothing to prevent skin contact.

RECOMMENDATION: Use of protective gloves in butyl rubber, nitrile rubber, or other chemically resistant gloves.

Section continued on the next page

844AR
ACRYLIC ESD COATING (AEROSOL)

Respiratory Protection For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid in aerosol format	Lower Flammability Limit ^{b)}	2%
Appearance	Colorless	Upper Flammability Limit ^{b)}	11%
Odor	Ethereal	Vapor Pressure ^{b)} @20 °C	3 500 hPa [2 600 mmHg]
Odor Threshold	Not available	Vapor Density	≥1.5 (Air =1)
pH	Not available	Relative Density @25 °C	1.06
Freezing/Melting Point	Not available	Solubility in Water	Partially miscible
Initial Boiling Point ^{a)}	≥56 °C [132 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point ^{a)}	-17 °C [1.4 °F]	Auto-ignition Temperature ^{c)}	427 °C [800 °F]
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability	Flammable	Viscosity @20 °C	<20.5 mm ² /s

a) Based on acetone boiling point and closed cup value

b) Based on propellant

c) Ethyl acetate auto-ignition value, which is the lowest among the mixture components.

844AR
ACRYLIC ESD COATING (AEROSOL)
Section 10: Stability and Reactivity

Reactivity	Not available
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Temperatures above 50 °C [122 °F], open flames, and incompatible substances
Incompatibilities	Strong oxidizing agents, bases, acids
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

Section 11: Toxicological Information
Summary of Effects and Symptoms by Routes of Exposure

Eyes	Causes redness, severe irritation, pain and blurred vision.
Inhalation	May cause cough, sore throat, dizziness, drowsiness, and headaches. A severe overexposure can cause weakness and unconsciousness.
Ingestion	May cause nausea, vomiting, and abdominal pain.
Skin	May cause dry skin, mild irritation and allergic dermatitis.
Chronic	Prolonged or repeated exposure may cause skin dryness, cracking, as well as defatting the skin.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
ethyl acetate	5 620 mg/kg Rat	>20 000 µL/kg Rabbit	6 000 ppm 6 h Rat
propane	Not applicable	Not applicable	>800 000 ppm 4 h Rat
tin oxide	>20 000 mg/kg Rat	Not available	>2.04 mg/L 4 h Rat

Section continued on the next page

844AR
ACRYLIC ESD COATING (AEROSOL)
Continued...

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
acetone	5 800 mg/kg Rat	20 mL/kg Rabbit ^{a)}	16 000 ppm 6 h Rat
Isobutane	Not applicable	Not applicable	>570 000 ppm 4 h Rat
propan-2-ol	3 600 mg/kg Rat	12 800 mg/kg Rabbit	16 000 ppm 8 h Rat
1-methoxy-2-propyl acetate	8 532 mg/kg Rat	2 000 mg/kg Rat	Not available
barium bis (dinonylnaphthalenesulphonate)	Not available	Not available	Not available

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier SDSs were also consulted.

a) Supplier MSDS

Other Toxicological Effects

Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/irritation	Ethyl acetate, acetone, and propan-2-ol are known serious eye irritants.
Sensitization (allergic reactions)	Barium bis(dinonylnaphthalenesulphonate) is known as a skin sensitizer.
Carcinogenicity (risk of cancer)	None of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.
Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not met.

Section continued on the next page

844AR**ACRYLIC ESD COATING (AEROSOL)**

STOT-single exposure	Ethyl acetate, acetone, and propan-2-ol can affect the central nervous system by inhalation causing drowsiness or dizziness.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	The liquid content does not meet the aspiration hazard criteria. The mixture doesn't contain category 1 substances.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Acetone, ethyl acetate, and propan-2-ol are not classifiable as an environmental toxicant (with minimal LC50 of >100 mg/L).

- Acetone is readily biodegradable and has a minimal LC50 96 h of 5 540 mg/L for *Oncorhynchus mykiss* (rainbow trout); EC50 48 h 13 500 mg/L *Daphnia magna* (water flea).
- Ethyl acetate is readily biodegradable and has a minimal LC50 of 220 mg/L for *Pimephales promelas* (fathead minnow); LC50 24 h of 560 mg/L and EC50 24 h of 2 300 mg/L *Daphnia magna* (water flea).
- Propan-2-ol is readily biodegradable and has a minimal LC50 96 h of 9 640 mg/L for *Pimephales promelas* (fathead minnow); an EC50 24 h of 5 102 mg/L *Daphnia magna* (water flea); and an EC50 72 h of >2 000 mg/L *Desmodesmus subspicatus* (green algae).

Acute Ecotoxicity

Available toxicity data does not meet classification thresholds

Chronic Ecotoxicity

Available toxicity data does not meet classification thresholds

Biodegradability

The constituents are volatile and readily biodegradable.

Other Effects

Not available

844AR

ACRYLIC ESD COATING (AEROSOL)

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations);
USA DOT 49 CFR (Parts 100 to 185) **Regulations.**

Limited Quantity



Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Limited Quantity
Max Net Qty/Pkg =
30 kg Gross



FOR REFERENCE ONLY

UN number: UN1950

Shipping Name: AEROSOL, flammable

Class: 2.1

Packing Group: Not applicable

Marine Pollutant: No

Sea

Refer to IMDG regulations.

Limited Quantity



FOR REFERENCE ONLY

UN number: UN1950

Shipping Name: AEROSOL, flammable

Class: 2.1

Packing Group: Not applicable

Marine Pollutant: No

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

844AR

ACRYLIC ESD COATING (AEROSOL)

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL/NDSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.


USA

Other Classifications

HMIS® RATING

HEALTH:	* 2
FLAMMABILITY:	3
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains propan-2-ol (CAS# 67-63-0), which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

This product contains ethyl acetate (CAS# 141-78-6) and acetone (CAS# 67-64-1), which are subject to the CERCLA reporting requirements at the 5 000 lb (2 268 kg) threshold.

Section continued on the next page

844AR**ACRYLIC ESD COATING (AEROSOL)****TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any substances known to be listed in California.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

MSDS Prepared by	MG Chemicals' Regulatory Department
Date of Revision	03 March 2020
Supersedes	28 February 2020
Reason for Changes:	Update to the emergency phone number information.

References

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Section continued on the next page

844AR**ACRYLIC ESD COATING (AEROSOL)****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.