

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: 9310

Other Means of Identification: One-Part Epoxy General Purpose Adhesive, High Tg **Related Part #** 9310-10ML, 9310-300ML

Recommended Use and Restriction on Use

Use: general purpose epoxy adhesive

Uses Advised Against: Not for use as a spray coating

Details of Manufacturer or Importer

Manufacturer MG Chemicals 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA

MG Chemicals (Head Office) 9347-193 Street Surrey, British Columbia V4N 4E7 CANADA

***** +1-800-340-0772
 Fax +1-800-340-0773
 E-MAIL <u>support@mgchemicals.com</u>

 WEB

 www.mgchemicals.com

 Image: system
 +1-905-331-1396

 Fax
 +1-905-331-2682

 E-MAIL
 info@mgchemicals.com

E-маіц (Competent Person): <u>sds@mgchemicals.com</u>

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962** (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones



Section 2: Hazard(s) Identification

Classification of Hazardous Chemical

GHS Categories

Criteria		Category	Signal Word	Pictograms
Sensitization	Skin	1	Warning	Exclamation
Eye Irritation		2	Warning	Exclamation
Skin Irritation		2	Warning	Exclamation
Hazardous to the Aquatic Environment	Chronic	2	none	Environment

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	WARNING
Pictograms	Hazard Statements
	H317: May cause an allergic skin reaction H319: Causes serious eye irritation H315: Causes skin irritation
¥2	H411: Toxic to aquatic life with long lasting effects



Continued	
Prevention	Precautionary Statements
P102	Keep out of reach of children.
P261	Avoid breathing fumes or vapors.
P280	Wear protective gloves, protective clothing, and eye protection.
P264	Wash hands and exposed skin thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
Response	Precautionary Statements
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P302 + P352	IF ON SKIN: Wash with plenty water.
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None



Section 3: Composition/Information on Ingredients		
CAS #	Chemical Name	%(weight)
25085-99-8	bisphenol-A epoxy resin (reaction product)	77%
9003-35-4	phenol, polymer with formaldehyde	4%

Section 4: First-Aid Measures

Exposure Condition	GHS Code/Symptoms/Precautionary Statements
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	redness, serious irritation, pain
Response	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	If eye irritation persists: Get medical advice or attention.
IF ON SKIN	P302 + P352, P333 + P313, P362 + P364
Immediate	redness, irritation, allergic contact dermatitis
Response	Wash with plenty water.
	If skin irritation or rash occurs: Get medical advice or attention.
	Take off contaminated clothing and wash it before reuse.
IF INHALED	P304 + P340
Immediate Symptoms	none known or expected
Response	Remove person to fresh air and keep comfortable for breathing.
IF SWALLOWED	P301 + P330 + P331
Immediate Symptoms	none known or expected
Response	Rinse mouth. Do NOT induce vomiting.



Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
Specific Hazards	Not flammable or combustible, but burns if involved in a fire. Produces irritating smoke of unknown toxicity in fires.
	Prevent fire-fighting wash from entering waterway or sewer system.
Combustion Products	Produces carbon oxides (CO,CO ₂), nitrogen oxides, ammonia, aldehydes, phenolics and other toxic fumes.
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	Avoid breathing the fumes or vapors. Remove or keep away all sources of extreme heat or open flames.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
Containment Methods	Contain with inert and non-flammable absorbent (such as soil, sand, vermiculite).
Cleaning Methods	Collect liquid in a sealable, chemical-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash residue with a paper towel wetted with alcohol, ethyl lactate, or another suitable organic solvent; and place dirty towels in container. Use soap and water to remove the last traces of residue.
Disposal Methods	Dispose of spill waste according to Section 13.



Section 7: Handling and Storage		
Prevention	Keep out of reach of children.	
	Avoid breathing fumes or vapors. Contaminated work clothing should not be allowed out of the workplace.	
	Avoid release to the environment.	
Handling	Wear protective gloves or eye protection. Wash hands and exposed skin thoroughly after handling. Take off contaminated clothing and wash it before reuse.	
	Collect spillage.	
Storage	RECOMMENDATION: Keep in a dry and clean area, away from incompatible substances.	

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Contains no substances with occupational exposure limits.

Engineering Controls

Ventilation	General ventilation is adequate for normal use; keep overall
	exposure as low as possible.

Personal Protective Equipment

Eye protection	Wear appropriate protective eyeglasses or chemical safety goggles.
	Recommendation: Ensure that glasses have side shields for lateral protection.
Skin Protection	For likely contacts, use of protective butyl rubber, latex, neoprene, or other chemically resistant gloves.
	For incidental contacts, use nitrile, latex, neoprenee or other chemically resistant gloves.
	Section continued on the next page



Respiratory Protection For over-exposures up to 10 x OEL of vapors, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Physical State	Liquid	Lower Flammability Limit	Not available
Appearance	Amber	Upper Flammability Limit	Not available
Odor	Mild	Vapor Pressure @20 °C	Not available
Odor Threshold	Not available	Vapor Density	Not available
рН	Not available	Relative Density @25 °C	1.15
Freezing/Melting Point	Not available	Solubility in Water	Insoluble
Initial Boiling Point ^{a)}	150 °C [302 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point ^{a)}	250 °C [482 °F]	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability	Not available	Viscosity @40 °C	>20.5 mm²/s

Section 9: Physical and Chemical Properties

a) Values based on bisphenol-A epoxy resin, which is the component with the lowest value.

Page **7** of **15** Date: 04 March 2020 / Ver. 1.01



Section 10: Stability and Reactivity

Reactivity	Reacts exothermically with amines.
Chemical Stability	Chemically stable at normal temperatures and pressures.
Conditions to Avoid	Avoid ignition sources, open flames, and incompatible substances. Do not use in away that forms mist or aerosolizes the product.
Incompatibilities	Avoid oxidizing agents, acids, bases and peroxides.
Polymerization	Will not occur by itself. Masses of more than one pound (0.5 kg) of product plus an aliphatic amine will cause irreversible polymerization with considerable heat buildup.
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

Section 11: Toxicological Information

Summary of Effects and Symptoms by Routes of Exposure

Eyes	May cause redness, serious irritation, or pain.
Skin	Causes skin redness, irritation, dry skin, or allergic contact dermatitis.
Inhalation	None known or expected.
Ingestion	None known or expected.
Chronic	Prolonged and repeated exposure may lead to skin sensitization.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50	LD50	LC50
	oral	dermal	inhalation
bisphenol-A epoxy resin	>15 000 mg/kg	23 000 mg/kg	Not
(reaction product)	Rat ^{a)}	Rabbit ^{a)}	established
phenol, polymer with	>5 000 mg/kg	>2 000 mg/kg	Not
formaldehyde	Rat ^{a)}	Rat ^{a)}	established

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier SDS were also consulted.

a) Supplier SDS



Other Toxicological Effects

Skin corrosion/irritation	Bisphenol-A is a known skin irritant.	
Serious eye damage/irritation	Phenol, polymer with formaldehyde and bisphenol-A causes serious eye irritation.	
Sensitization (allergic reactions)	May cause skin sensitization based on animal studies due to the epoxy components.	
Carcinogenicity (risk of cancer)	Not classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.	
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.	
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.	
Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not met.	
STOT-single exposure	Based on available data, the classification criteria are not met.	
STOT-repeated exposure	Based on available data, the classification criteria are not met.	
Aspiration hazard	There is no category 1 components, and the kinematic viscosity is >20.5 mm ² /s at 40 °C.	

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<u>http://echa.europa.eu</u>), and other reliable sources.

In Europe, similar epoxy resin mixtures with CAS# 25085-99-8 are generally classified as chronic category 2 marine pollutant due to LC50 96 h of >1 mg/L but \leq 10 mg/L.

Based on available data, phenol, polymer with formaldehyde is not classified as an environmental hazard according to GHS criteria.

Acute Ecotoxicity

Available toxicity data does not meet classification thresholds.



Chronic Ecotoxicity

Category 2 Toxic to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

Biodegradability

Not readily biodegradable

Bioaccumulation

Not available

Other Effects

Not available

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.



Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Sizes under 450 L	
9310-10ML, 9310-300ML	FOR REFERENCE ONLY
NOT REGULATED in TDG	UN number: UN3082
per Special Provisions 99	Shipping Name: ENVIRONMENTALLY
Sizes 5 L and under	HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(bisphenol-A epoxy resin (reaction product))
NOT REGULATED in 49 CFR	Class: 9
per exception 171.4 (c)(2)	Packing Group: III
	Marine Pollutant: Yes
1	

Special Provision 99 (2): These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

Air

Refer to ICAO-IATA regulations.

Sizes 5 L and under 9310-10ML, 9310-300ML **NOT REGULATED** On air waybill, write: "Not Restricted, as per Special Provisions A197"

Special Provision A197: These substances when transported in single or combination packagings containing net quantity per single or inner packaging of less than 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Section continued on the next page

Page **11** of **15** Date: 04 March 2020 / Ver. 1.01



Sea

Refer to IMDG regulations.

Sizes 5 L and under 9310-10ML, 9310-300ML NOT REGULATED per 2.10.2.7

2.10.2.7: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provision of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this Code relevant to any additional hazards continue to apply.

Note: Shipper must be appropriately <u>trained and certified</u> before involvement with the transport of dangerous goods.

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.



USA

Other Classifications

HMIS® RATING

HEALTH:	*	2
FLAMMABILITY:		1
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend: 0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain substances, which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, June 06, 2014 revision, USA).

This product does not contain any of the listed substances.

Europe

RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.



Section	16: Other	Information	
---------	-----------	--------------------	--

SDS Prepared by	Regulatory Department

Date of Review 04 March 2020

Supersedes 02 February 2017

Reason for Changes: Change to emergency phone numbers and RoHS declaration.

Reference

1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH American Conference of Governmental Industrial Hygienists (USA)

- EC50 Half maximal effective concentration
- EL50 Half maximal effective loading
- IARC International Agency for Research on Cancer
- NOELR No observable effect loading ratio
- NTP National Toxicology Program
- GHS Globally Harmonized System of Classification of Labeling of Chemicals
- LC50 Lethal Concentration 50%
- LCLo Lowest published lethal concentration
- LD50 Lethal Dose 50%
- OEL Occupational Exposure Limit
- PEL Permissible Exposure Limit
- SDS Safety Data Sheet
- STEL Short-Term Exposure Limit
- TCLo Lowest published toxic concentration
- TWA Time Weighted Average
- VOC Volatile Organic Content



Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at <u>www.mgchemicals.com</u>.

Email: support@mgchemicals.com

Mailing Addresses	Manufacturing & Support	Head Office
	1210 Corporate Drive	9347–193rd Street
	Burlington, Ontario, Canada	Surrey, British Columbia, Canada
	L7L 5R6	V4N 4E7+

Disclaimer This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.