

XS1177-ZE

TOUCH UP SPRAY PAINT—BROWN METALLIC (AEROSOL)

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: XS1177-ZE**Other Product Identifier:** Touch Up Spray Paint—Brown Metallic (Aerosol)**Related Part #** XS1177-ZE-140G, XS1177-ZE-340G

Recommended Use and Restriction on Use

Use: Touch up spray paint**Uses Advised Against:** Not available

Details of Manufacturer or Importer

ManufacturerMG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADAMG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA**TEL** +1-800-340-0772**TEL** +1-905-331-1396**FAX** +1-800-340-0773**FAX** +1-905-331-2682**E-MAIL** support@mgchemicals.com**E-MAIL** info@mgchemicals.com**WEB** www.mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number



For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**
(Service access code: 335388)**For emergencies involving the transport of dangerous goods;** 24/7 service
CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

Section 2: Hazard(s) Identification
Classification of Hazardous Chemical
GHS Categories

Criteria	Category	Signal Word	Pictograms
Aspiration Hazard	1	Danger	Health
Specific Target Organ Toxicity Repeated Exposure	2	Warning	Health
Carcinogenicity	2	Warning	Health
Reproductive Toxicity	2	Warning	Health
Flammable Aerosol	2	Warning	Flame
Gas Under Pressure	Liquefied Gas	Warning	Gas Cylinder
Skin Irritation	2	Warning	Exclamation
Eye Irritation	2	Warning	Exclamation
Specific Target Organ Toxicity Single Exposure	3	Warning	Exclamation
Hazardous to the Aquatic Environment Acute	3	<i>none</i>	<i>none</i>



Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H304: May be fatal if swallowed and enters airways H373: May cause damage to organs (central nervous system, inner ear, liver, kidney) through prolonged or repeated exposure H351: Suspected of causing cancer H361: Suspected of damaging fertility or the unborn child
	H223: Flammable aerosol

Section continued on the next page

XS1177-ZE
TOUCH UP SPRAY PAINT—BROWN METALLIC (AEROSOL)
Continued...

Pictograms	Hazard Statements
	H229: Pressurized container: may burst if heated
	H315: Causes skin irritation H319: Causes serious eye irritation H336: May cause drowsiness or dizziness
<i>No Symbol Mandated</i>	H402: Harmful to aquatic life
Prevention	Precautionary Statements
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe mist, vapors, and spray.
P271	Use only outdoors or in a well-ventilated area.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves and eye protection or face protection.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.

Section continued on the next page

XS1177-ZE
TOUCH UP SPRAY PAINT—BROWN METALLIC (AEROSOL)
Continued...

Response	Precautionary Statements
P308 + P313	IF exposed or concerned: Get medical advice or attention.
P301 + P310, P331	IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.
P302 + P352	IF ON SKIN: Wash with plenty water.
P332 + P313	If skin irritation occurs: Get medical advice or attention.
P304 + P340, P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P314	Get medical advice or attention if you feel unwell.
P362 + P364	Take off contaminated clothing and wash it before reuse.
Storage	Precautionary Statements
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].
P403	Store in well-ventilated place.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents and container in accordance to local, regional, national, and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Simple Asphyxiants	May displace oxygen and cause rapid suffocation.	Warning	None
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
29118-24-9	trans-1,3,3,3-tetrafluoroprop-1-ene	45%
67-64-1	acetone	17%
108-88-3	toluene	10%
110-19-0	isobutyl acetate	3%
110-43-0	heptan-2-one	3%
108-65-6	1-methoxy-2-propanol acetate	3%
64-17-5	ethanol	3%
141-78-6	ethyl acetate	2%
1330-20-7	xylene	0.7%
8052-41-3	Stoddard solvent	0.7%
1333-86-4	carbon black	0.5%
100-41-4	ethylbenzene	0.3%
13463-67-7	titanium dioxide	0.2%
7429-90-5	aluminum powder	0.2%

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
IF SWALLOWED	P301 + P310, P331, P308 + P313
Immediate Symptoms	<i>nausea, sore throat, diarrhea, drowsiness, dizziness</i>
Response	IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. IF exposed or concerned: Get medical advice or attention.

Section continued on the next page

XS1177-ZE
TOUCH UP SPRAY PAINT—BROWN METALLIC (AEROSOL)
Continued...

IF INHALED	P304 + P340, P312, P308 + P313
Immediate Symptoms	<i>drowsiness, dizziness, cough, headaches, nausea, unconsciousness</i>
Response	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell. If exposed or concerned: Get medical advice or attention.
IF ON SKIN	P302 + P352, P332 + P313, P314
Immediate Symptoms	<i>dry skin, redness, irritation</i>
Response	Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. Get medical advice or attention if you feel unwell.
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>irritation, redness, pain, blurred vision, possible cornea damage</i>
Response	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Section 5: Fire-Fighting Measures

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish. Use water spray to cool containers.
Specific Hazards	Aerosols containers may erupt with force at temperatures above 50 °C [122 °F]. Produces irritating and toxic fumes in fires or in contact with hot surfaces. The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.
Combustion Products	Produces carbon oxides (CO, CO ₂), halogenated compounds, and hydrogen fluorides.
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	Do not breathe the mist, spray, and vapors. Remove or keep away all sources of extreme heat or open flames.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
Containment Methods	Not applicable
Cleaning Methods	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.
Disposal Methods	Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention	Keep out of reach of children. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe mist, vapors, and spray. Use only outdoors or in a well-ventilated area. Avoid release to the environment.
Handling	Wear protective gloves and eye protection or face protection. Wash hands thoroughly after handling.
Storage	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F]. Store in well-ventilated place. Store locked up.

Section 8: Exposure Controls/Personal Protection
Substances with Occupational Exposure Limit Values

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
trans-1,3,3,3-tetrafluoroprop-1-ene	MG Chemicals ^{a)} ACGIH U.S.A. OSHA PEL Canada	800 ppm Not established Not established Not established	Not established Not established Not established Not established
acetone	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	500 ppm 1 000 ppm 500 ppm 250 ppm 500 ppm 750 ppm	750 ppm Not established 750 ppm 500 ppm 750 ppm 1 000 ppm
toluene	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	20 ppm 200 ppm 50 ppm 20 ppm 20 ppm 100 ppm	Not established 300 ppm Not established Not established Not established 150 ppm
isobutyl acetate	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	150 ppm 150 ppm 150 ppm 150 ppm 150 ppm 150 ppm	Not established Not established Not established Not established Not established Not established
heptan-2-one	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	50 ppm 100 ppm 50 ppm 50 ppm 25 ppm 50 ppm	Not established Not established Not established Not established Not established Not established
1-methoxy-2-propanol acetate	ACGIH U.S.A. OSHA WEEL Canada AB Canada BC Canada ON Canada QC	Not established 50 ppm Not established 50 ppm 50 ppm Not established	Not established Not established Not established 75 ppm Not established Not established

a) Manufacture's recommended limit.

Section continued on the next page

XS1177-ZE
TOUCH UP SPRAY PAINT—BROWN METALLIC (AEROSOL)
Continued...

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
ethanol	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	Not established 1 000 ppm 1 000 ppm Not established Not established 1 000 ppm	1 000 ppm Not established Not established 1 000 ppm 1 000 ppm Not established
ethyl acetate	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	400 ppm 400 ppm 400 ppm 150 ppm Not established 400 ppm	Not established Not established Not established Not established Not established Not established
xylene	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	100 ppm 100 ppm 100 ppm 100 ppm 100 ppm 100 ppm	150 ppm Not established 150 ppm 150 ppm 150 ppm 150 ppm
Stoddard solvent	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	100 ppm 500 ppm 100 ppm 290 mg/m ³ 100 ppm 100 ppm	Not established Not established Not established 580 mg/m ³ Not established Not established
carbon black	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	3.5 mg/m ³ 3.5 mg/m ³ 3.5 mg/m ³ 3 mg/m ³ 3.5 mg/m ³ 3.5 mg/m ³	Not established Not established Not established Not established Not established Not established
ethylbenzene	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	20 ppm 100 ppm 100 ppm 20 ppm (2B) 100 ppm 100 ppm	Not established Not established 125 ppm Not established 125 ppm 125 ppm
titanium dioxide	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	10 mg/m ³ 15 mg/m ³ 10 mg/m ³ 10 mg/m ³ 10 mg/m ³ 10 mg/m ³	Not established Not established Not established Not established Not established Not established

Section continued on the next page

XS1177-ZE

TOUCH UP SPRAY PAINT—BROWN METALLIC (AEROSOL)

Continued...

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
aluminum powder	ACGIH ^{b)} U.S.A. OSHA PEL ^{b)} Canada AB ^{c)} Canada BC ^{b)} Canada ON ^{b)} Canada QC ^{c)}	10 mg/m ³ 15 mg/m ³ 5 mg/m ³ 1 mg/m ³ 1 mg/m ³ 5 mg/m ³	Not established Not established Not established Not established Not established Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS database² and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

b) Respirable

c) Pyro powders

(2B) Carcinogen

Engineering Controls

Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

Personal Protective Equipment

Eye protection

Wear appropriate protective eyeglasses or chemical safety goggles.

Recommendation: Ensure that glasses have side shields for lateral protection.

Skin Protection

For likely contacts, use of protective butyl rubber, fluorinated rubber, or other chemically resistant gloves.

For incidental contacts, use nitrile, neoprene, or other chemically resistant gloves.

Section continued on the next page

XS1177-ZE
TOUCH UP SPRAY PAINT—BROWN METALLIC (AEROSOL)

Respiratory Protection For over-exposures up to 10 x OEL of mist, vapors, and spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid, in aerosol format	Lower Flammability Limit ^{a)}	1%
Appearance	Brown metallic	Upper Flammability Limit ^{a)}	13%
Odor	Ethereal	Vapor Pressure @20 °C ^{b)}	~131 hPa [~98 mmHg]
Odor Threshold	Not available	Vapor Density	>2 (Air =1)
pH	Not available	Relative Density @25 °C	0.92
Freezing/Melting Point	Not available	Solubility in Water	Partially soluble
Initial Boiling Point ^{a)}	≥56 °C [≥132 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point ^{a)}	-17 °C [-1.4 °F]	Auto-ignition Temperature ^{c)}	≥330 °C [≥626 °F]
Evaporation Rate	fast	Decomposition Temperature	Not available
Flammability	Not available	Viscosity @40 °C	<20.5 mm ² /s

a) Values based on acetone component.

b) Calculated based on volatile liquid components.

c) Values based on 2-methoxy-1-methylethyl acetate

Section 10: Stability and Reactivity

Reactivity	Not available
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Temperatures above 50 °C [122 °F], open flames, and incompatible substances
Incompatibilities	Oxidizing agents, strong acids, strong bases, alkali, alkali metals, peroxides, halogens, vinyl chloride, and iodine pentafluoride
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5

Section 11: Toxicological Information**Summary of Effects and Symptoms by Routes of Exposure**

Ingestion	May cause nausea, sore throat, and diarrhea (see inhalation symptoms).
Inhalation	May cause drowsiness, dizziness, cough, headaches, nausea, or unconsciousness.
Eyes	May cause redness and severe irritation
Skin	May cause skin redness, irritation, and dry skin.
Chronic	Prolonged or repeated exposure may cause skin dryness, cracking, as well as defatting the skin. Ingestion or inhalation of paint material, mist, or vapor during pregnancy may increase the chances fetal death and developmental defects.

Section continued on the next page

XS1177-ZE
TOUCH UP SPRAY PAINT—BROWN METALLIC (AEROSOL)
Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
trans-1,3,3,3-tetrafluoroprop-1-ene	Not available	Not available	>207 000 ppm 4 h Rat ^{a)}
acetone	5 800 mg/kg Rat	20 mL/kg Rabbit ^{a)}	16 000 ppm 6 h Rat
toluene	636 mg/kg Rat	12 124 mg/kg Rabbit	49 g/m ³ 4 h Rat
isobutyl acetate	13 400 mg/kg Rat	>17 400 mg/kg Rabbit	>13.24 mg/L 6 h Rat
heptan-2-one	1 670 mg/kg Rat	12 600 µL/kg Rabbit	Not available
1-methoxy-2-propanol acetate	8 532 mg/kg Rat	>5 g/kg Rabbit	Not available
ethanol	7 060 mg/kg Rat	Not available	20 000 ppm 10 h Rat
ethyl acetate	5 620 mg/kg Rat	>20 000 µL/kg Rabbit	45 g/m ³ 2 h Mouse
xylene	4 350 mg/kg Rat	>1 700 mg/kg Rabbit	5 000 ppm 4 h Rat
Stoddard solvent	>5 000 mg/kg Rat	>3 000 mg/kg Rat	14 000 ppm 8 h Rat
carbon black	>15 g/kg Rat	>3 g/kg Rabbit ^{b)}	Not available
ethylbenzene	3 500 mg/kg Rat	>5 000 mg/kg Rabbit	35 500 mg/m ³ 2 h Mouse
titanium dioxide	5 000 mg/kg Rat	Not available	5 g/L 4 h Rat

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier (M)SDSs were also consulted.

a) According to supplier safety data sheet.

b) Lethal dose

Other Toxicological Effects
Skin corrosion/irritation

Toluene and xylenes causes skin irritation based on Draize tests on animals.

Section continued on the next page

Page **13** of **20**

Date: 02 March 2020 / Ver. 1.03

XS1177-ZE**TOUCH UP SPRAY PAINT—BROWN METALLIC (AEROSOL)****Serious eye damage/irritation**

Acetone, ethanol, and ethyl acetate are known serious eye irritants.

Sensitization
(allergic reactions)

Based on available data, the classification criteria are not met.

Carcinogenicity
(risk of cancer)

Carbon black and titanium dioxide are possibly carcinogenic by airborne routes of exposures under WHMIS.

Carbon Black [1333-86-4]

IARC Group 2B: Possibly carcinogenic to humans

ACGIH A3: Confirmed Animal Carcinogen with Unknown Relevance to Humans

CA Prop 65: Listed as a carcinogen (airborne, as unbound particles of respirable size)

NTP: Not listed

Titanium Dioxide [13463-67-7]

IARC Group 2B: Possibly carcinogenic to humans

ACGIH A4: Not classified as a human carcinogen

CA Prop 65: Listed as a carcinogen (airborne, as unbound particles of respirable size)

NTP: Not listed

Ethanol [64-17-5]

IARC Group 1: Carcinogenic to human when consumed as beverage.

ACGIH A3: Confirmed animal carcinogen with unknown relevance to humans

CA Prop 65: Listed as a carcinogen when consumed as a beverage

NTP: Not listed

Ethylbenzene [100-41-4]

IARC Group 2B: Possibly carcinogenic to humans

ACGIH A3: Confirmed animal carcinogen with unknown relevance to humans

CA Prop 65: Listed as a carcinogen

NTP: Not listed

Section continued on the next page

XS1177-ZE**TOUCH UP SPRAY PAINT—BROWN METALLIC (AEROSOL)****Mutagenicity**

(risk of heritable genetic effects)

Based on available data, the classification criteria are not met.

Reproductive Toxicity

(risk to sex functions)

At high doses, spermatogenesis was observed in male rat by inhalation of toluene.

Teratogenicity (risk of fetus malformation)

Fetotoxicity is observed in animal studies for inhalation and oral exposures for toluene. Extreme consumption of ethanol also presents risks for the newborn.

STOT-single exposure

Acetone, toluene, 1-methoxy-2-propanol acetate, isobutyl acetate, heptan-2-one, ethyl acetate, and xylenes can affect the central nervous system by inhalation causing drowsiness or dizziness.

STOT-repeated exposure

Contains Stoddard solvent, which is classified by European authorities as a Cat 1 STOT RE toxicant with respect to the central nervous system.

Contains toluene, which is a Cat 2 STOT repeated exposure hazard for the central nervous system and cochlear systems.

Toluene and xylenes are ototoxic chemicals according to rat studies: inhalation exposure in the presence of noise may lead to cochlear impairment.

Aspiration hazard

The liquid content is classified as Cat 1 aspiration hazards. It is composed of >10% Cat 1 substances, and the kinematic viscosity is <20.5 mm²/s at 40 °C.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Acetone is not classifiable as an aquatic toxicant. It has a minimal LC50 96 h of 5 540 mg/L for *Oncorhynchus mykiss* (rainbow trout); EC50 48 h of 13 500 mg/L *Daphnia magna* (water flea).

Toluene is an acute category 2 aquatic toxicant. It has a minimal LC50 96 h of 7.63 mg/L for *Oncorhynchus mykiss* (rainbow trout); EC50 24 h of 8.9 mg/L *Daphnia magna* (water flea); and EC50 24 h of 10 mg/L *Pseudokirchneriella subcapitata* (green algae).

The 1-methoxy-2-propanol acetate component is an acute category 3 aquatic toxicant. It has a minimal LC50 96 h of ≥100 mg/L *Oncorhynchus mykiss* (rainbow trout).

Section continued on the next page

XS1177-ZE**TOUCH UP SPRAY PAINT—BROWN METALLIC (AEROSOL)**

Ethylbenzene is acutely toxic to the aquatic environment of category 2 with minimal LC50 96 h of 4.2 mg/L for *Oncorhynchus mykiss* (rainbow trout); EC50 48 h 2.9 mg/L *Daphnia magna* (water flea).

The xylene isomers mixture is acutely toxic to the aquatic environment of category 2 with a minimal LC50 96 h of 2.5 mg/L for *Oncorhynchus mykiss* (rainbow trout).

Isobutyl acetate, heptan-2-one, ethanol, ethyl acetate, titanium dioxide, carbon black, and aluminum powder are not classifiable as an environmental toxicant with minimal LC50 of >100 mg/L.

- Heptan-2-one has a minimal LC50 96 h of 126 mg/L for *Pimephales promelas* (fathead minnow).
- Ethanol is biodegradable and has minimal LC50 of 12 000 mg/L 96 h for *Oncorhynchus mykiss* (rainbow trout) and 5 770 mg/L for *Pimephales promelas* (fathead minnow); and an LC50 24 h of 5 012 mg/L for *Ceriodaphnia* spp (water flea).
- Ethyl acetate is biodegradable and has a minimal LC50 96 h of 220 mg/L for *Pimephales promelas* (fathead minnow); LC50 24 h of 560 mg/L and an EC50 48 h of 2 300 mg/L for *Daphnia magna* (water flea); and an EC50 72 h of 1 800 mg/L for *Selenastrum* (green algae).

Acute Ecotoxicity

Harmful to aquatic life

Avoid release to the environment.

Chronic Ecotoxicity

Available toxicity data does not meet classification thresholds.

Biodegradability

Expected to be biodegradable. The volatile solvent constituents will oxidize rapidly in air by photochemical reaction.

Other Effects

Actual VOC (Volatile Organic Compounds) content according to the US (EPA) and Canadian (CEPA) authorities.

Actual volatile organic compound (VOC) content = 26% [267 g/L]

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

XS1177-ZE

TOUCH UP SPRAY PAINT—BROWN METALLIC (AEROSOL)

Section 14: Transport Information

Ground

Refer to TDG (Canadian Transportation of Dangerous Goods regulations) and **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Limited Quantity



Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Limited Quantity
Max Net Qty/Pkg =
30 kg Gross



UN number: UN1950
Shipping Name:
AEROSOLS, flammable
Class: 2.1
Packing Group: Not applicable
Marine Pollutant: No

Sea

Refer to IMDG regulations.

Limited Quantity



UN number: UN1950
Shipping Name:
AEROSOLS, flammable
Class: 2.1
Packing Group: Not applicable
Marine Pollutant: No

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.


USA

Other Classifications

HMIS® RATING

HEALTH:	* 2
FLAMMABILITY:	3
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product contains toluene, xylene, and ethylbenzene which are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains ethylbenzene (CAS # 100-41-4; reportable quantity = 1 000 lb), toluene (CAS# 108-88-3; reportable quantity = 1 000 lb), and xylene (CAS# 1330-20-7, reportable quantity = 100 lb), which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

This product contains acetone (CAS# 67-64-1), isobutyl acetate (CAS# 110-19-0) and ethyl acetate (CAS# 141-78-6), which are subject to the CERCLA reporting requirements at the 5 000 lb (2 268 kg) threshold.

Section continued on the next page

XS1177-ZE**TOUCH UP SPRAY PAINT—BROWN METALLIC (AEROSOL)****TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product contains toluene, which is listed as reproductively toxic in California.

This product contains ethylbenzene, which is listed as a carcinogen in California.

This product contains ethanol, which is listed as reproductively toxic and as a carcinogen when in an alcoholic beverage.

This product contains carbon black and titanium dioxide, which is listed as a carcinogenic substance when airborne, as unbound particles of respirable size.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

SDS Prepared by	Regulatory Department
Date of Review	02 March 2020
Supersedes	18 May 2018
Reason for Changes:	Change to classification.

Reference

1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Section continued on the next page

XS1177-ZE**TOUCH UP SPRAY PAINT—BROWN METALLIC (AEROSOL)****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347–193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.