

XS1952-ZE

TOUCH UP SPRAY PAINT—HIGH HIDE FAST DRY (AEROSOL)

# Safety Data Sheet

## Section 1: Identification

### Product Identifier and Other Means of Identification

**Product Identifier:** XS1952-ZE**Other Product Identifier:** Touch Up Spray Paint—High Hide Fast Dry (Aerosol)**Related Part #** XS1952-ZE-140G, XS1952-ZE-340G

### Recommended Use and Restriction on Use

**Use:** Touch up spray paint**Uses Advised Against:** Not available

### Details of Manufacturer or Importer

**Manufacturer**MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADAMG Chemicals (Head Office)  
9347-193 Street  
Surrey, British Columbia V4N 4E7  
CANADA**TEL** +1-800-340-0772**TEL** +1-905-331-1396**FAX** +1-800-340-0773**FAX** +1-905-331-2682**E-MAIL** [support@mgchemicals.com](mailto:support@mgchemicals.com)**E-MAIL** [info@mgchemicals.com](mailto:info@mgchemicals.com)**WEB** [www.mgchemicals.com](http://www.mgchemicals.com)**E-MAIL** (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)

### Emergency Phone Number



**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents)  
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**  
(Service access code: 335388)**For emergencies involving the transport of dangerous goods;** 24/7 service  
CANADA—Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones

**Section 2: Hazard(s) Identification**
**Classification of Hazardous Chemical**
**GHS Categories**

Criteria	Category	Signal Word	Pictograms
Aspiration Hazard	1	Danger	Health
Reproductive Toxicity	1B	Danger	Health
Specific Target Organ Toxicity    Repeated Exposure	2	Warning	Health
Carcinogenicity	2	Warning	Health
Flammable Aerosol	2	Warning	Flame
Gas Under Pressure	Liquefied Gas	Warning	Gas Cylinder
Skin Irritation	2	Warning	Exclamation
Eye Irritation	2	Warning	Exclamation
Specific Target Organ Toxicity    Single Exposure	3	Warning	Exclamation
Hazardous to the Aquatic Environment    Chronic	3	<i>none</i>	<i>none</i>



*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

**Label Elements**

<b>Signal Word</b>	<b>DANGER</b>
<b>Pictograms</b>	<b>Hazard Statements</b>
	H304: May be fatal if swallowed and enters airways H360: May damage fertility or the unborn child H373: May cause damage to organs (central nervous system, inner ear, liver, kidney) through prolonged or repeated exposure H351: Suspected of causing cancer
	H223: Flammable aerosol

*Section continued on the next page*

**XS1952-ZE**
**TOUCH UP SPRAY PAINT—HIGH HIDE FAST DRY (AEROSOL)**
*Continued...*

<b>Pictograms</b>	<b>Hazard Statements</b>
	H229: Pressurized container: may burst if heated
	H315: Causes skin irritation H319: Causes serious eye irritation H336: May cause drowsiness or dizziness
No Symbol Mandated	H412: Harmful to aquatic life with long lasting effects
<b>Prevention</b>	<b>Precautionary Statements</b>
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe mist, vapors, and spray.
P271	Use only outdoors or in a well-ventilated area.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves and eye protection or face protection.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.

*Section continued on the next page*

**XS1952-ZE**
**TOUCH UP SPRAY PAINT—HIGH HIDE FAST DRY (AEROSOL)**
*Continued...*

<b>Response</b>	<b>Precautionary Statements</b>
P308 + P313	IF exposed or concerned: Get medical advice or attention.
P301 + P310, P331	IF SWALLOWED: Immediately call a POISON CENTER. Do NOT induce vomiting.
P302 + P352	IF ON SKIN: Wash with plenty water.
P332 + P313	If skin irritation occurs: Get medical advice or attention.
P304 + P340, P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P314	Get medical advice or attention if you feel unwell.
P362 + P364	Take off contaminated clothing and wash it before reuse.
<b>Storage</b>	<b>Precautionary Statements</b>
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].
P403	Store in well-ventilated place.
P405	Store locked up.
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of contents and container in accordance to local, regional, national, and international regulations.

**Hazards Not Otherwise Classified**

<b>Other Criteria</b>	<b>Hazard Statements/Precautionary Statement</b>	<b>Signal Word</b>	<b>Pictograms</b>
Simple Asphyxiants	May displace oxygen and cause rapid suffocation.	Warning	None
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

**Section 3: Composition/Information on Ingredients**

<b>CAS #</b>	<b>Chemical Name</b>	<b>%(weight)</b>
29118-24-9	trans-1,3,3,3-tetrafluoroprop-1-ene	47%
67-64-1	Acetone	25%
108-88-3	toluene	7%
13463-67-7	titanium dioxide	7%
110-19-0	isobutyl acetate	3%
110-43-0	heptan-2-one	3%
64-17-5	ethanol	3%
108-65-6	1-methoxy-2-propanol acetate	2%
141-78-6	ethyl acetate	1%
67-63-0	propan-2-ol	1%
85-68-7	benzyl butyl phthalate	1%
1330-20-7	xylene	1%
100-41-4	ethylbenzene	0.4%

**Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
<b>IF SWALLOWED</b>	P301 + P310, P331, P308 + P313
<b>Immediate Symptoms</b>	<i>nausea, sore throat, diarrhea, drowsiness, dizziness</i>
<b>Response</b>	IF SWALLOWED: Immediately call a POISON CENTER or doctor.  Do NOT induce vomiting.  IF exposed or concerned: Get medical advice or attention.
<b>IF INHALED</b>	P304 + P340, P312, P308 + P313
<b>Immediate Symptoms</b>	<i>drowsiness, dizziness, cough, headaches, nausea, unconsciousness</i>
<b>Response</b>	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell.  IF exposed or concerned: Get medical advice or attention.

*Section continued on the next page*

**XS1952-ZE TOUCH UP SPRAY PAINT—HIGH HIDE FAST DRY (AEROSOL)**

*Continued...*

<b>IF IN EYES</b>	P305 + P351 + P338, P337 + P313
<b>Immediate Symptoms</b>	<i>irritation, redness, pain, blurred vision, possible cornea damage</i>
<b>Response</b>	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  If eye irritation persists: Get medical advice or attention.
<b>IF ON SKIN</b>	P302 + P352, P332 + P313, P314
<b>Immediate Symptoms</b>	<i>dry skin, redness, irritation</i>
<b>Response</b>	Wash with plenty of water.  If skin irritation occurs: Get medical advice or attention.  Get medical advice or attention if you feel unwell.

**Section 5: Fire-Fighting Measures**

<b>Extinguishing Media</b>	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.  Use water spray to cool containers.
<b>Specific Hazards</b>	Aerosols containers may erupt with force at temperatures above 50 °C [122 °F].  Produces irritating and toxic fumes in fires or in contact with hot surfaces.  The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> ), halogenated compounds, and hydrogen fluorides.
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

**Section 6: Accidental Release Measures**

<b>Personal Protection</b>	See personal protection recommendations in Section 8.
<b>Precautions for Response</b>	Do not breathe the mist, spray, or vapors. Remove or keep away all sources of extreme heat or open flames.
<b>Environmental Precautions</b>	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
<b>Containment Methods</b>	Not applicable
<b>Cleaning Methods</b>	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.
<b>Disposal Methods</b>	Dispose of spill waste according to Section 13.

**Section 7: Handling and Storage**

<b>Prevention</b>	Keep out of reach of children. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe mist, vapors, and spray. Use only outdoors or in a well-ventilated area. Avoid release to the environment.
<b>Handling</b>	Wear protective gloves and eye protection or face protection. Wash hands thoroughly after handling.
<b>Storage</b>	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F]. Store in well-ventilated place. Store locked up.

**Section 8: Exposure Controls/Personal Protection**
**Substances with Occupational Exposure Limit Values**

<b>Chemical Name</b>	<b>Country/ Provinces</b>	<b>Long Term Exposure Limits (PEL)</b>	<b>Short Term Exposure Limits (STEL)</b>
trans-1,3,3,3-tetrafluoroprop-1-ene	MG Chemicals <sup>a)</sup> ACGIH U.S.A. OSHA PEL Canada	800 ppm Not established Not established Not established	Not established Not established Not established Not established
acetone	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	500 ppm 1 000 ppm 500 ppm 250 ppm 500 ppm 750 ppm	750 ppm Not established 750 ppm 500 ppm 750 ppm 1 000 ppm
toluene	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	20 ppm 200 ppm 50 ppm 20 ppm 20 ppm 100 ppm	Not established 300 ppm Not established Not established Not established 150 ppm
titanium dioxide	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	10 mg/m <sup>3</sup> 15 mg/m <sup>3</sup> 10 mg/m <sup>3</sup> 10 mg/m <sup>3</sup> 10 mg/m <sup>3</sup> 10 mg/m <sup>3</sup>	Not established Not established Not established Not established Not established Not established
isobutyl acetate	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	150 ppm 150 ppm 150 ppm 150 ppm 150 ppm 150 ppm	Not established Not established Not established Not established Not established Not established
heptan-2-one	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	50 ppm 100 ppm 50 ppm 50 ppm 25 ppm 50 ppm	Not established Not established Not established Not established Not established Not established

a) Manufacture's recommended limit.

*Section continued on the next page*



**XS1952-ZE**
**TOUCH UP SPRAY PAINT—HIGH HIDE FAST DRY (AEROSOL)**
*Continued...*

<b>Chemical Name</b>	<b>Country/ Provinces</b>	<b>Long Term Exposure Limits (PEL)</b>	<b>Short Term Exposure Limits (STEL)</b>
ethanol	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	Not established 1 000 ppm 1 000 ppm Not established Not established 1 000 ppm	1 000 ppm Not established Not established 1 000 ppm 1 000 ppm Not established
1-methoxy-2-propanol acetate	ACGIH U.S.A. OSHA WEEL Canada AB Canada BC Canada ON Canada QC	Not established 50 ppm Not established 50 ppm 50 ppm Not established	Not established Not established Not established 75 ppm Not established Not established
ethyl acetate	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	400 ppm 400 ppm 400 ppm 150 ppm Not established 400 ppm	Not established Not established Not established Not established Not established Not established
propan-2-ol	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	200 ppm 400 ppm 200 ppm 200 ppm 200 ppm 400 ppm	400 ppm Not established 400 ppm 400 ppm 400 ppm 500 ppm
xylene	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	100 ppm 100 ppm 100 ppm 100 ppm 100 ppm 100 ppm	150 ppm Not established 150 ppm 150 ppm 150 ppm 150 ppm
ethylbenzene	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	20 ppm 100 ppm 100 ppm 20 ppm (2B) 100 ppm 100 ppm	Not established Not established 125 ppm Not established 125 ppm 125 ppm

*Note:* Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS database<sup>2</sup> and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

(2B) Carcinogen

*Section continued on the next page*

## XS1952-ZE

## TOUCH UP SPRAY PAINT—HIGH HIDE FAST DRY (AEROSOL)

**Engineering Controls**

**Ventilation** Keep airborne concentrations below the occupational exposure limits (OEL).

**Personal Protective Equipment**

**Eye protection** Wear appropriate protective eyeglasses or chemical safety goggles.

**Recommendation:** Ensure that glasses have side shields for lateral protection.

**Skin Protection** For likely contacts, use of protective butyl rubber, fluorinated rubber, or other chemically resistant gloves.

For incidental contacts, use nitrile, neoprene, or other chemically resistant gloves.

**Respiratory Protection** For over-exposures up to 10 x OEL of mist, vapors, or spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

**General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.

**Section 9: Physical and Chemical Properties**

<b>Physical State</b>	Liquid, in aerosol format	<b>Lower Flammability Limit</b> <sup>a)</sup>	1%
<b>Appearance</b>	Not available	<b>Upper Flammability Limit</b> <sup>a)</sup>	13%
<b>Odor</b>	Ethereal	<b>Vapor Pressure @20 °C</b> <sup>b)</sup>	~131 hPa [~98 mmHg]
<b>Odor Threshold</b>	Not available	<b>Vapor Density</b>	>2 (Air =1)
<b>pH</b>	Not available	<b>Relative Density @25 °C</b>	0.86
<b>Freezing/Melting Point</b>	Not available	<b>Solubility in Water</b>	Partially soluble
<b>Initial Boiling Point</b> <sup>a)</sup>	≥56 °C [≥132 °F]	<b>Partition Coefficient n-octanol/water</b>	Not available
<b>Flash Point</b> <sup>a)</sup>	-17 °C [-1.4 °F]	<b>Auto-ignition Temperature</b> <sup>c)</sup>	≥330 °C [≥626 °F]
<b>Evaporation Rate</b>	fast	<b>Decomposition Temperature</b>	Not available
<b>Flammability</b>	Not available	<b>Viscosity @40 °C</b>	<20.5 mm <sup>2</sup> /s

a) Values based on acetone component.

b) Calculated based on volatile liquid components.

c) Values based on 2-methoxy-1-methylethyl acetate

**Section 10: Stability and Reactivity**

<b>Reactivity</b>	Not available
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures
<b>Conditions to Avoid</b>	Temperatures above 50 °C [122 °F], open flames, and incompatible substances
<b>Incompatibilities</b>	Oxidizing agents, strong acids, strong bases, alkali, alkali metals, peroxides, halogens, vinyl chloride, and iodine pentafluoride
<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5

**Section 11: Toxicological Information**
**Summary of Effects and Symptoms by Routes of Exposure**

<b>Ingestion</b>	May cause nausea, sore throat, and diarrhea (see inhalation symptoms).
<b>Inhalation</b>	May cause drowsiness, dizziness, cough, headaches, nausea, or unconsciousness.
<b>Eyes</b>	May cause redness and severe irritation
<b>Skin</b>	May cause skin redness, irritation, and dry skin.
<b>Chronic</b>	Prolonged or repeated exposure may cause skin dryness, cracking, as well as defatting the skin.  Ingestion or inhalation of paint material, mist, or vapor during pregnancy may increase the chances fetal death and developmental defects.

**Acute Toxicity (Lethal Exposure Concentrations)**

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
trans-1,3,3,3-tetrafluoroprop-1-ene	Not available	Not available	>207 000 ppm 4 h Rat <sup>a)</sup>
acetone	5 800 mg/kg Rat	20 mL/kg Rabbit <sup>a)</sup>	16 000 ppm 6 h Rat
toluene	636 mg/kg Rat	12 124 mg/kg Rabbit	49 g/m <sup>3</sup> 4h Rat
titanium dioxide	5 000 mg/kg Rat	Not available	5 g/L 4 h Rat
isobutyl acetate	13 400 mg/kg Rat	>17 400 mg/kg Rabbit	>13.24 mg/L 6 h Rat
heptan-2-one	1 670 mg/kg Rat	12 600 µL/kg Rabbit	Not available
ethanol	7 060 mg/kg Rat	Not available	20 000 ppm 10 h Rat

*Section continued on the next page*

**XS1952-ZE**
**TOUCH UP SPRAY PAINT—HIGH HIDE FAST DRY (AEROSOL)**
*Continued...*

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
1-methoxy-2-propanol acetate	8 532 mg/kg Rat	>5 g/kg Rabbit	Not available
ethyl acetate	5 620 mg/kg Rat	>20 000 µL/kg Rabbit	45 g/m <sup>3</sup> 2 h Mouse
propan-2-ol	5 000 mg/kg Rat	12 8000 mg/kg Rabbit	24.6 mg/L 6 h Rat
benzyl butyl phthalate	Not available	Not available	Not available
xylene	4 350 mg/kg Rat	>1 700 mg/kg Rabbit	5 000 ppm 4 h Rat
ethylbenzene	3 500 mg/kg Rat	>5 000 mg/kg Rabbit	35 500 mg/m <sup>3</sup> 2 h Mouse

*Note:* Toxicity data from the RTECS<sup>2</sup> and ECHA databases were consulted. The data from supplier (M)SDSs were also consulted.

a) According to supplier safety data sheet.

### Other Toxicological Effects

**Skin corrosion/irritation**

Toluene and xylenes causes skin irritation based on Draize tests on animals.

**Serious eye damage/irritation**

Acetone, ethanol, ethyl acetate, propan-2-ol, and xylene are known serious eye irritants.

**Sensitization**  
(allergic reactions)

Based on available data, the classification criteria are not met.

*Section continued on the next page*

**XS1952-ZE****TOUCH UP SPRAY PAINT—HIGH HIDE FAST DRY (AEROSOL)****Carcinogenicity**  
(risk of cancer)

The titanium dioxide is possibly carcinogenic by airborne routes of exposures under WHMIS.

**Titanium Dioxide [13463-67-7]**

IARC Group 2B: Possibly carcinogenic to humans

ACGIH A4: Not classified as a human carcinogen

CA Prop 65: Listed as a carcinogen (airborne, as unbound particles of respirable size)

NTP: Not listed

**Ethanol [64-17-5]**

IARC Group 1: Carcinogenic to human when consumed as beverage.

ACGIH A3: Confirmed animal carcinogen with unknown relevance to humans

CA Prop 65: Listed as a carcinogen when consumed as a beverage

NTP: Not listed

**Ethylbenzene [100-41-4]**

IARC Group 2B: Possibly carcinogenic to humans

ACGIH A3: Confirmed animal carcinogen with unknown relevance to humans

CA Prop 65: Listed as a carcinogen

NTP: Not listed

**Mutagenicity**  
(risk of heritable genetic effects)

Based on available data, the classification criteria are not met.

**Reproductive Toxicity**  
(risk to sex functions)

Benzyl butyl phthalate is classified as a 1B reproductive toxicant in ECHA Annex IV. At high doses, spermatogenesis was observed in male rat by inhalation of toluene.

**Teratogenicity** (risk of fetus malformation)

Fetotoxicity is observed in animal studies for inhalation and oral exposures for toluene. Extreme consumption of ethanol also presents risks for the newborn.

*Section continued on the next page*

**XS1952-ZE****TOUCH UP SPRAY PAINT—HIGH HIDE FAST DRY (AEROSOL)****STOT-single exposure**

Acetone, toluene, 1-methoxy-2-propanol acetate, isobutyl acetate, heptan-2-one, ethyl acetate, and xylenes can affect the central nervous system by inhalation causing drowsiness or dizziness.

**STOT-repeated exposure**

Contains toluene, which is a Cat 2 STOT repeated exposure hazard for the central nervous system and cochlear systems.

Toluene and xylenes are ototoxic chemicals according to rat studies: inhalation exposure in the presence of noise may lead to cochlear impairment.

**Aspiration hazard**

The liquid is content is classified as Cat 1 aspiration hazards. It is composed of >10% Cat 1 substances, and the kinematic viscosity is <20.5 mm<sup>2</sup>/s at 40 °C.

**Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Acetone is not classifiable as an aquatic toxicant. It has a minimal LC50 96 h of 5 540 mg/L for *Oncorhynchus mykiss* (rainbow trout); EC50 48 h of 13 500 mg/L *Daphnia magna* (water flea).

Toluene is an acute category 2 aquatic toxicant. It has a minimal LC50 96 h of 7.63 mg/L for *Oncorhynchus mykiss* (rainbow trout); EC50 24 h of 8.9 mg/L *Daphnia magna* (water flea); and EC50 24 h of 10 mg/L *Pseudokirchneriella subcapitata* (green algae).

The 1-methoxy-2-propanol acetate component is an acute category 3 aquatic toxicant. It has a minimal LC50 96 h of ≥100 mg/L *Oncorhynchus mykiss* (rainbow trout).

Benzyl butyl phthalate is an acute category 1 and a chronic category 1 toxicant.

Isobutyl acetate, heptan-2-one, ethanol, ethyl acetate, and titanium dioxide are not classifiable as an environmental toxicant with minimal LC50 of >100 mg/L.

- Heptan-2-one has a minimal LC50 96 h of 126 mg/L for *Pimephales promelas* (fathead minnow).
- Ethanol is biodegradable and has minimal LC50 of 12 000 mg/L 96 h for *Oncorhynchus mykiss* (rainbow trout) and 5 770 mg/L for *Pimephales promelas* (fathead minnow); and an LC50 24 h of 5 012 mg/L for *Ceriodaphnia* spp (water flea).
- Ethyl acetate is biodegradable and has a minimal LC50 96 h of 220 mg/L for *Pimephales promelas* (fathead minnow); LC50 24 h of 560 mg/L and an EC50 48 h of 2 300 mg/L for *Daphnia magna* (water flea); and an EC50 72 h of 1 800 mg/L for *Selenastrum* (green algae).

*Section continued on the next page*

**XS1952-ZE TOUCH UP SPRAY PAINT—HIGH HIDE FAST DRY (AEROSOL)****Acute Ecotoxicity**

Harmful to aquatic life

**Chronic Ecotoxicity**

Harmful to aquatic life with long lasting effects

Avoid release to the environment.

**Biodegradability**

Expected to be biodegradable. The volatile solvent constituents will oxidize rapidly in air by photochemical reaction.

**Other Effects**

Actual VOC (Volatile Organic Compounds) content according to the US (EPA) and Canadian (CEPA) authorities.

Actual volatile organic compound (VOC) content = 21% [222 g/L]

**Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, national, and international regulations.

**Section 14: Transport Information****Ground****Refer to TDG** (Canadian Transportation of Dangerous Goods regulations) and **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.****Limited Quantity***Section continued on the next page*



XS1952-ZE

TOUCH UP SPRAY PAINT—HIGH HIDE FAST DRY (AEROSOL)

**Air****Refer to ICAO-IATA Dangerous Goods Regulations.****Limited Quantity**Max Net Qty/Pkg =  
30 kg Gross**UN number:** UN1950**Shipping Name:**

AEROSOLS, flammable

**Class:** 2.1**Packing Group:** Not applicable

Marine Pollutant: No

**Sea****Refer to IMDG regulations.****Limited Quantity****UN number:** UN1950**Shipping Name:**

AEROSOLS, flammable

**Class:** 2.1**Packing Group:** Not applicable

Marine Pollutant: No

**Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.**

**Section 15: Regulatory Information****Canada****Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL.

**Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

*Section continued on the next page*

**XS1952-ZE TOUCH UP SPRAY PAINT—HIGH HIDE FAST DRY (AEROSOL)**


**USA**

**Other Classifications**

**HMIS® RATING**

<b>HEALTH:</b>	<b>* 2</b>
<b>FLAMMABILITY:</b>	<b>3</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	

**NFPA® 704 CODES**



*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

**CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product contains toluene, xylene, and ethylbenzene which are listed as hazardous air pollutants.

**EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains ethylbenzene (CAS# 100-41-4; reportable quantity = 1 000 lb), toluene (CAS# 108-88-3; reportable quantity = 1 000 lb), and xylene (CAS# 1330-20-7, reportable quantity = 100 lb), which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

This product contains acetone (CAS# 67-64-1), isobutyl acetate (CAS# 110-19-0) and ethyl acetate (CAS# 141-78-6), which are subject to the CERCLA reporting requirements at the 5 000 lb (2 268 kg) threshold.

**TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

*Section continued on the next page*

**XS1952-ZE TOUCH UP SPRAY PAINT—HIGH HIDE FAST DRY (AEROSOL)**

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity, USA).

This product contains toluene, which is listed as reproductively toxic in California.

This product contains ethylbenzene, which is listed as a carcinogen in California.

This product contains ethanol, which is listed as reproductively toxic and as a carcinogen when in an alcoholic beverage.

This product contains titanium dioxide, which is listed as a carcinogenic substance when airborne, as unbound particles of respirable size.

**Europe**

**RoHS** (Restriction of Hazardous Substances Directive)

This product contains benzyl butyl phthalate and is therefore subject to restricted uses with respect to the RoHS directive.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

**Section 16: Other Information**

<b>SDS Prepared by</b>	Regulatory Department
<b>Date of Review</b>	01 March 2020
<b>Supersedes</b>	15 May 2018
<b>Reason for Changes:</b>	Change of emergency phone numbers.

**Reference**

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

*Section continued on the next page*

**XS1952-ZE****TOUCH UP SPRAY PAINT—HIGH HIDE FAST DRY (AEROSOL)****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

**Mailing Addresses** *Manufacturing & Support*  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

*Head Office*  
9347–193rd Street  
Surrey, British Columbia, Canada  
V4N 4E7

**Disclaimer**

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.