(R) Chemicals ISO 9001 Registered Quality System. Burlington, Ontario, Canada QMI File # 004008

Electrosolve[™] Contact Cleaner 409B Technical Data Sheet

409B-Aerosol

Description

The 409B *Electrosolve™ Contact Cleaner* is a very fast drying and zero residue contact cleaner. It is effective at dissolving oils and non-polar residues, and for assisting with the removal of oxidation using a brush. It cleans connectors, contacts, circuit breakers, microprocessors, and LED and PCB components.

Features and Benefits

- Suitable for Use in Food Facilities as a Non-Food Chemical—Canadian and NFS recognition letters available on request
- Safe on many plastics
- · Zero residue
- Fast evaporation rate
- Dissolves oils and residues
- RoHS compliant

ATTENTION!

Do NOT use on live circuits.

For use on equipment that will not tolerate aqueous cleaning solutions. Not for use in direct contact with food.

Usage Parameters

| Properties | Value |
|------------|-------|
| Shelf Life | 5 y |

Temperature Ranges

| Properties | Value |
|----------------------|----------------|
| Storage Temperature | -20 to 40 °C |
| Limits ^{a)} | [-4 to 104 °F] |

a) Storage below zero is not necessary. Cool, dry, and well ventilated area recommended.

Properties

| Physical Properties | Method | Value |
|--------------------------------|----------------|--------------------------------|
| High Purity | | No residue |
| Color | | Clear |
| Odor | _ | Mild hydrocarbon |
| Density @25°C [77 °F] | | 0.66 g/mL |
| Viscosity @25°C [77 °F] | Brookfield SP1 | 0.3 cP [0.0003 Pa·s] |
| Flash Point | Closed Cup | -29 °C [-20 °F] |
| Boiling Point | - | 52 °C [126 °F] |
| Vapor Pressure @25°C [77 °F] | | 33 kPa [250 mmHg] |
| Relative Evaporation Rate | | 0.8 (Ether = 1); 9.4 (ButAc=1) |
| Volatile Organic Content (VOC) | | 100% |
| | | |



Electrosolve[™] Contact Cleaner 409B Technical Data Sheet

409B-Aerosol

| Solvation Parameters Solubility in Water KB (Kauri Butanol) Value | Value Insoluble 30 | |
|---|--|---|
| Hansen Solubility Parameters ^{a)} Total Non-Polar Polar Hydrogen Bonding | (MPa) ^{1/2} 14.9 14.9 0.0 0.0 | [cal/cm ³] ^½ 7.28 7.00 0.0 |

a) Hansen parameters calculate using component literature values and volume fraction composition.

Compatibility

Substrate Compatibility: Consult 409B partial compatibility chart table for substrate compatibility. It is always recommended to perform a compatibility test on a non-critical test area prior to large scale applications. Perform this test even if the chart predicts high compatibility since modern plastic parts may incorporated hidden incompatible materials in the form of plastic blends or as protective and decorative coatings.

Compatibility Chart

| Plastic type | Resistance |
|--------------------------------------|------------|
| Epoxy | Very Good |
| ABS (acrylonitrile butadiene styrene | Poor |
| PMMA (Acrylic) | Good |
| PVC (Polyvinyl chloride) | Good |
| HD-PE (high density polyethylene) | Good |
| LD-PE (low density polyethylene) | Partial |
| PP (polypropylene) | Good |
| PS (polystyrene) | Partial |
| PC (Polycarbonate) | Poor |
| | |

ATTENTION!

Use with care on thin plastics or near parts that are chemically sensitive.

Solvent Miscibility: The 409B is generally miscible organic solvent, but it is immiscible with water.

ISO 9001 Registered Quality System. Rurlington, Ontario, Canada QMI File # 004008

Electrosolve[™] Contact Cleaner 409B Technical Data Sheet

409B-Aerosol

Health, Safety, and Environmental Awareness

Please see the 409B **Safety Data Sheet** (SDS) for more details on transportation, storage, handling and other security guidelines.

Health and Safety: This liquid is highly flammable and should be kept away from flames and other ignition sources. Avoid breathing in fumes or direct contact with the material.

HMIS® RATING

| HEALTH: | * | 2 |
|----------------------|---|---|
| FLAMMABILITY: | | 3 |
| PHYSICAL HAZARD: | | 0 |
| PERSONAL PROTECTION: | | |

2 0

NFPA® 704 CODES

Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

Environmental Impact: It is RoHS compliant.

Application Instructions

To clean residues in aerosol format

- 1. Spray dirty area.
- 2. Ensure that wash runs off the circuit board along the shortest unencumbered path to prevent redeposit of solvated residues

Packaging and Supporting Products

| Cat. No. | Packaging | Net Volume | | Net Weight | | Packaging Weight | |
|-----------|-----------|------------|------------|------------|---------|----------------------|----------------------|
| 409B-140G | Aerosol | 188 mL | 6.35 fl oz | 140 g | 4.93 oz | 2.2 kg ^{a)} | 4.9 lb ^{a)} |
| 409B-340G | Aerosol | 457 mL | 15.4 fl oz | 340 g | 11.9 oz | 4.6 kg ^{a)} | 10 lb ^{a)} |

a) Case pack of ten

Supporting Products

Hog Hair Cleaning Brush: Cat. No. 852

• Large Hog Hair Cleaning Brush: Cat. No. 853

Chemicals ISO 9001 Registered Quality System. Burlington, Ontario, Canada QMI File # 004008

Electrosolve[™] Contact Cleaner 409B Technical Data Sheet

409B-Aerosol

Technical Support

Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Phone: +(1) 800-340-0772 (Canada, Mexico & USA)

+(1) 905-331-1396 (International)

Fax: +(1) 905-331-2862 or +(1) 800-340-0773

Mailing address: Manufacturing & Support Head Office

1210 Corporate Drive 9347–193rd Street

Burlington, Ontario, Canada Surrey, British Columbia, Canada

L7L 5R6 V4N 4E7

Disclaimer

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. *M.G. Chemicals Ltd.* does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.