

413C



Heavy Duty Flux Remover

413C Heavy Duty Flux Remover is specially formulated to dissolve and remove the most stubborn, encrusted, hard, baked-on fluxes and residues left on parts after soldering. It penetrates quickly to remove non-ionic and ionic contaminants left on the non-component sides of circuit boards. It can also work aggressively on isolated and hard-to-reach areas that require spot cleaning. It is also available in aerosol format.

413C is the best flux cleaner for removing rosin, non-rosin, no-clean fluxes, non-ionic and ionic contamination.

For plastic safe versions, visit 4050A and 4140A flux removers.

Features & Benefits

RoHS Compliant

Quickly dissolves burnt-on flux

Fast dry time

Zero residue

Storage and Handling

Store between 4 and 27 °C in a dry area, away from sunlight. Store in well-ventilated places (see SDS).

Properties

Density @ 25 °C	0.8 g/mL
Viscosity @ 25 °C	<20.5 mm ² /s
Flash Point	11 °C
Boiling Point	83 °C
Auto-ignition Temperature	456 °C
Water Miscibility	Miscible
Shelf Life	5 y



Available Packaging

Part #	Packaging	Net Vol.	Net Wt.
413C-1L	Bottle	945 mL	793 g

Disclaimer: This information is believed to be accurate. It is intended for professional end-users who have the skills required to evaluate and use the data properly. M.G. Chemicals Ltd. does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

MG Chemicals 1210 Corporate Drive Burlington, Ontario, Canada L7L 5R6 ISO 9001:2015 Quality Management System SAI Global File: 004008 support@mgchemicals.com **North America** +(1) 800-340-0772 **International** +(1) 905-331-1396 **Europe** +44 1663 362888 10 September 2025 / Ver. 2.0